

PDSP16318/PDSP16318A

COMPLEX ACCUMULATOR

(Supersedes version in December 1993 Digital Video & Video Digital Signal Processing IC Handbook, HB3923-1)

The PDSP16318 contains two independent 20-bit Adder/Subtractors combined with accumulator registers and shift structures. The four port architecture permits full 20MHz throughout in FFT and filter applications.

Two PDSP16318As combined with a single PDSP16112A Complex Multiplier provide a complete arithmetic solution for a Radix 2 DIT FFT Butterfly. A new complex Butterfly result can be generated every 50ns allowing 1K complex FFTs to be executed in 256µs.

FEATURES

- Full 20MHz Throughout in FFT Applications
- Four Independent 16-bit I/O Ports
- 20-bit Addition or Accumulation
- Fully Compatible with PDSP16112 Complex Multiplier
- On Chip Shift Structures for Result Scaling
- Overflow Detection
- Independent Three-State Outputs and Clock Enables for 2 Port 20MHz Operation
- 1.4 micron CMOS
- 500mW Maximum Power Dissipation
- 84 Pin PGA or QFP packages




Fig.1 Pin connections - bottom view (AC84 - PGA)

APPLICATIONS

- High speed Complex FFT or DFTs
- Complex Finite Impulse Response (FIR) Filtering
- Complex Conjugation
- Complex Correlation/Convolution

ASSOCIATED PRODUCTS

- PDSP16112** 16 x 12 Complex Multiplier
- PDSP16116** 16 x 16 Complex Multiplier
- PDSP1601** ALU and Barrel Shifter
- PDSP16330** Pythagoras Processor




Fig. 2 PDSP16318 simplified block diagram




Fig. 3 Block diagram

FUNCTIONAL DESCRIPTION

The PDSP16318 is a Dual 20-bit Adder/Subtractor configured to support Complex Arithmetic. The device may be used with each of the adders allocated to real or imaginary data (e.g. Complex Conjugation), the entire device allocated to Real or Imaginary Data (e.g. Radix 2 Butterflies) or each of the adders configured as accumulators and allocated to real or imaginary data (Complex Filters). Each of these modes ensures that a full 20MHz throughput is maintained through both adders, the first and last mode illustrating true Complex operation, where both real and imaginary data is handled by the single device.

Both Adder/Subtractors may be controlled independently via the ASR and ASI inputs. These controls permit $A + B$, $A - B$, $B - A$ or pass A operations, where the A input to the Adder is derived from the input multiplexer. The CLR control line allows the clearing of both accumulator registers. The two multiplexers may be controlled via the MS inputs, to select either new input data, or fed-back data from

the accumulator registers. The PDSP16318 contains an 8-cycle deskew register selected via the DEL control. This deskew register is used in FFT applications to ensure correct phasing of data that has not passed through the PDSP16112 Complex Multiplier.

The 16-bit outputs from the PDSP16318 are derived from the 20-bit result generated by the Adders. The three bit S2:0 input selects eight different shifted output formats ranging from the most significant 16 bits of the 20-bit data, to the least significant 13 bits of the 20-bit data. In this mode the 14th, 15th and 16th bits of the output are set to zero. The shift selected is applied to both adder outputs, and determines the function of the OVR flag. The OVR flag becomes active when either of the two adders produces a result that has more significant digits than the MSB of the 16-bit output from the device. In this manner all cases when invalid data appears on the output are flagged.

Symbol	Type	Description
A15:0	Input	Data presented to this input is loaded into the input register on the rising edge of CLK. A15 is the MSB.
B15:0	Input	Data presented to this input is loaded into the input register on the rising edge of CLK. B15 is the MSB and has the same weighting as A15.
C15:0	Output	New data appears on this output after the rising edge of CLK. C15 is the MSB.
D15:0	Output	New data appears on this output after the rising edge of CLK. C15 is the MSB.
CLK	Input	Common Clock to all internal registers
<u>CEA</u>	Input	Clock enable: when low the clock to the A input register is enabled.
<u>CEB</u>	Input	Clock enable: when low the clock to the B input register is enabled.
<u>OEC</u>	Input	Output enable: Asynchronous 3-state output control: The C outputs are in a high impedance state when this input is high.
<u>OED</u>	Input	Output enable: Asynchronous 3-state output control: The D outputs are in a high impedance state when this input is high.
OVR	Output	Overflow flag: This flag will go high in any cycle during which either the output data overflows the number range selected or either of the adder results overflow. A new OVR appears after the rising edge of the CLK.
ASR1:0	Input	Add/subtract Real: Control input for the 'Real' adder. This input is latched by the rising edge of clock.
ASI1:0	Input	Add/subtract Imag: Control input for the 'Imag' adder. This input is latched by the rising edge of clock.
<u>CLR</u>	Input	Accumulator Clear: Common accumulator clear for both Adder/Subtractor units. This input is latched by the rising edge of CLK.
MS	Input	Mux select: Control input for both adder multiplexers. This input is latched by the rising edge of CLK. When high the feedback path is selected.
S2:0	Input	Scaling control: This input selects the 16-bit field from the 20-bit adder result that is routed to the outputs. This input is latched by the rising edge of CLK.
DEL	Input	Delay Control: This input selects the delayed input to the real adder for operations involving the PDSP16112. This input is latched by the rising edge of CLK.
VCC	Power	+5V supply: Both Vcc pins must be connected.
GND	Ground	0V supply: Both GND pins must be connected.

GG pin	AC pin	Function	GG pin	AC pin	Function	GG pin	AC pin	Function	GG pin	AC pin	Function
77	B2	D7	6	K2	C7	31	K10	A1	56	B10	B10
82	C2	D8	7	K3	C6	32	J10	A2	57	B9	B9
83	B1	D9	8	L2	C5	33	K11	A3	58	A10	B8
84	C1	D10	9	L3	C4	34	J11	A4	59	A9	B7
85	D2	GND	10	K4	C3	35	H10	A5	60	B8	B6
86	D1	VCC	11	L4	C2	36	H11	A6	61	A8	B5
87	E3	D11	12	J5	C1	37	F10	A7	62	B6	B4
88	E2	D12	13	K5	C0	38	G10	A8	63	B7	B3
89	E1	D13	14	L5	<u>OED</u>	39	G11	A9	64	A7	B2
90	F2	D14	15	K6	<u>OEC</u>	40	G9	A10	65	C7	B1
91	F3	D15	16	J6	S2	41	F9	A11	66	C6	B0
92	G3	C15	17	J7	S1	42	F11	A12	67	A6	CLK
93	G1	C14	18	L7	S0	43	E11	A13	68	A5	<u>CEB</u>
94	G2	C13	19	K7	MS	44	E10	A14	69	B5	OVR
95	F1	C12	20	L6	AS11	45	E9	A15	70	C5	D0
96	H1	VCC	21	L8	AS10	46	D11	<u>CEA</u>	71	A4	D1
97	H2	GND	22	K8	DEL	47	D10	B15	72	B4	D2
98	J1	C11	23	L9	<u>CLR</u>	48	C11	B14	73	A3	D3
99	K1	C10	24	L10	ASR1	49	B11	B13	74	A2	D4
100	J2	C9	25	K9	ASR0	50	C10	B12	75	B3	D5
5	L1	C8	26	L11	A0	51	A11	B11	76	A1	D6

Device Pinout for ceramic 84 - pin PGA (AC84) and ceramic QFP (GG100)

PDSP16318/16318A

ASR or ASI		ALU Function
ASX1	ASX0	
0	0	A + B
0	1	A
1	0	A - B
1	1	B - A

DEL	Delay Mux Control
0	A port input
1	Delayed A port input

MS	Real and Imag' Mux Control
0	B port input/Del mux output
1	C accumulator/D accumulator

S2:0			Adder result																				
S2	S1	S0	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	
0	0	0	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0					
0	0	1			15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0			
0	1	0				15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0		
0	1	1					15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	
1	0	0						15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	0	1							15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
1	1	0								15	14	13	12	11	10	9	8	7	6	5	4	3	2
1	1	1									15	14	13	12	11	10	9	8	7	6	5	4	3

NOTE

This table shows the portion of the adder result passed to the D15:0 and C15:0 outputs. Where fewer than 16 adder bits are selected the output data is padded with zeros.

ABSOLUTE MAXIMUM RATINGS (Note 1)






Supply voltage V_{CC}	-0.5V to 7.0V
Input voltage V_{IN}	-0.9V to $V_{CC} + 0.9V$
Output voltage V_{OUT}	-0.9V to $V_{CC} + 0.9V$
Clamp diode current per pin I_k (see Note 2)	18mA
Static discharge voltage (HMB) V_{STAT}	500V
Storage temperature range T_s	-65°C to +150°C
Ambient temperature with power applied T_{amb}	
Industrial	-40°C to +85°C
Military	-55°C to +125°C
Junction temperature	150°C
Package power dissipation P_{TOT}	1000mW

THERMAL CHARACTERISTICS

Package Type	θ_{JC} °C/W	θ_{JA} °C/W
LC	12	35
AC	12	36

NOTES

- Exceeding these ratings may cause permanent damage. Functional operation under these conditions is not implied.
- Maximum dissipation or 1 second should not be exceeded, only one output to be tested at any one time.
- Exposure to absolute maximum ratings for extended periods may affect device reliability.

Test	Waveform - measurement level
Delay from output high to output high impedance	
Delay from output low to output high impedance	
Delay from output high impedance to Output low	
Delay from output high impedance to Output high	
NOTES 1. V_H - Voltage reached when output driven high 2. V_L - Voltage reached when output driven low 	

PDSP16318/16318A

ELECTRICAL CHARACTERISTICS

Test conditions (unless otherwise stated):

T_{amb} (Commercial) = 0°C to +70°C, $V_{CC} = 5.0V \pm 5\%$, GND = 0V

T_{amb} (Industrial) = -40°C to +85°C, $V_{CC} = 5.0V \pm 10\%$, GND = 0V

T_{amb} (Military) = -55°C to +125°C, $V_{CC} = 5.0V \pm 10\%$, GND = 0V

STATIC CHARACTERISTICS

Characteristic	Symbol	Value			Units	Conditions
		Min.	Typ.	Max.		
Output high voltage	V_{OH}	2.4		-	V	$I_{OH} = 3.2mA$ $I_{OL} = -3.2mA$
Output low voltage	V_{OL}	-		0.4	V	
Input high voltage	V_{IH}	3.5		-	V	$GND \leq V_{IN} \leq V_{CC}$ $GND \leq V_{OUT} \leq V_{CC}$ $V_{CC} = \text{Max}$
Input low voltage	V_{IL}	-		0.5	V	
Input leakage current	I_{IL}	-10		+10	μA	
Output leakage current	I_{OZ}	-50	-	+50	μA	
Output SC current	I_{OS}	20	-	200	mA	
Input capacitance	C_{IN}	-	9	-	pF	

SWITCHING CHARACTERISTICS

Characteristic	Value Industrial + Commercial				Value Military		Units	Conditions
	PDSP16318 PDSP16318A				PDSP16318			
	Min.	Max.	Min.	Max.	Min.	Max.		
Clock period	100	-	50	-	100	-	ns	2 x LSTTL + 20pF 2 x LSTTL + 20pF 2 x LSTTL + 20pF 2 x LSTTL + 20pF V _{CC} = max, TTL input levels Outputs unloaded, f _{CLK} = max
Clock High Time	20	-	15	-	20	-	ns	
Clock Low Time	20	-	15	-	20	-	ns	
A15:0, B15:0 setup to clock rising edge	8	-	5	-	8	-	ns	
A15:0, B15:0 hold after clock rising edge	2	-	2	-	2	-	ns	
MS, S2:0, ASI setup to clock rising edge	10	-	10	-	10	-	ns	
DEL, ASR, <u>CLR</u> setup to clock rising edge	8	-	5	-	8	-	ns	
DEL, ASR, <u>CLR</u> , MS, S2:0, ASI hold after clock rising edge	2	-	2	-	2	-	ns	
<u>CEA</u> , <u>CEB</u> setup to clock falling edge	2	-	2	-	2	-	ns	
<u>CEA</u> , <u>CEB</u> hold after clock rising edge	8	-	8	-	8	-	ns	
Clock rising edge to OVR, C15:0, D15:0	5	40	5	30	5	40	ns	
<u>OEC/OED</u> low to C15:0/D15:0 high data valid	-	40	-	30	-	40	ns	
<u>OEC/OED</u> low to C15:0/D15:0 low data valid	-	40	-	30	-	40	ns	
<u>OEC/OED</u> high to C15:0/D15:0 high impedance	-	40	-	30	-	40	ns	
Vcc current	-	70	-	110	-	70	mA	
Vcc current	-	30	-	60	-	30	mA	V _{CC} = max, CMOS input levels Outputs unloaded, f _{CLK} = max

NOTES

1. LSTTL is equivalent to $I_{OH} = 20$ microamps, $I_{OL} = -0.4mA$
2. Current is defined as negative into the device
3. CMOS input levels are defined as:
 $V_{IL} = 0.5$
 $V_{IH} = V_{DD} - 0.5$

ORDERING INFORMATION

Comercial (0°C to +70°C)

PDSP16318/C0/AC	(10MHz - PGA)
PDSP16318/C0/GG	(10MHz - QFP)
PDSP16318A/C0/AC	(20MHz - PGA)
PDSP16318A/C0/GG	(20MHz - QFP)

Industrial (-40°C to +85°C)

PDSP16318/B0/AC	(10MHz - PGA)
PDSP16318/B0/GG	(10MHz - QFP)
PDSP16318A/B0/AC	(20MHz - PGA)
PDSP16318A/B0/GG	(20MHz - QFP)

Military (-55°C to +125°C)

PDSP16318/A0/AC	(10MHz - PGA)
PDSP16318/A0/GG	(10MHz - QFP)
PDSP16318A/A0/AC	(20MHz - PGA)
PDSP16318A/A0/GG	(20MHz - QFP)

Call for availability on High Reliability parts and MIL 883C screening.



HEADQUARTERS OPERATIONS
GEC PLESSEY SEMICONDUCTORS
Cheney Manor, Swindon,
Wiltshire SN2 2QW, United Kingdom.
Tel: (0793) 518000
Fax: (0793) 518411

GEC PLESSEY SEMICONDUCTORS
P.O. Box 660017
1500 Green Hills Road,
Scotts Valley, California 95067-0017,
United States of America.
Tel: (408) 438 2900
Fax: (408) 438 5576

CUSTOMER SERVICE CENTRES

- **FRANCE & BENELUX** Les Ulis Cedex Tel: (1) 64 46 23 45 Tx: 602858F
Fax : (1) 64 46 06 07
- **GERMANY** Munich Tel: (089) 3609 06-0 Tx: 523980 Fax : (089) 3609 06-55
- **ITALY** Milan Tel: (02) 66040867 Fax: (02) 66040993
- **JAPAN** Tokyo Tel: (03) 3296-0281 Fax: (03) 3296-0228
- **NORTH AMERICA Integrated Circuits and Microwave Products** Scotts Valley, USA
Tel (408) 438 2900 Fax: (408) 438 7023.
Hybrid Products, Farmingdale, USA Tel (516) 293 8686
Fax: (516) 293 0061.
- **SOUTH EAST ASIA** Singapore Tel: (65) 3827708 Fax: (65) 3828872
- **SWEDEN** Stockholm, Tel: 46 8 702 97 70 Fax: 46 8 640 47 36
- **UNITED KINGDOM & SCANDINAVIA**
Swindon Tel: (0793) 518510 Tx: 444410 Fax : (0793) 518582

These are supported by Agents and Distributors in major countries world-wide.

© GEC Plessey Semiconductors 1995 Publication No. DS3708 Issue No. 2.1 February 1995

This publication is issued to provide information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose nor form part of any order or contract nor to be regarded as a representation relating to the products or services concerned. No warranty or guarantee express or implied is made regarding the capability, performance or suitability of any product or service. The Company reserves the right to alter without prior knowledge the specification, design or price of any product or service. Information concerning possible methods of use is provided as a guide only and does not constitute any guarantee that such methods of use will be satisfactory in a specific piece of equipment. It is the user's responsibility to fully determine the performance and suitability of any equipment using such information and to ensure that any publication or data used is up to date and has not been superseded. These products are not suitable for use in any medical products whose failure to perform may result in significant injury or death to the user. All products and materials are sold and services provided subject to the Company's conditions of sale, which are available on request.