

SP8782A & B

1GHz ÷16/17, ÷32/33 MULTI-MODULUS DIVIDER

The SP8782 is a multi-modulus divider which divides by 16/17 when the Ratio Select input is low and by 32/33 when the Ratio Select input is high. When high, the Modulus Control input selects the lower division ratio (16 or 32) and the higher ratio (17 or 33) when it is low.

The device uses resynchronisation techniques to reduce the effects of propagation delays in frequency synthesis.

The SP8782A (ceramic DIL package) is characterised over the full military temperature range of -55°C to $+125^{\circ}\text{C}$, the SP8782B (miniature plastic DIL package) over the industrial range of -40°C to $+85^{\circ}\text{C}$.

FEATURES

- Advanced Resynchronisation Techniques to Negate Loop Delay Effects
- CMOS Compatible Output Capability
- Multi-Modulus Division

QUICK REFERENCE DATA

- Supply Voltage Range: 4V to 5.5V
- Full Military Temperature Range:
 -55°C to $+125^{\circ}\text{C}$ (SP8782A)

ORDERING INFORMATION

SP8782 A DG
SP8782 B MP
DES9208921/AC/DG (SMD)




Fig. 1 Pin connections - top view (not to scale)

ABSOLUTE MAXIMUM RATINGS

Supply voltage	6V
Clock input level	2.5V p-p
Junction temperature	+175°C
Storage temperature range:	
SP8782A	-55°C to $+150^{\circ}\text{C}$
SP8782B	-55°C to $+125^{\circ}\text{C}$




Fig. 2 Functional diagram

ELECTRICAL CHARACTERISTICS

Unless otherwise stated, the Electrical Characteristics are guaranteed over specified supply, frequency and temperature range

Supply voltage, $V_{CC} = +4V$ to $+5.5V$, $V_{EE} = 0V$

Temperature, $T_{AMB} = -55^{\circ}C$ to $+125^{\circ}C$ (SP8782A), $-40^{\circ}C$ to $+85^{\circ}C$ (SP8782B)

Characteristic	Pin	Value		Units	Conditions
		Min.	Max.		
Maximum frequency (sinewave input)	2, 3	1		GHz	Input = 200-1200mV p-p
Minimum frequency (sinewave input)	2, 3		50	MHz	Input = 400-1200mV p-p
Min slew rate for low frequency operation	2, 3		100	V/ μ s	
Power supply current, I_{CC}	8		60	mA	Output unloaded, $V_{CC} = 5.5V$
Output low voltage	7	0	1.7	V	
Output high voltage	7	$V_{CC}-1.4$	V_{CC}	V	
Modulus control input high voltage	5	$0.7V_{CC}$	V_{CC}	V	At driver end of 3kW resistor
Modulus control input low voltage	5	0	$0.3V_{CC}$	V	At driver end of 3kW resistor
Modulus control input high current	5	0.6	1.2	mA	Via 3kW resistor to V_{CC}
Modulus control input low current	5	-0.6	-1.2	mA	Via 3kW resistor to V_{CC}
Ratio select input high voltage	1	$0.6V_{CC}$	V_{CC}	V	
Ratio select input low voltage	1	0	$0.4V_{CC}$	V	
Ratio select input current	1	-10	10	μ A	
Clock to output propagation delay	2, 3, 7		3	ns	
Set-up time, t_s	5, 7	3		ns	See note 1 and Fig. 3a
Release time, t_r	5, 7	3		ns	See note 2 and Fig. 3b

NOTES

1. The set-up time t_s is defined as the minimum time that can elapse between L $\rightarrow$ E/H transition of the modulus control input and the next L $\rightarrow$ E/H output transition to ensure that the $\div 16$ (32) mode is obtained.

2. The release time t_r is defined as the minimum time that can elapse between H $\rightarrow$ E/L transition of the modulus control input and the next L $\rightarrow$ E/H output transition to ensure that the $\div 17$ (33) mode is obtained.

Modulus control input	Ratio select input	
	0	1
0	$\div 17$	$\div 33$
1	$\div 16$	$\div 32$

Table 1 Truth table for control inputs




Fig. 3a Setting divide-by-16 (32) mode




Fig. 3b Setting divide-by-17 (33) mode

Fig. 3 Timing diagrams




Fig. 4 Typical input characteristics




Fig. 5 Typical application showing interfacing





Fig. 6 Typical input impedance. Test conditions: supply voltage = 5V, ambient temperature = 25°C, frequencies in MHz, Impedances normalised to 50W


PACKAGE DETAILS

Dimensions are shown thus: mm (in).



NOTES
1. Controlling dimensions are inches.
2. This package outline diagram is for guidance only. Please contact your GPS Customer Service Centre for further information.

8-LEAD CERAMIC DIL - DG8



NOTES
1. Controlling dimensions are inches.
2. This package outline diagram is for guidance only. Please contact your GPS Customer Service Centre for further information.

8-LEAD MINIATURE PLASTIC DIL - MP8



HEADQUARTERS OPERATIONS
GEC PLESSEY SEMICONDUCTORS
Cheney Manor, Swindon,
Wiltshire SN2 2QW, United Kingdom.
Tel: (01793) 518000
Fax: (01793) 518411

GEC PLESSEY SEMICONDUCTORS
P.O. Box 660017
1500 Green Hills Road,
Scotts Valley, CA95067-0017
United States of America.
Tel (408) 438 2900
Fax: (408) 438 5576

CUSTOMER SERVICE CENTRES

- **FRANCE & BENELUX** Les Ulis Cedex Tel: (1) 69 18 90 00 Fax: (1) 64 46 06 07
- **GERMANY** Munich Tel: (089) 3609 06-0 Fax: (089) 3609 06-55
- **ITALY** Milan Tel: (02) 66040867 Fax: (02) 66040993
- **JAPAN** Tokyo Tel: (3) 5276-5501 Fax: (3) 5276-5510
- **NORTH AMERICA** Scotts Valley, USA Tel: (408) 438 2900 Fax: (408) 438 7023.
- **SOUTH EAST ASIA** Singapore Tel: (65) 3827708 Fax: (65) 3828872
- **SWEDEN** Stockholm Tel: 46 8 702 97 70 Fax: 46 8 640 47 36
- **TAIWAN, ROC** Taipei Tel: 886 2 5461260 Fax: 886 2 7190260
- **UK, EIRE, DENMARK, FINLAND & NORWAY**
Swindon Tel: 01793 518527/518566 Fax: 01793 518582

These are supported by Agents and Distributors in major countries world-wide.

© GEC Plessey Semiconductors 1995 Publication No. DS3653 Issue No. 1.2 October 1995
TECHNICAL DOCUMENTATION - NOT FOR RESALE. PRINTED IN UNITED KINGDOM

This publication is issued to provide information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose nor form part of any order or contract nor to be regarded as a representation relating to the products or services concerned. No warranty or guarantee express or implied is made regarding the capability, performance or suitability of any product or service. The Company reserves the right to alter without prior notice the specification, design or price of any product or service. Information concerning possible methods of use is provided as a guide only and does not constitute any guarantee that such methods of use will be satisfactory in a specific piece of equipment. It is the user's responsibility to fully determine the performance and suitability of any equipment using such information and to ensure that any publication or data used is up to date and has not been superseded. These products are not suitable for use in any medical products whose failure to perform may result in significant injury or death to the user. All products and materials are sold and services provided subject to the Company's conditions of sale, which are available on request.