

SP8833

3.5GHz ÷ 32 FIXED MODULUS DIVIDER

The SP8833 is one of a range of very high speed low power prescalers for professional and military applications. The device features a complementary output stage with on chip current source for the emitter follower outputs.

FEATURES

- Very High Speed Operation 3.5GHz
- Silicon Technology for low Phase Noise (Typically better than -150dBc/Hz at 10kHz)
- Specified Over the Full Military Temperature Range
- Low Power Dissipation 375mW (typ)
- 5V Single Supply Operation
- High Input Sensitivity
- Very Wide Operating Frequency Range

ABSOLUTE MAXIMUM RATINGS

Supply voltage V_{CC}	6.5V
Clock Input voltage	2.5V p-p
Storage temperature range	-65°C to +150°C
Junction temperature	+175°C




Fig.1 Pin connections top view

THERMAL CHARACTERISTICS

$\theta_{JA} = 150^{\circ}\text{C/W}$

ORDERING INFORMATION

SP8833/B/DG Military temperature range




Fig.2 SP8833 Block diagram

ELECTRICAL CHARACTERISTICS

Guaranteed over the temperature range T_{amb} -40°C to +85°C and supply voltage range V_{CC} = 4.75V to 5.25V.
Tested at T_{amb} = -40°C and +85°C, V_{CC} = 4.75V and 5.25V.

Characteristic	Pin	Value			Units	Conditions
		Min	Typ	Max		
Supply current	1		78	90	mA	V_{CC} = 5V RMS sinewave measured in 50W system. See Figs. 3 & 4
Input sensitivity	2, 3			175	mV	
0.65GHz to 3.0GHz				500	mV	
3.5GHz					W	
Input impedance (series equivalent)	2, 3		50		pF	
			2			
Output Voltage with f_{in} = 650MHz	6, 7	.780	1.04	1.30	Vp-p	V_{CC} = 5V
Output Voltage with f_{in} = 3GHz	6, 7		0.95		Vp-p	V_{CC} = 5V load as Fig. 4




Fig.3 Typical input sensitivity




Fig.4 Test circuit




Fig.5 Typical input impedance





Fig.6 Typical phase noise of SP8833 at 1GHz carrier



HEADQUARTERS OPERATIONS

GEC PLESSEY SEMICONDUCTORS

Cheney Manor, Swindon,
Wiltshire SN2 2QW, United Kingdom.
Tel: (01793) 518000
Fax: (01793) 518411

GEC PLESSEY SEMICONDUCTORS

P.O. Box 660017
1500 Green Hills Road,
Scotts Valley, California 95067-0017,
United States of America.
Tel: (408) 438 2900
Fax: (408) 438 5576

CUSTOMER SERVICE CENTRES

- **FRANCE & BENELUX** Les Ulis Cedex Tel: (1) 64 46 23 45 Fax : (1) 64 46 06 07
- **GERMANY** Munich Tel: (089) 3609 06-0 Fax : (089) 3609 06-55
- **ITALY** Milan Tel: (02) 66040867 Fax: (02) 66040993
- **JAPAN** Tokyo Tel: (03) 5276-5501 Fax: (03) 5276-5510
- **NORTH AMERICA** Scotts Valley, USA Tel: (408) 438 2900 Fax: (408) 438 7023.
- **SOUTH EAST ASIA** Singapore Tel: (65) 3827708 Fax: (65) 3828872
- **SWEDEN** Stockholm Tel: 46 8 702 97 70 Fax: 46 8 640 47 36
- **TAIWAN, ROC** Taipei Tel: 886 2 5461260. Fax: 886 2 7190260
- **UK, EIRE, DENMARK, FINLAND & NORWAY**

Swindon Tel: (01793) 518510 Fax : (01793) 518582

These are supported by Agents and Distributors in major countries world-wide.

© GEC Plessey Semiconductors 1995 Publication No. DS3158 Issue No. 2.1 July 1995

TECHNICAL DOCUMENTATION - NOT FOR RESALE. PRINTED IN UNITED KINGDOM.

This publication is issued to provide information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose nor form part of any order or contract nor to be regarded as a representation relating to the products or services concerned. No warranty or guarantee express or implied is made regarding the capability, performance or suitability of any product or service. The Company reserves the right to alter without prior knowledge the specification, design or price of any product or service. Information concerning possible methods of use is provided as a guide only and does not constitute any guarantee that such methods of use will be satisfactory in a specific piece of equipment. It is the user's responsibility to fully determine the performance and suitability of any equipment using such information and to ensure that any publication or data used is up to date and has not been superseded. These products are not suitable for use in any medical products whose failure to perform may result in significant injury or death to the user. All products and materials are sold and services provided subject to the Company's conditions of sale, which are available on request.