

Advanced Power MOSFET

SSH4N80AS

FEATURES


- Avalanche Rugged Technology
- Rugged Gate Oxide Technology
- Lower Input Capacitance
- Improved Gate Charge
- Extended Safe Operating Area
- Lower Leakage Current : 25 μ A (Max.) @ $V_{DS} = 800V$
- Low $R_{DS(ON)}$: 2.450 Ω (Typ.)

$BV_{DSS} = 800 V$

$R_{DS(on)} = 3.0 \Omega$

$I_D = 4.5 A$

TO-3P



1.Gate 2.Drain 3.Source

Absolute Maximum Ratings

Symbol	Characteristic	Value	Units
V_{DSS}	Drain-to-Source Voltage	800	V
I_D	Continuous Drain Current ($T_C=25^\circ C$)	4.5	A
	Continuous Drain Current ($T_C=100^\circ C$)	2.8	
I_{DM}	Drain Current-Pulsed	18	A
V_{GS}	Gate-to-Source Voltage	± 30	V
E_{AS}	Single Pulsed Avalanche Energy	324	mJ
I_{AR}	Avalanche Current	4.5	A
E_{AR}	Repetitive Avalanche Energy	14	mJ
dv/dt	Peak Diode Recovery dv/dt	2.0	V/ns
P_D	Total Power Dissipation ($T_C=25^\circ C$)	140	W
	Linear Derating Factor	1.12	W/C
T_J, T_{STG}	Operating Junction and Storage Temperature Range	- 55 to +150	$^\circ C$
T_L	Maximum Lead Temp. for Soldering Purposes, 1/8" from case for 5-seconds	300	

Thermal Resistance

Symbol	Characteristic	Typ.	Max.	Units
$R_{\theta_{JC}}$	Junction-to-Case	--	0.89	$^\circ C/W$
$R_{\theta_{CS}}$	Case-to-Sink	0.24	--	
$R_{\theta_{JA}}$	Junction-to-Ambient	--	40	

SAMSUNG

ELECTRONICS

SSH4N80AS

N-CHANNEL
POWER MOSFET

Electrical Characteristics ($T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Characteristic	Min.	Typ.	Max.	Units	Test Condition
BV_{DSS}	Drain-Source Breakdown Voltage	800	--	--	V	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_D=250\mu\text{A}$
$\Delta \text{BV}/\Delta T_J$	Breakdown Voltage Temp. Coeff.	--	0.96	--	$\text{V}/^\circ\text{C}$	$\text{I}_D=250\mu\text{A}$ See Fig 7
$\text{V}_{\text{GS(th)}}$	Gate Threshold Voltage	2.0	--	3.5	V	$\text{V}_{\text{DS}}=5\text{V}, \text{I}_D=250\mu\text{A}$
I_{GSS}	Gate-Source Leakage , Forward	--	--	100	nA	$\text{V}_{\text{GS}}=30\text{V}$
	Gate-Source Leakage , Reverse	--	--	-100		$\text{V}_{\text{GS}}=-30\text{V}$
I_{DSS}	Drain-to-Source Leakage Current	--	--	25	μA	$\text{V}_{\text{DS}}=800\text{V}$
		--	--	250		$\text{V}_{\text{DS}}=640\text{V}, \text{T}_C=125^\circ\text{C}$
$\text{R}_{\text{DS(on)}}$	Static Drain-Source On-State Resistance	--	--	3.0	Ω	$\text{V}_{\text{GS}}=10\text{V}, \text{I}_D=0.85\text{A}$ ④*
g_{fs}	Forward Transconductance	--	3.47	--	S	$\text{V}_{\text{DS}}=50\text{V}, \text{I}_D=0.85\text{A}$ ④
C_{iss}	Input Capacitance	--	880	1140	pF	$\text{V}_{\text{GS}}=0\text{V}, \text{V}_{\text{DS}}=25\text{V}, f = 1\text{MHz}$ See Fig 5
C_{oss}	Output Capacitance	--	90	105		
C_{rss}	Reverse Transfer Capacitance	--	35	42		
$t_{\text{d(on)}}$	Turn-On Delay Time	--	19	50	ns	$\text{V}_{\text{DD}}=400\text{V}, \text{I}_D=2\text{A},$ $\text{R}_G=16 \Omega$ See Fig 13 ④ ⑤
t_r	Rise Time	--	32	75		
$t_{\text{d(off)}}$	Turn-Off Delay Time	--	67	145		
t_f	Fall Time	--	32	75		
Q_g	Total Gate Charge	--	40	52	nC	$\text{V}_{\text{DS}}=640\text{V}, \text{V}_{\text{GS}}=10\text{V},$ $\text{I}_D=2\text{A}$ See Fig 6 & Fig 12 ④ ⑤
Q_{gs}	Gate-Source Charge	--	7.3	--		
Q_{gd}	Gate-Drain("Miller") Charge	--	18.1	--		

Source-Drain Diode Ratings and Characteristics

Symbol	Characteristic	Min.	Typ.	Max.	Units	Test Condition
I_s	Continuous Source Current	--	--	4.5	A	Integral reverse pn-diode in the MOSFET
I_{SM}	Pulsed-Source Current ①	--	--	18		
V_{SD}	Diode Forward Voltage ④	--	--	1.4	V	$\text{T}_J=25^\circ\text{C}, \text{I}_s=4.5\text{A}, \text{V}_{\text{GS}}=0\text{V}$
t_{rr}	Reverse Recovery Time	--	430	--	ns	$\text{T}_J=25^\circ\text{C}, \text{I}_F=4.5\text{A}$ $d\text{I}/dt=100\text{A}/\mu\text{s}$ ④
Q_{rr}	Reverse Recovery Charge	--	4.06	--		

Notes :

“ Repetitive Rating : Pulse Width Limited by Maximum Junction Temperature

“ $L=30\text{mH}, I_{AS}=4.5\text{A}, V_{DD}=50\text{V}, R_G=27\Omega$, Starting $T_J=25^\circ\text{C}$

“ $I_{SD} \leq 4.5\text{A}, dI/dt \leq 120\text{A}/\mu\text{s}, V_{DD} \leq \text{BV}_{\text{DSS}}$, Starting $T_J=25^\circ\text{C}$

“ Pulse Test : Pulse Width = $250\mu\text{s}$, Duty Cycle $\leq 2\%$

“ Essentially Independent of Operating Temperature

**N-CHANNEL
POWER MOSFET**

SSH4N80AS

Fig 1. Output Characteristics




Fig 2. Transfer Characteristics




Fig 3. On-Resistance vs. Drain Current




Fig 4. Source-Drain Diode Forward Voltage




Fig 5. Capacitance vs. Drain-Source Voltage










Fig 6. Gate Charge vs. Gate-Source Voltage



SSH4N80AS

N-CHANNEL
POWER MOSFET



N-CHANNEL
POWER MOSFET

SSH4N80AS

Fig 12. Gate Charge Test Circuit & Waveform




Fig 13. Resistive Switching Test Circuit & Waveforms




Fig 14. Unclamped Inductive Switching Test Circuit & Waveforms




Fig 15. Peak Diode Recovery dv/dt Test Circuit & Waveforms

