

Advanced Power MOSFET


SSP7N60A

FEATURES

- Avalanche Rugged Technology
- Rugged Gate Oxide Technology
- Lower Input Capacitance
- Improved Gate Charge
- Extended Safe Operating Area
- Lower Leakage Current : 25 μ A (Max.) @ $V_{DS} = 600V$
- Lower $R_{DS(on)}$: 0.977 Ω (Typ.)

$BV_{DSS} = 600 V$
 $R_{DS(on)} = 1.2 \Omega$
 $I_D = 7 A$

TO-220



1.Gate 2. Drain 3. Source

Absolute Maximum Ratings

Symbol	Characteristic	Value	Units
V_{DSS}	Drain-to-Source Voltage	600	V
I_D	Continuous Drain Current ($T_C=25^\circ C$)	7	A
	Continuous Drain Current ($T_C=100^\circ C$)	4.4	
I_{DM}	Drain Current-Pulsed ①	28	A
V_{GS}	Gate-to-Source Voltage	± 30	V
E_{AS}	Single Pulsed Avalanche Energy ②	535	mJ
I_{AR}	Avalanche Current ①	7	A
E_{AR}	Repetitive Avalanche Energy ①	14.7	mJ
dv/dt	Peak Diode Recovery dv/dt ③	3.0	V/ns
P_D	Total Power Dissipation ($T_C=25^\circ C$)	147	W
	Linear Derating Factor	1.18	$W/\text{ }^\circ C$
T_J, T_{STG}	Operating Junction and Storage Temperature Range	- 55 to +150	$^\circ C$
	Maximum Lead Temp. for Soldering Purposes, 1/8 " from case for 5-seconds	300	

Thermal Resistance

Symbol	Characteristic	Typ.	Max.	Units
$R_{\theta JC}$	Junction-to-Case	--	0.85	$^\circ C/W$
$R_{\theta CS}$	Case-to-Sink	0.5	--	
$R_{\theta JA}$	Junction-to-Ambient	--	62.5	

SSP7N60A

N-CHANNEL
POWER MOSFET

Electrical Characteristics ($T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Characteristic	Min.	Typ.	Max.	Units	Test Condition
BV_{DSS}	Drain-Source Breakdown Voltage	600	--	--	V	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_D=250\mu\text{A}$
$\Delta \text{BV}/\Delta T_J$	Breakdown Voltage Temp. Coeff.	--	0.65	--	$\text{V}/^\circ\text{C}$	$\text{I}_D=250\mu\text{A}$ See Fig 7
$\text{V}_{\text{GS(th)}}$	Gate Threshold Voltage	2.0	--	4.0	V	$\text{V}_{\text{DS}}=5\text{V}, \text{I}_D=250\mu\text{A}$
I_{GSS}	Gate-Source Leakage , Forward	--	--	100	nA	$\text{V}_{\text{GS}}=30\text{V}$
	Gate-Source Leakage , Reverse	--	--	-100		$\text{V}_{\text{GS}}=-30\text{V}$
I_{DSS}	Drain-to-Source Leakage Current	--	--	25	μA	$\text{V}_{\text{DS}}=600\text{V}$
		--	--	250		$\text{V}_{\text{DS}}=480\text{V}, T_C=125^\circ\text{C}$
$\text{R}_{\text{DS(on)}}$	Static Drain-Source On-State Resistance	--	--	1.2	Ω	$\text{V}_{\text{GS}}=10\text{V}, \text{I}_D=3.5\text{A}$ ④
g_{fs}	Forward Transconductance	--	5.73	--	S	$\text{V}_{\text{DS}}=50\text{V}, \text{I}_D=3.5\text{A}$ ④
C_{iss}	Input Capacitance	--	1150	1500	pF	$\text{V}_{\text{GS}}=0\text{V}, \text{V}_{\text{DS}}=25\text{V}, f=1\text{MHz}$ See Fig 5
C_{oss}	Output Capacitance	--	130	150		
C_{rss}	Reverse Transfer Capacitance	--	53	62		
$t_{\text{d(on)}}$	Turn-On Delay Time	--	18	45	ns	$\text{V}_{\text{DD}}=300\text{V}, \text{I}_D=7\text{A}, \text{R}_G=9.1\Omega$ See Fig 13 ④ ⑤
t_r	Rise Time	--	19	50		
$t_{\text{d(off)}}$	Turn-Off Delay Time	--	72	155		
t_f	Fall Time	--	28	65		
Q_g	Total Gate Charge	--	49	65	nC	$\text{V}_{\text{DS}}=480\text{V}, \text{V}_{\text{GS}}=10\text{V}, \text{I}_D=7\text{A}$ ④ ⑤
Q_{gs}	Gate-Source Charge	--	8.4	--		See Fig 6 & Fig 12
Q_{gd}	Gate-Drain("Miller") Charge	--	22.1	--		

Source-Drain Diode Ratings and Characteristics

Symbol	Characteristic	Min.	Typ.	Max.	Units	Test Condition
I_s	Continuous Source Current	--	--	7	A	Integral reverse pn-diode in the MOSFET
I_{SM}	Pulsed-Source Current ①	--	--	28		
V_{SD}	Diode Forward Voltage ④	--	--	1.4	V	$T_J=25^\circ\text{C}, \text{I}_s=7\text{A}, \text{V}_{\text{GS}}=0\text{V}$
t_{rr}	Reverse Recovery Time	--	415	--	ns	$T_J=25^\circ\text{C}, I_F=7\text{A}$ $dI_F/dt=100\text{A}/\mu\text{s}$ ④
Q_{rr}	Reverse Recovery Charge	--	3.8	--		

Notes :

- ① Repetitive Rating : Pulse Width Limited by Maximum Junction Temperature
- ② $L=20\text{mH}, \text{I}_{\text{AS}}=7\text{A}, \text{V}_{\text{DD}}=50\text{V}, \text{R}_G=27\Omega, \text{Starting } T_J=25^\circ\text{C}$
- ③ $\text{I}_{\text{SD}} \leq 7\text{A}, dI/dt \leq 120\text{A}/\mu\text{s}, \text{V}_{\text{DD}} < \text{BV}_{\text{DSS}}, \text{Starting } T_J=25^\circ\text{C}$
- ④ Pulse Test : Pulse Width = $250\mu\text{s}$, Duty Cycle $\leq 2\%$
- ⑤ Essentially Independent of Operating Temperature

**N-CHANNEL
POWER MOSFET**

SSP7N60A

Fig 1. Output Characteristics




Fig 2. Transfer Characteristics




Fig 3. On-Resistance vs. Drain Current




Fig 4. Source-Drain Diode Forward Voltage




Fig 5. Capacitance vs. Drain-Source Voltage





Fig 6. Gate Charge vs. Gate-Source Voltage



SSP7N60A

N-CHANNEL
POWER MOSFET








Fig 12. Gate Charge Test Circuit & Waveform




Fig 13. Resistive Switching Test Circuit & Waveforms






Fig 14. Unclamped Inductive Switching Test Circuit & Waveforms



$$E_{AS} = \frac{1}{2} L_L I_{AS}^2 \frac{BV_{DSS}}{BV_{DSS} - V_{DD}}$$



SSP7N60A

N-CHANNEL
POWER MOSFET

Fig 15. Peak Diode Recovery dv/dt Test Circuit & Waveforms

