

POWER SCHOTTKY RECTIFIER

MAIN PRODUCT CHARACTERISTICS


$I_{F(AV)}$	2 A
V_{RRM}	60 V
T_j (max)	150°C
V_F (max)	0.55 V

FEATURES AND BENEFITS

- NEGLIGIBLE SWITCHING LOSSES
- LOW FORWARD VOLTAGE DROP
- AVALANCHE CAPABILITY SPECIFIED

DESCRIPTION

Axial and Surface Mount Power Schottky rectifier suited for Switch Mode Power Supplies and high frequency DC to DC converters. Packaged in DO-41 and SMA, this device is intended for use in low voltage, high frequency inverters and small battery chargers.



ABSOLUTE RATINGS (limiting values)

Symbol	Parameter			Value	Unit		
V_{RRM}	Repetitive peak reverse voltage			60	V		
$I_{F(RMS)}$	RMS forward current			10	A		
$I_{F(AV)}$	Average forward current	$T_L = 115^\circ\text{C}$	$\delta = 0.5$	2	A		
		$T_L = 110^\circ\text{C}$	$\delta = 0.5$	DO-41			
I_{FSM}	Surge non repetitive forward current	$t_p = 10 \mu\text{s}$ Sinusoidal		75	A		
P_{ARM}	Repetitive peak avalanche power	$t_p = 1 \mu\text{s}$ $T_j = 25^\circ\text{C}$		1600	W		
T_{stg}	Storage temperature range			- 65 to + 150	°C		
T_j	Maximum junction temperature *			150	°C		
dV/dt	Critical rate of rise of reverse voltage			10000	V/ μs		

* : $\frac{dP_{tot}}{dT_j} < \frac{1}{R_{th}(j - a)}$ thermal runaway condition for a diode on its own heatsink

STPS2L60/A

THERMAL RESISTANCES

Symbol	Parameter			Value	Unit
$R_{th(j-l)}$	Junction to leads	Lead length = 10 mm	DO-41	30	$^{\circ}\text{C/W}$
		SMA		25	

STATIC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Tests conditions		Min.	Typ.	Max.	Unit
I_R *	Reverse leakage current	$T_j = 25^{\circ}\text{C}$	$V_R = 60\text{V}$			0.1	mA
		$T_j = 100^{\circ}\text{C}$			2	10	
V_F *	Forward voltage drop	$T_j = 25^{\circ}\text{C}$	$I_F = 2\text{ A}$			0.60	V
		$T_j = 125^{\circ}\text{C}$				0.51	
		$T_j = 25^{\circ}\text{C}$	$I_F = 4\text{ A}$			0.77	
		$T_j = 125^{\circ}\text{C}$				0.62	

Pulse test : * $t_p = 380 \mu\text{s}$, $\delta < 2\%$

To evaluate the maximum conduction losses use the following equation:

$$P = 0.43 \times I_{F(\text{AV})} + 0.06 \times I_F^2 (\text{RMS})$$

Fig. 1: Average forward power dissipation versus average forward current.




Fig. 2: Average forward current versus ambient temperature ($\delta = 0.5$).




Fig. 3: Normalized avalanche power derating versus pulse duration.




Fig. 5-1: Non repetitive surge peak forward current versus overload duration (maximum values) (DO-41).




Fig. 6-1: Relative variation of thermal impedance junction to ambient versus pulse duration (DO-41).




Fig. 4: Normalized avalanche power derating versus junction temperature.




Fig. 5-2: Non repetitive surge peak forward current versus overload duration (maximum values) (SMA).





Fig. 6-2: Relative variation of thermal impedance junction to ambient versus pulse duration (SMA).



STPS2L60/A

Fig. 7: Reverse leakage current versus reverse voltage applied (typical values).




Fig. 9: Forward voltage drop versus forward current (low level, maximum values).




Fig. 11-1: Thermal resistance junction to ambient versus copper surface under each lead (Epoxy printed circuit board FR4, Cu: 35 μm) (SMA).




Fig. 8: Junction capacitance versus reverse voltage applied (typical values).




Fig. 10: Thermal resistance versus lead length (DO-41).






Fig. 11-2: Thermal resistance junction to ambient versus copper surface under each lead (Epoxy printed circuit board FR4, Cu: 35 μm) (DO-41).



PACKAGE MECHANICAL DATA
SMA (JEDEC DO-214AC)

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.70	0.075	0.106
A2	0.05	0.20	0.002	0.008
b	1.25	1.65	0.049	0.065
c	0.15	0.41	0.006	0.016
E	4.80	5.60	0.189	0.220
E1	3.95	4.60	0.156	0.181
D	2.25	2.95	0.089	0.116


FOOT PRINT DIMENSIONS (in millimeters)



STPS2L60/A

PACKAGE MECHANICAL DATA

DO-41 plastic



REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	4.07	5.20	0.160	0.205
B	2.04	2.71	0.080	0.107
C	28		1.102	

Ordering type	Marking	Package	Weight	Base qty	Delivery mode
STPS2L60	STPS2L60	DO-41	0.34g	2000	Ammopack
STPS2L60RL	STPS2L60	DO-41	0.34g	5000	Tape & Reel
STPS2L60A	S26	SMA	0.068 g	5000	Tape & Reel

- EPOXY MEETS UL94,V0

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 2003 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany
 Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore
 Spain - Sweden - Switzerland - United Kingdom - United States.

<http://www.st.com>