

HIGH VOLTAGE ULTRAFAST RECTIFIER

MAIN PRODUCT CHARACTERISTICS


$I_{F(AV)}$	1 A
V_{RRM}	1000 V
T_j (max)	175 °C
V_F (max)	1.42 V

FEATURES AND BENEFITS

- Low forward voltage drop
- High reliability
- High surge current capability
- Soft switching for reduced EMI disturbances
- Planar technology

DESCRIPTION

The STTH110, which is using ST ultrafast high voltage planar technology, is specially suited for free-wheeling, clamping, snubbing, demagnetization in power supplies and other power switching applications.



ABSOLUTE RATINGS (limiting values)

Symbol	Parameter			Value	Unit
V_{RRM}	Repetitive peak reverse voltage			1000	V
$V_{(RMS)}$	RMS voltage			700	V
$I_{F(AV)}$	Average forward current		$T_l = 100^\circ\text{C}$ $\delta = 0.5$	DO-41	1
			$T_l = 125^\circ\text{C}$ $\delta = 0.5$	SMA	1
I_{FSM}	Forward surge current $t = 8.3 \text{ ms}$			DO-41	20
				SMA	18
T_{stg}	Storage temperature range			- 50 + 175	°C
T_j	Maximum operating junction temperature			+ 175	°C

STTH110/A

THERMAL PARAMETERS

Symbol	Parameter			Value	Unit
$R_{th}(j-l)$	Junction to lead		$L = 10 \text{ mm}$	DO-41	45
			SMA	30	$^{\circ}\text{C/W}$
$R_{th}(j-a)$	Junction to ambient		$L = 10 \text{ mm}$	DO-41	110

STATIC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Tests conditions		Min.	Typ.	Max.	Unit
I_R	Reverse leakage current	$V_R = 1000\text{V}$	$T_j = 25^{\circ}\text{C}$			10	μA
			$T_j = 125^{\circ}\text{C}$			50	
V_F	Forward voltage drop	$I_F = 1 \text{ A}$	$T_j = 25^{\circ}\text{C}$			1.7	V
			$T_j = 150^{\circ}\text{C}$		0.98	1.42	

To evaluate the maximum conduction losses use the following equation :

$$P = 1.20 \times I_{F(AV)} + 0.225 \times I_F^2(\text{RMS})$$

DYNAMIC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Tests conditions		Min.	Typ.	Max.	Unit
t_{rr}	Reverse recovery time	$I_F = 0.5 \text{ A}$ $I_{rr} = 0.25 \text{ A}$	$I_R = 1\text{A}$	$T_j = 25^{\circ}\text{C}$		75	ns
t_{fr}	Forward recovery time	$I_F = 1 \text{ A}$ $dI_F/dt = 50 \text{ A}/\mu\text{s}$		$T_j = 25^{\circ}\text{C}$		300	ns
V_{FP}	Forward recovery voltage	$V_{FR} = 1.1 \times V_{F\max}$				18	V

Fig. 1: Conduction losses versus average current.




Fig. 3-1: Relative variation of thermal impedance junction ambient versus pulse duration (epoxy FR4, $L_{leads} = 10\text{mm}$) (DO-41).




Fig. 4-1: Thermal resistance junction to ambient versus copper surface under each lead (epoxy printed circuit board FR4, copper thickness: $35\mu\text{m}$) (DO-41).




Fig. 2: Forward voltage drop versus forward current.




Fig. 3-2: Relative variation of thermal impedance junction ambient versus pulse duration (epoxy FR4) (SMA).






Fig. 4-2: Thermal resistance junction to ambient versus copper surface under each lead (epoxy printed circuit board FR4, copper thickness: $35\mu\text{m}$) (SMA).




PACKAGE MECHANICAL DATA
SMA

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.70	0.075	0.106
A2	0.05	0.20	0.002	0.008
b	1.25	1.65	0.049	0.065
c	0.15	0.41	0.006	0.016
E	4.80	5.60	0.189	0.220
E1	3.95	4.60	0.156	0.181
D	2.25	2.95	0.089	0.116
L	0.75	1.60	0.030	0.063

FOOTPRINT (in millimeters)

PACKAGE MECHANICAL DATA

DO-41



REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	4.07	5.20	0.160	0.205
B	2.04	2.71	0.080	0.107
C	28		1.102	
D	0.712	0.863	0.028	0.034

Ordering code	Marking	Package	Weight	Base qty	Delivery mode
STTH110	STTH110	DO-41	0.34 g	2000	Ammopack
STTH110A	H10	SMA	0.068 g	5000	Tape & reel
STTH110RL	STTH110	DO-41	0.34 g	5000	Tape & reel

- Epoxy meets UL 94,V0

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 2003 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany

Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore

Spain - Sweden - Switzerland - United Kingdom - United States.

<http://www.st.com>