


TURBOSWITCH™ Tandem 600V ULTRA-FAST BOOST DIODE

MAJOR PRODUCTS CHARACTERISTICS

$I_{F(AV)}$	8 A
V_{RRM}	600 V (in series)
$T_j(\text{max})$	150 °C
$V_F(\text{max})$	2.6 V
$I_{RM}(\text{typ.})$	4 A

FEATURES AND BENEFITS

- ESPECIALLY SUITED AS BOOST DIODE IN CONTINUOUS MODE POWER FACTOR CORRECTORS AND HARD SWITCHING CONDITIONS.
- DESIGNED FOR HIGH DI/DT OPERATION.
- ULTRA-FAST RECOVERY CURRENT TO COMPETE WITH GaAs DEVICES. SIZE DIMINUTION OF MOSFET AND HEATSINKS ALLOWED.
- INTERNAL CERAMIC INSULATED PACKAGE ALLOWS FLEXIBLE HEATSINKING ON COMMON OR SEPARATE HEATSINK.
- MATCHED DIODES FOR TYPICAL PFC APPLICATION WITHOUT VOLTAGE BALANCE NETWORK.
- INSULATED VERSION: :
Insulated voltage = 2500 V_(RMS)
Capacitance = 7 pF



DESCRIPTION

The TURBOSWITCH "H" is an ultra high performance diode composed of two 300V dice in series. TURBOSWITCH "H" family drastically cuts losses in the associated MOSFET when run at high dI_F/dt.

ABSOLUTE RATINGS (limiting values for both diodes in series)

Symbol	Parameter	Value	Unit
V_{RRM}	Repetitive peak reverse voltage	600	V
$I_{F(RMS)}$	RMS forward current	14	A
I_{FSM}	Surge non repetitive forward current	80	A
T_{stg}	Storage temperature range	-65 +150	°C
T_j	Maximum operating junction temperature	+ 150	°C

STTH806TTI

THERMAL AND POWER DATA

Symbol	Parameter	Test conditions	Value	Unit
$R_{th(j-c)}$	Junction to case thermal resistance	Per diode	5	$^{\circ}\text{C}/\text{W}$
$R_{th(c)}$		Coupling	0.2	
$R_{th(j-c)}$	Junction to case thermal resistance	Total	2.6	
P_1	Conduction power dissipation for both diodes	$I_{F(AV)} = 8 \text{ A}$ $\delta = 0.5$ $T_c = 80^{\circ}\text{C}$	27	W

STATIC ELECTRICAL CHARACTERISTICS (for both diodes)

Symbol	Parameter	Tests Conditions		Min.	Typ.	Max.	Unit
I_R *	Reverse leakage current	$V_R = V_{RRM}$	$T_j = 25^{\circ}\text{C}$			10	μA
			$T_j = 125^{\circ}\text{C}$		15	100	
V_F **	Forward voltage drop	$I_F = 8 \text{ A}$	$T_j = 25^{\circ}\text{C}$			3.6	V
			$T_j = 125^{\circ}\text{C}$		2.1	2.6	

Pulse test : * $t_p = 5 \text{ ms}$, $\delta < 2\%$

** $t_p = 380 \mu\text{s}$, $\delta < 2\%$

To evaluate the maximum conduction losses use the following equation :
 $P = 1.8 \times I_{F(AV)} + 0.1 I_{F}^2(\text{RMS})$

RECOVERY CHARACTERISTICS

Symbol	Tests Conditions			Min.	Typ.	Max.	Unit	
t_{rr}	$I_F = 0.5 \text{ A}$	$I_{Rr} = 0.25 \text{ A}$	$I_R = 1 \text{ A}$	$T_j = 25^{\circ}\text{C}$		13	ns	
	$I_F = 1 \text{ A}$	$dI_F/dt = -50 \text{ A}/\mu\text{s}$	$V_R = 30 \text{ V}$			30		
I_{RM}	$V_R = 400 \text{ V}$		$dI_F/dt = -200 \text{ A}/\mu\text{s}$	$T_j = 125^{\circ}\text{C}$		4	5.5	A
						0.4		-

TURN-ON SWITCHING CHARACTERISTICS

Symbol	Tests Conditions		Min.	Typ.	Max.	Unit
t_{fr}	$I_F = 8 \text{ A}$	$dI_F/dt = 100 \text{ A}/\mu\text{s}$, measured at $1.1 \times V_F$ max	$T_j = 25^{\circ}\text{C}$		200	ns
V_{FP}	$I_F = 8 \text{ A}$	$dI_F/dt = 100 \text{ A}/\mu\text{s}$	$T_j = 25^{\circ}\text{C}$		7	V

Fig. 1: Conduction losses versus average current.




Fig. 2: Forward voltage drop versus forward current.




Fig. 3: Relative variation of thermal impedance junction to case versus pulse duration.




Fig. 4: Peak reverse recovery current versus dI_F/dt (90% confidence).




Fig. 5: Reverse recovery time versus dI_F/dt (90% confidence).





Fig. 6: Reverse charges versus dI_F/dt (90% confidence).



STTH806TTI

Fig. 7: Softness factor versus dI_F/dt (typical values).




Fig. 8: Relative variation of dynamic parameters versus junction temperature (reference: $T_j = 125^\circ C$).




Fig. 9: Transient peak forward voltage versus dI_F/dt (90% confidence).






Fig. 10: Forward recovery time versus dI_F/dt (90% confidence).



PACKAGE MECHANICAL DATA
TO-220AB



REF.	DIMENSIONS					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	15.20		15.90	0.598		0.625
a1	3.50		4.20	0.137		0.165
a2	13.00		14.00	0.511		0.551
B	10.00		10.40	0.393		0.409
b1	0.61		0.88	0.024		0.034
b2	1.23		1.32	0.048		0.051
C	4.40		4.60	0.173		0.181
c1	0.49		0.70	0.019		0.027
c2	2.40		2.72	0.094		0.107
e	2.40		2.70	0.094		0.106
F	6.20		6.60	0.244		0.259
I	3.75		3.85	0.147		0.151
I4		16.40			0.646	
L	2.65		2.95	0.104		0.116
I2	1.14		1.70	0.044		0.066
I3	1.14		1.70	0.044		0.066
M		2.60			0.102	

Ordering code	Marking	Package	Weight	Base qty	Delivery mode
STTH806TTI	STTH806TTI	TO-220AB	2.3 g.	50	Tube

- Cooling method: C
- Recommended torque value: 0.8 N.m.
- Maximum torque value: 1 N.m.
- Epoxy meets UL94,V0

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 2003 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany
Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore
Spain - Sweden - Switzerland - United Kingdom - United States.

<http://www.st.com>