# W9923QF



## **GENERAL DESCRIPTION**

The W9923QF is a high performance single-chip VCD decoder. It performs real-time decompression of ISO/IEC-11172 MPEG (Moving Picture Experts Group) streams, including system layer, audio and video data. It incorporates an 8-bit host interface and a CD interface which make it easy to use. Also, its versatile features help to build high-quality and cost-effective standalone VCD applications. Moreover, The W9923QF enhanced with power management and 20-bit DSP is pin-to-pin compatible with W9925QF(-K).

### **FEATURES**

#### Integration

- MPEG-1 system/audio/video decoding and synchronization
- CD-ROM decoding
- Glueless interface to 8051-series micro controllers
- Standard 4-Pin CD Interface
- Supports both Fast Page DRAM and EDO DRAM
- Provides programmable I/O pins for system control
- On Screen Display
- TV timing generation
- User-programmable power-saving mode

#### **System Operations**

- Fully supports VCD2.0, VCD1.1, Karaoke CD, CD-I FMV, and CDDA titles
- Digest function, provides quick overviews of contents in one disc or among discs, with audio output
- Versatile playback commands, including slow-motion, scan, pause, single frame, video clipping, freeze, and stop
- Provides fast forward play incorporating with speed-up audio
- Enhanced error recovery algorithms to overcome disc scratches and CD-drive errors
- Write/read pictures via host, allows writing Logos on display or capturing pictures from titles

#### **Video Processing**

High quality video output of still pictures

# **VCD Decoder**

(704x480 or 704x576) with only 4M DRAM

- Provides vertical scaling which allows full screen display of 240 (480)-line sources on PAL systems
- Provides filters to enhance image quality for SIF format data on full screen display
- User-programmable fade-in, fade-out effects and adjustable brightness
- 8-bit YCbCr video output

#### **Audio Processing**


- Decodes MPEG1 (layer-1, 2) stereo channel audio
- Provides voice cancellation mode for the purpose to remove the voice component in Karaoke titles
- Provides key control functions for Karaoke applications
- Supports 3D and surround sound processing
- Digital volume control and various channel selection modes both in MPEG and CDDA playback
- 16-bit Audio serial PCM output

#### Physical

- Low power consumption: 0.5W at full speed operation
- 3.3V power supply
- 100-pin plastic QFP

### **APPLICATIONS**

Following figure shows a typical configuration of VCD player.



 
 Winbond Corporate Headquarters
 Taipei Sales Office Tel: 886-3-5790666
 Winbond Electronics North America Corp.
 Winbond Electronics H.K. Ltd.

 Tel: 886-3-5790666
 Tel: 886-2-27190505
 Tel: 1-408-943666
 Tel: 822-27513100

 Fax: 886-3-5796139
 Fax: 886-2-27197502
 Fax: 1-408-9436668
 Fax: 822-27552064

Details are subject to change without notice. All trade marks are property of their respective holders.

May 1999