

MA2S372

Silicon epitaxial planer type

For UHF and VHF electronic tuners


■ Features

- Large capacity variation ratio
- Small series resistance r_D
- SS-Mini package, enabling down-sizing of the equipment and automatic insertion through taping

■ Absolute Maximum Ratings (Ta= 25°C)

Parameter	Symbol	Rating	Unit
Reverse voltage (DC)	V_R	32	V
Peak reverse voltage	V_{RM}^*	34	V
Forward current (DC)	I_F	20	mA
Junction temperature	T_j	150	°C
Storage temperature	T_{stg}	– 55 to +150	°C

* $R_L = 2.2k\Omega$



Marking Symbol : L

■ Electrical Characteristics (Ta= 25°C)




Parameter	Symbol	Condition	min	typ	max	Unit
Reverse current (DC)	I_R	$V_R = 30V$			10	nA
Diode capacitance	$C_{D(2V)}$	$V_R = 2V, f = 1MHz$	14.220		15.473	pF
	$C_{D(25V)}$	$V_R = 25V, f = 1MHz$	2.132		2.287	pF
	$C_{D(10V)}$	$V_R = 10V, f = 1MHz$	5.307		6.128	pF
	$C_{D(17V)}$	$V_R = 17V, f = 1MHz$	2.909		3.411	pF
Capacitance ratio	$C_{D(2V)}/C_{D(25V)}$		6.22			—
	$C_{D(10V)}/C_{D(17V)}$		1.70		1.96	—
Diode capacitance deviation	ΔC	$C_D(2V)(10V)(17V)(25V)$			2.0	%
Series resistance	r_D^*	$C_D = 9pF, f = 470MHz$			0.45	Ω

Note 1. Rated input/output frequency : 470MHz

2. * r_D measurement device : YHP MODEL 4191A RF IMPEDANCE ANALYZER

■ Marking



$C_D - V_R$  $I_F - V_F$  $C_D - T_a$  $I_R - T_a$ 