

MA2SV01

Silicon epitaxial planer type


For VCO

■ Features

- Good linearity and large capacity ratio of $V_R - C_D$
- Small series resistance r_D
- SS-Mini package, enabling down-sizing of the equipment and automatic insertion through taping

■ Absolute Maximum Ratings (Ta= 25°C)

Parameter	Symbol	Rating	Unit
Reverse voltage (DC)	V_R	6	V
Junction temperature	T_j	150	°C
Storage temperature	T_{stg}	- 55 to + 150	°C



Marking Symbol : U

■ Electrical Characteristics (Ta= 25°C)




Parameter	Symbol	Condition	min	typ	max	Unit
Reverse current (DC)	I_R	$V_R=6V$			10	nA
Diode capacitance	$C_{D(1V)}$	$V_R=1V, f=1MHz$	15.0		17.0	pF
	$C_{D(3V)}$	$V_R= 3V, f=1MHz$	5.0		7.0	pF
Capacitance ratio	$C_{D(1V)}/C_{D(3V)}$		2.2			—
Series resistance	r_D^*	$C_D= 9pF, f=470MHz$			1.0	Ω

Note 1 : Rated input/output frequency : 470MHz

2 : * r_D measurement device : YHP MODEL 4191A RF IMPEDANCE ANALYZER

■ Marking



$I_F - V_F$  $C_D - V_R$  $I_R - T_a$  $C_D - T_a$ 