

Sensitive Gate TRIACS


Silicon Bidirectional Thyristors

Designed for high volume, low cost, industrial and consumer applications such as motor control; process control; temperature, light and speed control.

- Small Size Surface Mount DPAK Package
- Passivated Die for Reliability and Uniformity
- Four-Quadrant Triggering
- Blocking Voltage to 600 V
- On-State Current Rating of 4.0 Amperes RMS at 93°C
- Low Level Triggering and Holding Characteristics

ORDERING INFORMATION


- To Obtain "DPAK" in Surface Mount Leadform (Case 369A)
Shipped in Sleeves — No Suffix, i.e. MAC4DHM
Shipped in 16 mm Tape and Reel — Add "T4" Suffix to Device Number, i.e. MAC4DHMT4
- To Obtain "DPAK" in Straight Lead Version (Case 369) Shipped in Sleeves — Add "-1" Suffix to Device Number, i.e. MAC4DHM-1



MAC4DHM
MAC4DLM

Motorola Preferred Devices

TRIACS
4.0 AMPERES RMS
600 VOLTS



CASE 369A-13
STYLE 6

MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Peak Repetitive Off-State Voltage (1) (T _J = -40 to 110°C, Sine Wave, 50 to 60 Hz, Gate Open)	V _{DRM}	600 600	Volts
On-State RMS Current (Full Cycle Sine Wave, 60 Hz, T _C = 93°C)	I _{T(RMS)}	4.0	Amps
Peak Non-Repetitive Surge Current (One Full Cycle, 60 Hz, T _J = 110°C)	I _{TSM}	40	
Circuit Fusing Consideration (t = 8.3 msec)	i ² t	6.6	A ² sec
Peak Gate Power (Pulse Width ≤ 10 μsec, T _C = 93°C)	P _{GM}	0.5	Watts
Average Gate Power (t = 8.3 msec, T _C = 93°C)	P _{G(AV)}	0.1	
Peak Gate Current (Pulse Width ≤ 10 μsec, T _C = 93°C)	I _{GM}	0.2	Amps
Peak Gate Voltage (Pulse Width ≤ 10 μsec, T _C = 93°C)	V _{GM}	5.0	Volts
Operating Junction Temperature Range	T _J	-40 to 110	°C
Storage Temperature Range	T _{stg}	-40 to 150	

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance — Junction to Case	R _{θJC}	3.5	°C/W
— Junction to Ambient	R _{θJA}	88	
— Junction to Ambient (2)	R _{θJA}	80	
Maximum Lead Temperature for Soldering Purposes (3)	T _L	260	°C

(1) V_{DRM} for all types can be applied on a continuous basis. Ratings apply for zero or negative gate voltage; positive gate voltage shall not be applied concurrent with negative potential on the anode. Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the device are exceeded.

(2) Surface mounted on minimum recommended pad size.

(3) 1/8" from case for 10 seconds.

Preferred devices are Motorola recommended choices for future use and best overall value.

MAC4DHM MAC4DLM

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Characteristics	Symbol	Min	Typ	Max	Unit
Peak Repetitive Blocking Current (V _D = Rated V _{DRM} , Gate Open) T _J = 25°C T _J = 110°C	I _{DRM}	— —	— —	0.01 2.0	mA
Peak On-State Voltage (1) (I _{TM} = ±6.0 A)	V _{TM}	—	1.3	1.6	Volts
Gate Trigger Current (Continuous dc) (V _D = 12 V, R _L = 100 Ω) MT2(+), G(+) MAC4DLM MT2(+), G(-) MT2(-), G(-) MT2(-), G(+) MT2(+), G(+) MAC4DHM MT2(+), G(-) MT2(-), G(-) MT2(-), G(+)	I _{GT}	— — — — — — — —	1.8 2.1 2.4 4.2 1.8 2.1 2.4 4.2	3.0 3.0 3.0 5.0 5.0 5.0 5.0 10	mA
Gate Trigger Voltage (Continuous dc) (V _D = 12 V, R _L = 100 Ω) MT2(+), G(+) MT2(+), G(-) MT2(-), G(-) MT2(-), G(+) (V _D = 12 V, R _L = 10 K Ω, T _J = 110°C) MT2(+), G(+); MT2(+), G(-); MT2(-), G(-); MT2(-), G(+)	V _{GT}	0.5 0.5 0.5 0.5 0.1	0.62 0.57 0.65 0.74 0.4	1.3 1.3 1.3 1.3 —	Volts
Holding Current (V _D = 12 V, Gate Open, I _T = ±200 mA)	I _H	—	1.5	15	mA
Latching Current MT2(+), G(+) (V _D = 12 V, I _G = 5.0 mA) MT2(+), G(-) (V _D = 12 V, I _G = 5.0 mA) MT2(-), G(-) (V _D = 12 V, I _G = 5.0 mA) MT2(-), G(+) (V _D = 12 V, I _G = 10 mA)	I _L	— — — —	1.75 5.2 2.1 2.2	10 10 10 10	mA

DYNAMIC CHARACTERISTICS

Characteristics	Symbol	Min	Typ	Max	Unit
Rate of Change of Commutating Current (1) (V _D = 200 V, I _{TM} = 1.8 A, Commutating dv/dt = 1.0 V/μsec, T _J = 110°C, f = 250 Hz, CL = 5.0 μfd, LL = 80 mH, RS = 56 Ω, CS = 0.03 μfd) See Figure 10	di/dt(c)	—	3.0	—	A/ms
Critical Rate of Rise of Off-State Voltage (V _D = 0.67 X Rated V _{DRM} , Exponential Waveform, Gate Open, T _J = 110°C)	dv/dt	—	10	—	V/μs

(1) Pulse test: Pulse Width ≤ 2.0 msec, Duty Cycle ≤ 2%.




Figure 1. RMS Current Derating




Figure 2. On-State Power Dissipation




Figure 3. On-State Characteristics




Figure 4. Transient Thermal Response




Figure 5. Typical Gate Trigger Current versus Junction Temperature




Figure 6. Typical Gate Trigger Voltage versus Junction Temperature

MAC4DHM MAC4DLM




Figure 7. Typical Holding Current versus Junction Temperature




Figure 8. Typical Latching Current versus Junction Temperature




Figure 9. Exponential Static dv/dt versus Gate-MT1 Resistance, MT2(+)




Figure 10. Critical Rate of Rise of Commutating Voltage





Figure 11. Simplified Test Circuit to Measure the Critical Rate of Rise of Commutating Voltage

PACKAGE DIMENSIONS



Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

Mfax is a trademark of Motorola, Inc.

How to reach us:

USA/EUROPE/Locations Not Listed: Motorola Literature Distribution;
 P.O. Box 5405, Denver, Colorado 80217. 303-675-2140 or 1-800-441-2447

JAPAN: Nippon Motorola Ltd.: SPD, Strategic Planning Office, 4-32-1,
 Nishi-Gotanda, Shinagawa-ku, Tokyo 141, Japan. 81-3-5487-8488

Mfax™: RMFAX0@email.sps.mot.com – TOUCHTONE 602-244-6609
 – US & Canada ONLY 1-800-774-1848

ASIA/PACIFIC: Motorola Semiconductors H.K. Ltd.; 8B Tai Ping Industrial Park,
 51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852-26629298

INTERNET: <http://motorola.com/sps>

