


Chip resistor networks

MNR04 (1005 × 4 size)

●Features

- 1) Extremely small and light
Area ratio is 60% smaller than that of chip 1632 (MNR14), while weight ratio has been cut 75%.
- 2) High-density mounting
Can be mounted even more densely than four 1005 chips (MCR01), and mounting costs are lower.
- 3) Can be mounted on a wide variety of devices
Squared corners make it excellent for mounting on image recognition devices.
- 4) Convex electrodes
Easy to check the fillet after soldering is finished.
- 5) ROHM resistors comply with the international standard ISO-9001.
Furthermore, changes to the design and specifications of products may occur without notice. Therefore, before ordering or using this product, please make sure to reconfirm the specification sheet before ordering or using this product.

●Ratings

Item	Conditions	Specifications	
Rated power	<p>Power must be derated according to the power derating curve in Figure 1 when ambient temperature exceeds 70°C.</p>  <p style="text-align: center;">Fig.1</p>	0.031W (1 / 32W) at 70°C	
Rated voltage	<p>The voltage rating is calculated by the following equation. If the value obtained exceeds the maximum operating voltage, the voltage rating is equal to maximum operating voltage.</p> $E = \sqrt{P \times R}$ <p> E : Voltage rating (V) P : Power rating (W) R : Nominal resistance (Ω) </p>	Max. operating voltage	25V
		Max. overload voltage	50V
		Max. intermittent overload voltage	50V
Nominal resistance	See Table 1.		
Operating temperature		- 55°C to + 125°C	

Resistors

Jumper type

Resistance	Max.50mΩ
Rated current	1A
Peak current	2A
Operating temperature	- 55°C to + 125°C

Table 1

Resistance tolerance	Resistance range (Ω)	Resistance temperature coefficient (ppm / °C)
J (± 5%)	10 ≤ R ≤ 1M (E24)	± 300


●Before using components in circuits where they will be exposed to transients such as pulse loads (short-duration, high-level loads), be certain to evaluate the component in the mounted state. In addition, the reliability and performance of this component cannot be guaranteed if it is used with a steady state voltage that is greater than its rated voltage.

●Characteristics


Characteristics	Specifications	Test method (JIS C 5202)
DC resistance	J: ± 5%	JIS C 5202 5.1 Applied voltage : A
Resistance temperature characteristics	See Table 1	JIS C 5202 5.2 Test conditions : + 25 / - 55 / + 25 / + 125°C
Short time overload	± (5.0% + 0.1Ω)	JIS C 5202 5.5 Rated voltage (current) × 2.5, 5s Maximum overload voltage : 50V
Resistance to soldering heat	± (2.5% + 0.1Ω) Outside must not be noticeably damaged.	JIS C 5202 6.4 Soldering conditions : 260 ± 5°C Soldering time : 10 ± 1s.
Solderability	95% of terminal surface must be covered by new soldering, and there must be no soldering corrosion.	JIS C 5202 6.5 Rosin methanol : (25%WT) Soldering conditions : 235 ± 5°C Soldering time : 2 ± 0.5s.
Resistance to dry heat	± (5.0% + 0.1Ω)	JIS C 5202 7.2 125°C Test time : 1,000 to 1,048 hrs.
Endurance (rated load)	± (5.0% + 0.1Ω)	JIS C 5202 7.10 Rated voltage (current) , 70°C 1.5h : ON - 0.5h : OFF Test time : 1,000 to 1,048 hrs.
Endurance (under load in damp environment)	± (5.0% + 0.1Ω)	JIS C 5202 7.9 Rated voltage (current) , 60°C, 95%RH 1.5h : ON - 0.5h : OFF Test time : 1,000 to 1,048 hrs.
Resistance to humidity (steady state)	± (5.0% + 0.1Ω)	JIS C 5202 7.5 85°C, 85%RH Test time : 1,000 to 1,048 hrs.
Temperature cycling	± (2.5% + 0.1Ω)	JIS C 5202 7.4 Test temperature : - 55°C to + 125°C 100cyc.
Resistance to solvents	± (1.0% + 0.05Ω)	JIS C 5202 6.9 Room temperature, static immersion, 1 min. Solvent : Isopropyl alcohol

Resistors

●External dimensions (Units: mm)



●Equivalent circuit



Resistors

●Packaging

Reel

Diagram of a reel showing dimensions A, B, D, C, and a label. The reel is EIAJ ET-7001 compliant.

EIAJ ET-7001 compliant

(Units : mm)

A	B	C	D
$\phi 180 \begin{smallmatrix} 0 \\ -3 \end{smallmatrix}$	$\phi 60 \begin{smallmatrix} +1 \\ 0 \end{smallmatrix}$	9 ± 0.3	$\phi 13 \pm 0.2$

Taping

Diagram of a resistor tape showing dimensions W, F, E, A₀, B₀, D₀, P₀, P₁, P₂, and T₂. Labels include Heat crimp cover / Tape, Thick paper mount (Underside paper tape), Chip network resistors, and Square punchout hole.

(Units : mm)

W	F	E	A ₀	B ₀
8.0 ± 0.3	3.5 ± 0.05	1.75 ± 0.1	1.2 ± 0.1	2.2 ± 0.1
D ₀	P ₀	P ₁	P ₂	T ₂
$\phi 1.5 \begin{smallmatrix} +0.1 \\ 0 \end{smallmatrix}$	4.0 ± 0.1	2.0 ± 0.1	2.0 ± 0.05	Max. 0.5

●Product designation

Part no.											
M	N	R	0	4	M	0	A	B	J		
Packaging / Processing specifications				Circuit configuration				Resistance tolerance	Nominal resistance		
Code	Part no.	Packaging	Package style	code							
M0	MNR02 / 04	Taping	Paper reel tape (10,000)	AB	MNR04 / 12 / 14 / 32 / 34	J	± 5%	3-digit IEC coding system			