

SURFACE MOUNT DUAL POSITIVE AND NEGATIVE FIXED VOLTAGE REGULATORS



Dual 5V, 12V and 15V, 1.5 Amp Fixed Voltage Regulators In Isolated Hermetic Surface Mount Package

FEATURES

- Positive And Negative Regulators In One Package
- Hermetic 6-Pin Metal Package, Surface Mount
- Isolated Case
- Output Voltages: $\pm 5V$, $\pm 12V$, And $\pm 15V$
- Output Voltages Set Internally To $\pm 2.0\%$
- Built-In Thermal Overload Protection
- Short Circuit Current Limiting
- Product Is Available Screened To MIL-PRF-38535, TX, TXV, S Levels


DESCRIPTION

This series of products offers a positive and a negative fixed voltage regulator in one hermetically sealed, 6-pin package whose outline is a surface mount type. With heat sinking, they can regulate over 1.5 Amp of output current per device. Standard voltages are + or - 5V, 12V, and 15V. Output voltages are internally trimmed to $\pm 2.0\%$ of nominal voltage. These devices are ideally suited for military applications where small size and high reliability is required.

To order, use the following Omnidrel part numbers to determine the required output voltage of each regulator within one package.

Omnidrel Part Number	Output Voltages	
	Positive	Negative
OM7501SM	+5V	-5V
OM7502SM	+5V	-12V
OM7503SM	+5V	-15V
OM7504SM	+12V	-5V
OM7505SM	+12V	-12V
OM7506SM	+12V	-15V
OM7507SM	+15V	-5V
OM7508SM	+15V	-12V
OM7509SM	+15V	-15V

PIN CONNECTION



Pin 1: +In Pin 4: -Out
 Pin 2: Common Pin 5: Common
 Pin 3: -In Pin 6: +Out

3.5

INDIVIDUAL POSITIVE REGULATORS

ELECTRICAL CHARACTERISTICS +5 Volt $V_{IN} = 10V$, $I_o = 500mA$, $-55^{\circ}C$ to $125^{\circ}C$ (unless otherwise specified)

Parameter	Symbol	Test Conditions	Min.	Max.	Unit
Output Voltage	V_{OUT}	$T_A = 25^{\circ}C$	4.92	5.08	V
		$V_{IN} = 7.5V$ to 20V	•	4.85	5.15 V
Line Regulation (Note 1)	V_{RLINE}	$V_{IN} = 7.5V$ to 20V	•	5	mV
		$V_{IN} = 8.0V$ to 12V	•	12	mV
Load Regulation (Note 1)	V_{RLOAD}	$I_o = 5mA$ to 1.5 Amp	•	4	mV
		$I_o = 250mA$ to 750 mA	•	10	mV
Standby Current Drain	I_{SCD}		•	6	mA
Standby Current Drain Change With Line	ΔI_{SCD} (Line)	$V_{IN} = 7.5V$ to 20V	•	6.5	mA
Standby Current Drain Change With Load	ΔI_{SCD} (Load)	$I_o = 5mA$ to 1000mA	•	0.5	mA
Dropout Voltage	V_{DO}	$T_A = 25^{\circ}C$, $\Delta V_{OUT} = 100mV$, $I_o = 1.0A$		2.5	V
Peak Output Current	$I_o (pk)$	$T_A = 25^{\circ}C$		1.5	A
Short Circuit Current (Note 2)	I_{BS}	$V_{IN} = 35V$	•	1.2	A
Ripple Rejection	$\frac{\Delta V_{IN}}{\Delta V_{OUT}}$	f = 120 Hz, $\Delta V_{IN} = 10V$ (Note 3)	66		dB
Output Noise Voltage (Note 3)	N_O	$T_A = 25^{\circ}C$, f = 10 Hz to 100KHz		40	$\mu V/V$ RMS
Long Term Stability (Note 3)	$\frac{\Delta V_{OUT}}{\Delta t}$	$T_A = 25^{\circ}C$, t = 1000 hrs.		75	mV

ELECTRICAL CHARACTERISTICS +12 Volt $V_{IN} = 19V$, $I_o = 500mA$, $-55^{\circ}C$ to $125^{\circ}C$ (unless otherwise specified)

Parameter	Symbol	Test Conditions	Min.	Max.	Unit
Output Voltage	V_{OUT}	$T_A = 25^{\circ}C$	11.88	12.12	V
		$V_{IN} = 14.5V$ to 27V	•	11.64	12.36 V
Line Regulation (Note 1)	V_{RLINE}	$V_{IN} = 14.5V$ to 27V	•	18	mV
		$V_{IN} = 16V$ to 22V	•	50	mV
Load Regulation (Note 1)	V_{RLOAD}	$I_o = 5mA$ to 1.5 Amp	•	9	mV
		$I_o = 250mA$ to 750 mA	•	30	mV
Standby Current Drain	I_{SCD}		•	32	mA
Standby Current Drain Change With Line	ΔI_{SCD} (Line)	$V_{IN} = 15V$ to 30V	•	60	mA
Standby Current Drain Change With Load	ΔI_{SCD} (Load)	$I_o = 5mA$ to 1000mA	•	20	mA
Ripple Rejection	$\frac{\Delta V_{IN}}{\Delta V_{OUT}}$	f = 120 Hz, $\Delta V_{IN} = 10V$ (Note 3)	60		dB
Output Noise Voltage (Note 3)	N_O	$T_A = 25^{\circ}C$, f = 10 Hz to 100KHz		40	$\mu V/V$ RMS
Long Term Stability (Note 3)	$\frac{\Delta V_{OUT}}{\Delta t}$	$T_A = 25^{\circ}C$, t = 1000 hrs.		120	mV

Notes:

- Load and Line Regulation are specified at a constant junction temperature. Pulse testing with low duty cycle is used. Changes in output voltage due to heating effects must be taken into account separately.
- Short Circuit protection is only assured up to $V_{IN} = 35V$.
- If not tested, shall be guaranteed to the specified limits.

The • denotes the specifications which apply over the full operating temperature range.

INDIVIDUAL POSITIVE REGULATORS

ELECTRICAL CHARACTERISTICS +15 Volt $V_{IN} = 23V$, $I_O = 500mA$, $-55^\circ C$ to $125^\circ C$ (unless otherwise specified)

Parameter	Symbol	Test Conditions	Min.	Max.	Unit
Output Voltage	V_{OUT}	$T_A = 25^\circ C$	14.8	15.2	V
		$V_{IN} = 18.5V$ to 30V	• 14.6	15.4	V
Line Regulation (Note 1)	V_{RLINE}	$V_{IN} = 17.5V$ to 30V	•	20	mV
		$V_{IN} = 20V$ to 26V	•	50	mV
Load Regulation (Note 1)	V_{RLOAD}	$I_O = 5mA$ to 1.5 Amp	•	15	mV
		$I_O = 5mA$ to 1.0 Amp	•	25	mV
Standby Current Drain	I_{SCD}	$I_O = 250mA$ to 750 mA	•	35	mV
			•	75	mV
Standby Current Drain Change With Line	ΔI_{SCD} (Line)	$V_{IN} = 18.5V$ to 30V	•	21	mV
			•	45	mV
Standby Current Drain Change With Load	ΔI_{SCD} (Load)	$I_O = 5mA$ to 1000mA	•	6.0	mA
			•	6.5	mA
Dropout Voltage	V_{DO}	$T_A = 25^\circ C$, $\Delta V_{OUT} = 100mV$, $I_O = 1.0A$		2.5	V
Peak Output Current	$I_{O(pk)}$	$T_A = 25^\circ C$	1.5	3.3	A
Short Circuit Current (Note 2)	I_{DS}	$V_{IN} = 35V$	•	1.2	A
Ripple Rejection	$\frac{\Delta V_{IN}}{\Delta V_{OUT}}$	f = 120 Hz, $\Delta V_{IN} = 10V$ (Note 3)	54		dB
Output Noise Voltage (Note 3)	N_O	$T_A = 25^\circ C$, f = 10 Hz to 100KHz		40	$\mu V/V$ RMS
Long Term Stability (Note 3)	$\frac{\Delta V_{OUT}}{\Delta t}$	$T_A = 25^\circ C$, t = 1000 hrs.		150	mV

ELECTRICAL CHARACTERISTICS -5 Volt $V_{IN} = -10V$, $I_O = 500mA$, $-55^\circ C$ to $125^\circ C$ (unless otherwise specified)

Parameter	Symbol	Test Conditions	Min.	Max.	Unit
Output Voltage	V_{OUT}	$T_A = 25^\circ C$	-4.95	-5.05	V
		$V_{IN} = -7.5V$ to -20V	• -4.85	-5.15	V
Line Regulation (Note 1)	V_{RLINE}	$V_{IN} = -7.5V$ to -20V	•	12	mV
		$V_{IN} = -8.0V$ to -12V	•	25	mV
Load Regulation (Note 1)	V_{RLOAD}	$I_O = 5mA$ to 1.5 Amp	•	5	mV
		$I_O = 250mA$ to 750 mA	•	12	mV
Standby Current Drain	I_{SCD}		•	20	mA
Standby Current Drain Change With Line	ΔI_{SCD} (Line)	$V_{IN} = -7.0V$ to -20V	•	25	mA
Standby Current Drain Change With Load	ΔI_{SCD} (Load)	$I_O = 5mA$ to 1000mA	•	30	mA
Dropout Voltage	V_{DO}	$\Delta V_{OUT} = 100mV$, $I_O = 1.0A$	•	2.5	V
Peak Output Current	$I_{O(pk)}$	$T_A = 25^\circ C$	1.5	3.3	A
Short Circuit Current (Note 2)	I_{DS}	$V_{IN} = -35V$	•	1.2	A
Ripple Rejection	$\frac{\Delta V_{IN}}{\Delta V_{OUT}}$	f = 120 Hz, $\Delta V_{IN} = -10V$ (Note 3)	63		dB
Output Noise Voltage (Note 3)	N_O	$T_A = 25^\circ C$, f = 10 Hz to 100KHz		60	$\mu V/V$ RMS
Long Term Stability (Note 3)	$\frac{\Delta V_{OUT}}{\Delta t}$	$T_A = 25^\circ C$, t = 1000 hrs.		75	mV

Notes:

- Load and Line Regulation are specified at a constant junction temperature. Pulse testing with low duty cycle is used. Changes in output voltage due to heating effects must be taken into account separately.
- Short Circuit protection is only assured up to $V_{IN} = +35V$, positive regulator; $V_{IN} = -35V$, negative regulator.
- If not tested, shall be guaranteed to the specified limits.

The • denotes the specifications which apply over the full operating temperature range.

ELECTRICAL CHARACTERISTICS -12 Volt $V_{IN} = -19V$, $I_O = 500mA$, $-55^\circ C \leq T_A \leq 125^\circ C$ (unless otherwise specified)

Parameter	Symbol	Test Conditions	Min.	Max.	Unit
Output Voltage	V_{OUT}	$T_A = 25^\circ C$	-11.88	-12.12	V
		$V_{IN} = -14.5V$ to $-27V$	•	-11.64	-12.36
Line Regulation (Note 1)	V_{RLINE}	$V_{IN} = -14.5V$ to $-27V$	•	20	mV
		$V_{IN} = -16V$ to $-22V$	•	50	mV
		$V_{IN} = -16V$ to $-22V$	•	10	mV
Load Regulation (Note 1)	V_{RLOAD}	$I_O = 5mA$ to $1.5Amp$	•	30	mV
		$I_O = 250mA$ to $750mA$	•	16	mV
		$I_O = 250mA$ to $750mA$	•	30	mV
Standby Current Drain	I_{SCD}		•	3.5	mA
			•	4.0	mA
Standby Current Drain Change With Line	ΔI_{SCD} (Line)	$V_{IN} = -14.5V$ to $-27V$	•	0.8	mA
Standby Current Drain Change With Load	ΔI_{SCD} (Load)	$I_O = 5mA$ to $1000mA$	•	0.5	mA
Dropout Voltage	V_{DO}	$\Delta V_{OUT} = 100mV$, $I_O = 1.0A$	•	1.8	V
Peak Output Current	$I_{O(pk)}$	$T_A = 25^\circ C$, $I_O = 5mA$ to $1A$		1.5	A
Short Circuit Current (Note 2)	I_{DS}	$V_{IN} = -35V$	•	1.2	A
			•	2.8	A
Ripple Rejection	$\frac{\Delta V_{IN}}{\Delta V_{OUT}}$	$f = 120\text{ Hz}$, $\Delta V_{IN} = -10V$		56	dB
		(Note 3)	•	53	dB
Output Noise Voltage (Note 3)	N_O	$T_A = 25^\circ C$, $f = 10\text{ Hz}$ to 100 KHz		40	$\mu\text{V/V}$ RMS
Long Term Stability (Note 3)	$\frac{\Delta V_{OUT}}{\Delta t}$	$T_A = 25^\circ C$, $t = 1000\text{ hrs.}$		120	mV

ELECTRICAL CHARACTERISTICS -15 Volt $V_{IN} = -23V$, $I_O = 500mA$, $-55^\circ C \leq T_A \leq 125^\circ C$ (unless otherwise specified)

Parameter	Symbol	Test Conditions	Min.	Max.	Unit
Output Voltage	V_{OUT}	$T_A = 25^\circ C$	-14.85	-15.15	V
		$V_{IN} = -17.5V$ to $-30V$	•	-14.55	-15.45
Line Regulation (Note 1)	V_{RLINE}	$V_{IN} = -17.5V$ to $-30V$	•	25	mV
		$V_{IN} = -20V$ to $-26V$	•	50	mV
		$V_{IN} = -20V$ to $-26V$	•	15	mV
Load Regulation (Note 1)	V_{RLOAD}	$I_O = 5mA$ to $1.5Amp$	•	25	mV
		$I_O = 250mA$ to $750mA$	•	35	mV
		$I_O = 250mA$ to $750mA$	•	75	mV
Standby Current Drain	I_{SCD}		•	6.0	mA
			•	6.5	mA
Standby Current Drain Change With Line	ΔI_{SCD} (Line)	$V_{IN} = -17.5V$ to $-30V$	•	0.8	mA
Standby Current Drain Change With Load	ΔI_{SCD} (Load)	$I_O = 5mA$ to $1000mA$	•	0.5	mA
Dropout Voltage	V_{DO}	$\Delta V_{OUT} = 100mV$, $I_O = 1.0A$	•	2.5	V
Peak Output Current	$I_{O(pk)}$	$T_A = 25^\circ C$		1.5	A
Short Circuit Current (Note 2)	I_{DS}	$V_{IN} = -35V$	•	1.2	A
			•	2.8	A
Ripple Rejection	$\frac{\Delta V_{IN}}{\Delta V_{OUT}}$	$f = 120\text{ Hz}$, $\Delta V_{IN} = -10V$		53	dB
		(Note 3)	•	50	dB
Output Noise Voltage (Note 3)	N_O	$T_A = 25^\circ C$, $f = 10\text{ Hz}$ to 100 KHz		40	$\mu\text{V/V}$ RMS
Long Term Stability (Note 3)	$\frac{\Delta V_{OUT}}{\Delta t}$	$T_A = 25^\circ C$, $t = 1000\text{ hrs.}$		150	mV



Notes:

- Load and Line Regulation are specified at a constant junction temperature. Pulse testing with low duty cycle is used. Changes in output voltage due to heating effects must be taken into account separately.
 - Short Circuit protection is only assured up to $V_{IN} = -35V$.
 - If not tested, shall be guaranteed to the specified limits.
- The • denotes the specifications which apply over the full operating temperature range.

ABSOLUTE MAXIMUM RATINGS (Per Regulator)

Input Voltage, Positive Regulator	+35 V
Input Voltage, Negative Regulator	-35 V
Operating Junction Temperature Range.....	55°C to + 150°C
Storage Temperature Range	-65°C to + 150°C
Typical Power/Thermal Characteristics:	
Rated Power @ 25° C	
T_C17.5W
T_A	3W
Thermal Resistance	
θ_{JC}3°C/W
θ_{JA}	42°C/W
Thermal Shutdown, $I_O = 5\text{mA}$, V_{IN} @ Voltage175°C

MECHANICAL OUTLINE



3.5

NOTES:

- Case is metal/hermetically sealed
- Isolated Tab