



ICs for Communications

Dual LNA

PMB2362 V1.1

Preliminary Specification 05.99

T2362-XV11-P1-7600

ABM®, AOP®, ARCOFI®, ARCOFI®-BA, ARCOFI®-SP, DigiTape®, EPIC®-1, EPIC®-S, ELIC®, FALC®54, FALC®56, FALC®-E1, FALC®-LH, IDEC®, IOM®, IOM®-1, IOM®-2, IPAT®-2, ISAC®-P, ISAC®-S, ISAC®-S TE, ISAC®-P TE, ITAC®, IWE®, MUSAC®-A, OCTAT®-P, QUAT®-S, SICAT®, SICOFI®, SICOFI®-2, SICOFI®-4, SICOFI®-4μC, SLICOFI® are registered trademarks of Infineon Technologies AG.

ACE™, ASM™, ASP™, POTSWIRE™, QuadFALC™, SCOUT™ are trademarks of Infineon Technologies AG.

Edition 03.99

**Published by Infineon Technologies AG i. Gr.,
SC,
Balanstraße 73,
81541 München**

© Infineon Technologies AG i. Gr. 03.95.
All Rights Reserved.

Attention please!

As far as patents or other rights of third parties are concerned, liability is only assumed for components, not for applications, processes and circuits implemented within components or assemblies.

The information describes the type of component and shall not be considered as assured characteristics.

Terms of delivery and rights to change design reserved.

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies AG is an approved CECC manufacturer.

Packing

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport.

For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

Components used in life-support devices or systems must be expressly authorized for such purpose!

Critical components¹ of the Infineon Technologies AG, may only be used in life-support devices or systems² with the express written approval of the Infineon Technologies AG.


- 1 A critical component is a component used in a life-support device or system whose failure can reasonably be expected to cause the failure of that life-support device or system, or to affect its safety or effectiveness of that device or system.
- 2 Life support devices or systems are intended (a) to be implanted in the human body, or (b) to support and/or maintain and sustain human life. If they fail, it is reasonable to assume that the health of the user may be endangered.

Table of Contents		Page
1	Functional Description	5
1.1	Pin Configuration	5
1.2	Pin Definitions and Functions	5
1.3	Functional Block Diagram	6
1.4	Circuit Description	7
2	Electrical Characteristics	8
2.1	Absolute Maximum Ratings	8
2.2	Operational Range	9
2.3	AC/DC Characteristics	9
3	Test Circuit	12
3.1	S-Parameter Test Circuit	12
3.2	S-Parameter Measurement Conditions	13
3.3	S-Parameters / Noise Parameters / Diagramms	14
4	Application Circuit	18
5	Package Outlines	19

1 Functional Description

1.1 Pin Configuration


(top view)



1.2 Pin Definitions and Functions

Pin No.	Symbol	Function
1	PD	Power down total circuit
2	AI1	LNA1 GSM900 signal base input
3	GND	Internal not connected, external GND connection recommended
4	AI2	LNA2 GSM1800 signal base input
5	BSW	Band switch, LNA1/LNA2
6	VCC _{LNA}	RF shunt open collector output LNA1/2
7	AO2	LNA2 amplifier output, open collector
8	VCC	Supply voltage total circuit
9	AO1	LNA1 amplifier output, matched
10	GC	LNA1/2 gain control
Heat Sink		Ground total circuit

1.3 Functional Block Diagram



Heat Sink Connection for IC Grounding

1.4 Circuit Description

General Description

The PMB2362 is a dual band LNA circuit designed for dual band wireless frontends with excellent performance.

LNA1

The LNA1 is designed for input frequencies between 0.9 and 1.0GHz. Entering the IC at the base input pin AI1 the RF input signal is amplified in the LNA1 stage. The gain of this LNA stage is controlled by the DC level at pin GC and can be adjusted in a 20 dB step. The LNA output is internal matched and at pin AO1 the amplified and matched signal is available for further use.

LNA2

The LNA2 is designed for input frequencies between 1.8 and 1.9GHz. Entering the IC at the base input pin AI2 the RF input signal is amplified in the LNA2 stage. The gain of this LNA stage is also controlled by the DC level at pin GC and can be adjusted in a fixed gain step. The open collector LNA output at pin AO2 has to be connected to VCC and external matching elements.

COMMON

VCC is the supply voltage for both LNAs. The grounding is done with the heat sink at the bottom side of the package. An internal bias driver generates supply voltage and temperature compensated reference voltages. The PD pin allows the circuit to be switched in a low power consuming (sleeping) mode. All pins with the exception of AI1/2, AO1/2 and GND are ESD protected.

2 Electrical Characteristics

2.1 Absolute Maximum Ratings

The maximum ratings may not be exceeded under any circumstances, not even momentarily and individually, as permanent damage to the IC will result.

Ambient temperature $T_{amb} = -40^{\circ}\text{C} \dots +85^{\circ}\text{C}$

Parameter	Symbol	Limit Values		Units	Remarks
		Min	Max		
Supply Voltage	V_S	-0.3	5.0	V	
Input Voltage	V_{PD}	-0.3	$V_S+0.3$ 5.0max.	V	
Input Voltage	V_{BSW}	-0.3	$V_S+0.3$ 5.0max.	V	
Input Voltage	V_{GC}	-0.3	$V_S+0.3$ 5.0max.	V	$V_{PD}>0.5V$
Input Voltage	V_{GC}	-0.3	3.8	V	$V_{PD}=0V$
Input Voltage (AC Peak, Freq.>1MHz)	$V_{AI1/2}$	$V_S-5.5$ -2.0min.		V	$V_{PD}=0V$ $I_{AI1/2}<nA$
Open Collector Output Voltage	$V_{AO2/}$ V_{CCLNA}	$V_S-5.5$ -0.3min	$V_S+2.0$ 5.0max.	V	
Input Current	$I_{AI1/2}$		6.0	mA	DC and AC
Junction Temperature	T_j		125	$^{\circ}\text{C}$	
Storage Temperature	T_S	-40	125	$^{\circ}\text{C}$	
Thermal Resistance	R_{thJA}		100	K/W	Junction to Ambient
Thermal Resistance	R_{thJL}		12	K/W	¹⁾ Junction to Lead
ESD integrity	V_{ESD}	tbd.	tbd.	V	

1) Heat Sink Temperature Fixed At 25 Degrees Celsius

2.2 Operational Range

Within the operational range the IC operates as described in the circuit description. The AC/DC characteristic limits are not guaranteed.

Supply voltage $V_S = 2.7V...3.6V$, Ambient temperature $T_{amb} = -40^{\circ}C...85^{\circ}C$

Parameter	Symbol	Limit Values		Units	Remarks
		Min	Max		
AI1 Input Frequency LNA1	f_{AI1}	0.9	1.0	GHz	
AI2 Input Frequency LNA2	f_{AI2}	1.8	1.9	GHz	
Total Circuit On	V_{PD}	1.5	V_S	V	
Total Circuit Off	V_{PD}	0	0.5	V	
Gain Control Low Gain	V_{GC}	1.5	V_S	V	
Gain Control High Gain	V_{GC}	0	0.5	V	
Bandswitch LNA1 On	V_{BSW}	0	0.5	V	
Bandswitch LNA2 On	V_{BSW}	1.5	V_S	V	

Note: Power levels refer to 50 Ohms impedance

2.3 AC/DC Characteristics

AC/DC characteristics involve the spread of values guaranteed within the specified supply voltage and ambient temperature range. Typical characteristics are the median of the production.

Supply voltage $V_{VCC} = 2.7V...3.6V$, Ambient temperature $T_{amb} = +25^{\circ}$

Parameter	Symbol	Limit Values			Units	Test Conditions	Test Item
		Min	Typ	Max			

Supply Current

Supply current, 0.95GHz	$I_{6,8,9}$		9.5		mA	V_{PD} high, V_{BSW} low	1.1
Supply current, 1.85GHz	$I_{6,7,8}$		8.5		mA	V_{PD} high, V_{BSW} high	1.2
Supply current, sleep	I_8		<5		μA	V_{PD} low	1.3

AC/DC Characteristics (continued)

AC/DC characteristics involve the spread of values guaranteed within the specified supply voltage and ambient temperature range. Typical characteristics are the median of the production.

Supply voltage $V_{VCC} = 2.7V \dots 3.6V$, Ambient temperature $T_{amb} = +25^{\circ}$

Parameter	Symbol	Limit Values			Units	Test Conditions	Test Item ¹⁾
		Min	Typ	Max			

LNA1, Signal Input AI1, high gain

Input impedance vs. freq.	S_{11}	Table 1				Diagramm1	2.1
Max. input level, 1db comp.	P_{AI1}	-20.5	-18.5		dBm	f=0.95GHz	2.2
Input intercept, third order	$IICP_{AI1}$	-12	-10		dBm	f=0.95GHz	2.3*
Noise figure	F_{AI1}		1.5	2.2	dB	f=0.95GHz	2.4*

LNA1, Signal Input AI1, low gain

Input impedance vs. freq.	S_{11}	Table 1				Diagramm1	2.5
Max. input level, 1db comp.	P_{AI1}	-20.5	-18.5		dBm	f=0.95GHz	2.6
Input intercept, third order	$IICP_{AI1}$	-12	-10		dBm	f=0.95GHz	2.7*
Noise figure	F_{AI1}		8.0	10.0	dB	f=0.95GHz	2.8*

LNA1, Signal Output AO1, high gain

Output impedance	$VSWR$		1.5			f=0.95GHz	2.9
Output impedance vs. freq.	S_{22}	Table 1				Diagramm1	2.10
Power gain	S_{21}	16	17		dB	f=0.95GHz	2.11*

LNA1, Signal Output AO1, low gain

Output impedance	$VSWR$		1.5			f=0.95GHz	2.12
Output impedance vs. freq.	S_{22}	Table 1				Diagramm1	2.13
Power Gain	S_{21}	-4	-3		dB	f=0.95GHz	2.14*

1) * Measured with Application Circuit (Matched In- and Output)

AC/DC Characteristics (continued)

AC/DC characteristics involve the spread of values guaranteed within the specified supply voltage and ambient temperature range. Typical characteristics are the median of the production.

Supply voltage $V_{VCC} = 2.7V$ to $3.6V$, Ambient temperature $T_{amb} = +25^{\circ}$

Parameter	Symbol	Limit Values			Unit	Test Conditions	Test Item ¹⁾
		Min	Typ	Max			

LNA2, Signal Input AI2, high gain

Input impedance vs. freq.	S_{11}	Table 2				Diagramm2	3.1
Max. input level, 1db comp.	P_{AI2}	-19	-17		dBm	f=1.85GHz	3.2
Input intercept, third order	$IICP_{AI2}$	-9.5	-7.5		dBm	f=1.85GHz	3.3*
Noise figure	F_{AI2}		2.0	2.7	dB	f=1.85GHz	3.4*

LNA2, Signal Input AI2, low gain

Input impedance vs. freq.	S_{11}	Table 2				Diagramm	3.5
Max. input level, 1db comp.	P_{AI2}	-19	-17		dBm	f=1.85GHz	3.6
Input intercept, third order	$IICP_{AI2}$	-9.5	-7.5		dBm	f=1.85GHz	3.7*
Noise figure	F_{AI2}		11	13	dB	f=1.85GHz	3.8*

LNA2, Signal Output AO2, Open Collector, high gain

Output impedance vs. freq.	S_{22}	Table 2				Diagramm	3.9
Power gain	S_{21}	17	19		dB	f=1.85GHz	3.10*

LNA2, Signal Output AO2, Open Collector, low gain


Output impedance vs. freq.	S_{22}	Table 2				Diagramm	3.11
Power gain	S_{21}	-3	-1		dB	f=1.85GHz	3.12*

1) * Measured with Application Circuit (Matched In- and Output)

Remark: IICP3 Measured with 800kHz differential tone

3 Test Circuit

3.1 S-Parameter Test Circuit



Test Circuit 1: 925 MHz - 960 MHz


Test Circuit 2: 1805 MHz - 1880 MHz

Component values for blocking capacitors 10p @ VCC, 27p else

Blocking capacitors at Pin: 1, 5, 6, 8 and 10

DC Biasing LNA2 via Network Analyzer

3.2 S-Parameter Measurement Conditions



S-Parameter Measurement of LNA1/2 : S11, S12, S21, S22

The S-Parameters are tested at the indicated frequency on Duroid 5880 Teflon Boards.

Via the NWA the capacitive coupling is done.
The output levels at port1 and 2 for pin x and y are -30dbm.

S11 and S22 have to be considered as design hints and are measured with Infineon testboards

All S-Parameters are measured.

Test	Test frequency MHz	Pin X	Pin Y
Amp. S11, S12, S21, S22	30 - 3000	AI1/2	AO1/2
Amp. S11, S12, S21, S22	900-1000	AI1	AO1
Amp. S11, S12, S21, S22	1800-1900	AI2	AO2

3.3 S-Parameters / Noise Parameters / Diagramms

3.3.1 Table 1: S-Parameter LNA1

S-Parameters are available on 3.5" disk or by E-mail

High Gain

Frequency [GHz]	S11 MAG	ANG	S21 MAG	ANG	S12 MAG	ANG	S22 MAG	ANG
0.81	0.57468	-89.9	6.91583	131.3	0.003029	108.8	0.19661	-161
0.84	0.57036	-94.4	7.13553	126.7	0.003754	109.1	0.16465	-160.3
0.87	0.55963	-98.7	7.29022	121.9	0.005167	91.5	0.13922	-155.6
0.9	0.54796	-103.2	7.39837	116.7	0.006071	78.7	0.12151	-146.3
0.93	0.52863	-106.7	7.45604	112	0.006278	88.5	0.11372	-134.4
0.96	0.5219	-109.5	7.40121	107	0.007097	82.7	0.12553	-125.5
0.99	0.51085	-113.3	7.32031	102.8	0.007674	71.5	0.13011	-122.2
1.02	0.49465	-116.4	7.25988	98.8	0.007487	66.2	0.13604	-116.5
1.05	0.48186	-118.7	7.21209	95.2	0.007213	65	0.14442	-110.5
1.08	0.46918	-120.9	7.21321	91.4	0.007444	55.4	0.15835	-104.7
1.11	0.45961	-122.8	7.2465	87.4	0.007427	61.9	0.17981	-100.4

Low Gain

Frequency [GHz]	S11 MAG	ANG	S21 MAG	ANG	S12 MAG	ANG	S22 MAG	ANG
0.81	0.5257	-92	0.67474	133.8	0.00148	129.6	0.19295	-166.1
0.84	0.51998	-94.9	0.69912	130.1	0.00291	152.6	0.15726	-170.7
0.87	0.51502	-97.9	0.70104	124.8	0.002866	142.9	0.12124	-171.1
0.9	0.51035	-100.7	0.70771	121.5	0.00296	127.3	0.08884	-165.8
0.93	0.50507	-103.5	0.71506	117.2	0.003721	129.3	0.06165	-152.2
0.96	0.50343	-106.5	0.71056	113	0.004777	127	0.05343	-123.2
0.99	0.50052	-109.4	0.70932	109	0.005215	115.4	0.06368	-96.2
1.02	0.49629	-112.1	0.70358	104.8	0.005844	112.1	0.08836	-83
1.05	0.49323	-114.9	0.69611	100.9	0.005821	107.1	0.11838	-78
1.08	0.48924	-117.4	0.69115	96.8	0.006178	102.7	0.1497	-77.3
1.11	0.48684	-120	0.68395	92.7	0.006651	97.5	0.18416	-78.6

Noise Parameters @ 920MHz:

Fmin = 1.33dB	Rn = 6.17	Γopt: Mag: 0.132	Ang: 132.9
---------------	-----------	------------------	------------

3.3.2 Table 2: S-Parameter LNA2

S-Parameters are available on 3.5" disk or by E-mail

High Gain

Frequency [GHz]	S11 MAG	ANG	S21 MAG	ANG	S12 MAG	ANG	S22 MAG	ANG
1.71	0.49242	-152.6	6.88619	44	0.009319	106.7	0.97152	-52.6
1.74	0.49159	-154.5	6.78958	42.2	0.010126	112.5	0.97075	-53.6
1.77	0.49287	-156.5	6.67339	40.3	0.010619	107.5	0.96835	-54.9
1.8	0.49257	-158.1	6.54866	38.5	0.010952	103.6	0.96761	-55.9
1.83	0.49122	-160	6.44234	36.8	0.011616	109.8	0.97078	-57.1
1.86	0.4897	-161.9	6.35383	34.8	0.012092	100.5	0.97236	-58.1
1.89	0.49049	-163.8	6.22605	33	0.011617	104.6	0.97083	-59.5
1.92	0.49163	-165.6	6.11839	31.3	0.013675	102.4	0.96812	-60.6
1.95	0.48904	-167.1	6.01005	29.5	0.013032	101.7	0.96681	-61.6
1.98	0.48789	-169	5.90915	27.7	0.013869	99.9	0.96768	-62.7
2.01	0.48725	-171.3	5.81244	25.9	0.01401	99.3	0.96638	-63.9



Low Gain

Frequency [GHz]	S11 MAG	ANG	S21 MAG	ANG	S12 MAG	ANG	S22 MAG	ANG
1.71	0.49151	-156.7	0.61223	43.4	0.005883	137.2	0.95592	-49.2
1.74	0.49043	-158.9	0.59784	41.5	0.006472	130.3	0.95576	-50.2
1.77	0.49071	-161	0.58151	39.8	0.006974	127.6	0.95311	-51.3
1.8	0.48723	-162.9	0.56316	38.4	0.007237	127.7	0.95262	-52.2
1.83	0.4821	-164.6	0.5627	37.7	0.008687	123.6	0.95109	-53.2
1.86	0.48296	-166.4	0.5553	34.4	0.008648	126.1	0.94994	-54.2
1.89	0.48488	-168.5	0.53698	32.1	0.009628	121.2	0.94908	-55.2
1.92	0.48525	-170.6	0.52048	30.1	0.008635	119.8	0.94747	-56.1
1.95	0.48228	-172.4	0.50395	28	0.009701	116.5	0.94531	-57
1.98	0.47885	-174.6	0.48973	26.3	0.009804	117.5	0.94528	-57.9
2.01	0.47693	-177	0.47446	24.4	0.009466	111.3	0.94391	-58.8



Noise Parameters @ 1.82GHz:

Fmin = 1.86dB Rn = 6.76 Γ_{opt} : Mag: 0.197 Ang: -164.4


3.3.3 Diagramm1: S11 / S22 LNA1



3.3.4 Diagramm2: S11 / S22 LNA2



4 Application Circuit






Application Circuit Topology - Design Hint

LNA 1: 925 MHz - 960 MHz
LNA 2: 1805 MHz - 1880 MHz

Refer to PMB2362 Application Note

5

P-TSSOP-10-2
(Plastic Package)



Heat Sink For IC Grounding

Remarks: