

## **PVO402AP**

Microelectronic Power IC  
HEXFET® Power MOSFET Relay  
Single Pole, Normally Open + Ring Detector  
0-400V, 150mA AC/DC

### **General Description**

The PVO402AP Photovoltaic Relay is a single pole, normally open solid-state relay plus ring detector. By integrating these two functions in one package it can replace two discrete components, i.e., a relay and an AC-input opto-coupler. The relay portion of PVO402AP utilizes International Rectifier's HEXFET power MOSFET as the output switch, driven by an integrated circuit photovoltaic generator of novel construction. The output switch is controlled by radiation from a GaAlAs light emitting diode (LED) which is optically isolated from the photovoltaic generator. The ring detector portion of PVO402AP has two LEDs in inverse parallel connection as the input sensing element and a silicon NPN photo-transistor as the output switch.

PVO402AP is ideally suited for PCMCIA fax/modem cards. Its extremely low profile allows it to be used in Type II cards whose outer shells are only 5mm thick.


PVO402AP Relays are packaged in an 8-pin, molded 'Thin-Pak' DIP package with 'gull-wing' surface mount terminals. It is available in plastic shipping tubes or on tape-and-reel. Please refer to Part Identification (opposite) for details.

### **Applications**

- On/Off Hook switch
- Dial pulsing
- Ringer injection
- Ring detection
- Loop current detection

### **Features**

- HEXFET Power MOSFET output
- Bounce-free operation
- 3,750 V<sub>RMS</sub> I/O Isolation
- Linear AC/DC operation
- Solid-State Reliability
- BAPT certified



**PVO402AP 'Thin-Pak'**

### **Part Identification**

PVO402AP	SMT, plastic shipping tube
PVO402AP-T	SMT, tape and reel

**Electrical Specifications** ( $-40^{\circ}\text{C} \leq T_A \leq +85^{\circ}\text{C}$  unless otherwise specified)

**RELAY**

INPUT CHARACTERISTICS	Limits	Units
Min. Control Current (See Fig.1)	5.0	mA
Max. Control Current for Off-State Resistance @ $T_A=+25^{\circ}\text{C}$	0.4	mA
Control Current Range (Caution: current limit input LED, see Fig.6)	5.0 to 25	mA
Max. Reverse Voltage	7.0	V

OUTPUT CHARACTERISTICS	Limits	Units
Operating Voltage Range	0 to $\pm 400$	$V_{(\text{DC or AC peak})}$
Max. Load Current @ $T_A=+40^{\circ}\text{C}$ 5mA Control (See Fig.1)	150	mA
Max. On-State Resistance @ $T_A=+25^{\circ}\text{C}$ For 50mA Pulsed Load, 5mA Control (See Fig.4)	22	$\Omega$
Max. Off-State Leakage @ $T_A=+25^{\circ}\text{C}$ , $\pm 400\text{V}$ (See Fig.5)	1.0	$\mu\text{A}$
Max. Turn-On Time @ $T_A=+25^{\circ}\text{C}$ (See Fig. 7) For 50mA, 100 $V_{\text{DC}}$ Load, 5mA Control	1.0	ms
Max. Turn-Off Time @ $T_A=+25^{\circ}\text{C}$ (See Fig. 7) For 50mA, 100 $V_{\text{DC}}$ Load, 5mA Control	0.5	ms
Max. Output Capacitance @ 50 $V_{\text{DC}}$	12	pF

**DETECTOR**



INPUT CHARACTERISTICS	Limits	Units
Min. Control Current @ $I_C = 2\text{mA}$ , $V_{\text{CE}} = 0.5\text{V}$	5.0	mA
Max. Control Current for Off-State Leakage $I_C=1\mu\text{A}$ , $V_{\text{CE}}=5\text{V}$ @ $T_A=+25^{\circ}\text{C}$	5	$\mu\text{A}$
Control Current Range (Caution: current limit input LED, see Fig.6)	5.0 to 25	mA

OUTPUT CHARACTERISTICS	Limits	Units
Min. Collector-Emitter Breakdown Voltage @ $I_C = 10\mu\text{A}$	20	$V_{\text{DC}}$
Min.Current Transfer Ratio @ $I_{\text{LED}} = 6\text{mA}$ , $V_{\text{CE}} = 5\text{V}$ (see Fig. 9)	33	%
Max. Saturation Voltage @ $I_{\text{LED}} = 16\text{mA}$ , $I_C = 2\text{mA}$	0.5	V
Max. Leakage Current @ $I_{\text{LED}}=0\text{mA}$ , $V_{\text{CE}} = 5\text{V}$	500	nA
Max. Power Dissipation @ $T_A=+25^{\circ}\text{C}$ (derate linearly 2.0mW/ $^{\circ}\text{C}$ )	150	mW


**COMBINED**

GENERAL CHARACTERISTICS	Limits	Units
Min. Dielectric Strength, Input-Output	3750	$V_{\text{RMS}}$
Min. Dielectric Strength, Relay-Detector	1000	$V_{\text{DC}}$
Min. Insulation Resistance, Input-Output @ $T_A=+25^{\circ}\text{C}$ , 50%RH, 100 $V_{\text{DC}}$	$10^{12}$	$\Omega$
Max. Capacitance, Input-Output	3.0	pF
Max. Pin Soldering Temperature (10 seconds max.)	+260	$^{\circ}\text{C}$
Ambient Temperature Range: Operating Storage	-40 to +85 -40 to +100	

**Connection Diagram**



**Figure 1. Current Derating Curve**



**Figure 2. Typical Output Capacitance**




Figure 3. Linearity Characteristics




Figure 4. Typical Normalized On-Resistance




Figure 5. Typical Normalized Off-State Leakage




Figure 6. Input Characteristics (Current Controlled)




Figure 7. Typical Delay Times




Figure 8. Delay Time Definitions




Figure 9. Typical Transfer Characteristics

Case Outline

