

143

●Electrical and optical characteristics (Ta = 25°C)

Parameter	Symbol	Conditions	Red			Green			Unit
			Min.	Typ.	Max.	Min.	Typ.	Max.	
Forward voltage	V_F	$I_F=10\text{mA}$	—	2.0	3.0	—	2.1	3.0	V
Reverse current	I_R	$V_R=3\text{V}$	—	—	10	—	—	10	μA
Peak wavelength	λ_P	$I_F=10\text{mA}$	—	650	—	—	563	—	nm
Spectral line half width	$\Delta\lambda$	$I_F=10\text{mA}$	—	40	—	—	40	—	nm
Viewing angle	$2\theta_{1/2}$	Diffused	—	40	—	—	40	—	deg
Luminous intensity	I_v	$I_F=10\text{mA}$	2.2	6.3	—	3.6	10	—	mcd

●Luminous intensity vs. wavelength




Fig. 1

●Directional pattern




Fig. 2

●Electrical characteristic curves (red, green)




Fig. 3 Forward current vs. forward voltage




Fig. 4 Luminous intensity vs. case temperature




Fig. 5 Luminous intensity vs. forward current




Fig. 6 Maximum tolerable peak current vs. pulse duration (red)




Fig. 7 Maximum tolerable peak current vs. pulse duration (green)




Fig. 8 Maximum forward current vs. ambient temperature