

FEATURES

- 3.3V power supply
- 1.9ns typical propagation delay
- 275MHz f_{MAX} (Clock bit stream, not pseudo-random)
- Differential LVPECL inputs
- 24mA LVTTL outputs
- Flow-through pinouts
- Internal input resistors: pulldown on D, pulldown and pullup on /D
- Q output will default LOW with inputs open or at GND
- V_{BB} output
- Available in 8-pin MSOP and SOIC package



ECL Pro™

DESCRIPTION


The SY100EPT21L is a single differential LVPECL-to-LVTTL translator using a single +3.3V power supply. Because LVPECL (Low Voltage Positive ECL) levels are used, only +3.3V and ground are required. The small outline 8-lead SOIC package and low skew single gate design make the EPT21L ideal for applications that require the translation of a clock or data signal where minimal space, low power, and low cost are critical.

V_{BB} allows a differential, single-ended, or AC-coupled interface to the device. If used, the V_{BB} output should be bypassed to V_{CC} with 0.01 μ F capacitor.

Under open input conditions, the /D will be biased at a $V_{CC}/2$ voltage level and the D input will be pulled to ground. This condition will force the Q output low to provide added stability.

The 100EPT is compatible with positive ECL 100K logic levels.

PIN CONFIGURATION/BLOCK DIAGRAM



(Available in 8-pin SOIC and 8-pin MSOP)

PIN NAMES

Pin	Function
Q	LVTTL Output
D, /D	Differential LVPECL Input Pair
V_{CC}	Positive Supply
V_{BB}	Output Reference Voltage
GND	Ground

ABSOLUTE MAXIMUM RATINGS⁽¹⁾

Symbol	Parameter	Value	Unit
V_{CC}	Power Supply Voltage	-0.5 to +3.8	V
V_I	PECL Input Voltage	0V to $V_{CC}+0.5$	V
V_O	Voltage Applied to Output at HIGH State	-0.5 to V_{CC}	V
I_O	Current Applied to Output at LOW State	Twice the Rated I_{OL}	mA
T_{store}	Storage Temperature	-65 to +150	°C
T_A	Operating Temperature	-40 to +85	°C

TRUTH TABLE

D	/D	Q
L	H	L
H	L	H
Open	Open	L

NOTE:

1. Permanent device damage may occur if ABSOLUTE MAXIMUM RATINGS are exceeded. This is a stress rating only and functional operation is not implied at conditions other than those detailed in the operational sections of this data sheet. Exposure to ABSOLUTE MAXIMUM RATING conditions for extended periods may affect device reliability.

LV TTL DC ELECTRICAL CHARACTERISTICS

$$V_{CC} = +3.3V \pm 5\%$$

Symbol	Parameter	$T_A = -40^\circ\text{C}$		$T_A = 0^\circ\text{C}$		$T_A = +25^\circ\text{C}$			$T_A = +85^\circ\text{C}$		Unit	Condition
		Min.	Max.	Min.	Max.	Min.	Typ.	Max.	Min.	Max.		
I_{OS}	Output Short Circuit Current	-80	-275	-80	-275	-80	—	-275	-80	-275	mA	$V_{OUT} = 0V$
I_{CC}	Power Supply Current	—	20	—	20	—	14	20	—	20	mA	
V_{OH}	Output HIGH Voltage	2.0	—	2.0	—	2.0	—	—	2.0	—	V	$I_{OH} = -3.0\text{mA}$
V_{OL}	Output LOW Voltage	—	0.5	—	0.5	—	—	0.5	—	0.5	V	$I_{OL} = 24\text{mA}$

LV PECL DC ELECTRICAL CHARACTERISTICS

$$V_{CC} = +3.3V \pm 5\%$$

Symbol	Parameter	$T_A = -40^\circ\text{C}$		$T_A = 0^\circ\text{C}$		$T_A = +25^\circ\text{C}$			$T_A = +85^\circ\text{C}$		Unit	Condition
		Min.	Max.	Min.	Max.	Min.	Typ.	Max.	Min.	Max.		
I_{IH}	Input HIGH Current	—	150	—	150	—	—	150	—	150	μA	
I_{IL}	Input LOW Current	0.5 -300	— —	0.5 -300	— —	0.5 -300	— —	— —	0.5 -300	— —	μA	
V_{IH}	Input HIGH Voltage ⁽²⁾ 100EPT	2135	2420	2135	2420	2135	—	2420	2135	2420		
V_{IL}	Input LOW Voltage ⁽²⁾ 100EPT	1490	1825	1490	1825	1490	—	1825	1490	1825		
V_{BB}	Reference Output ⁽²⁾ 100EPT	1920	2040	1920	2040	1920	1980	2040	1920	2040		

NOTES:

1. These values are for $V_{CC} = 3.3V$. Level Specifications will vary 1:1 V_{CC} .

AC ELECTRICAL CHARACTERISTICS $V_{CC} = +3.3V \pm 5\%$

Symbol	Parameter	TA = -40°C		TA = 0°C		TA = +25°C			TA = +85°C		Unit	Condition
		Min.	Max.	Min.	Max.	Min.	Typ.	Max.	Min.	Max.		
t _{PLH} t _{PHL}	Propagation Delay	1.5	2.5	1.5	2.5	1.5	1.9	2.5	1.5	2.5	ns	C _L = 20pF
t _{skpp}	Part-to-Part Skew ^(1,2)	—	0.5	—	0.5	—	—	0.5	—	0.5	ns	C _L = 20pF
f _{MAX}	Maximum Input Frequency ^(3,4)	275	—	275	—	275	—	—	275	—	MHz	C _L = 20pF
V _{CMR}	Common Mode Range	1.2	V _{CC}	1.2	V _{CC}	1.2	—	V _{CC}	1.2	V _{CC}	V	
V _{PP}	Minimum Peak-to-Peak Input ⁽⁵⁾	100	—	100	—	100	—	—	100	—	mV	
t _r t _f	Output Rise/Fall Time (1.0V to 2.0V)	0.5	1.0	0.5	1.0	0.5	—	1.0	0.5	1.0	ns	C _L = 20pF

NOTES:

1. Part-to-Part Skew considering HIGH-to-HIGH transitions at common V_{CC} level.
2. These parameters are guaranteed but not tested.
3. Frequency at which output levels will meet a 0.8V to 2.0V minimum swing.
4. The f_{MAX} value is specified as the minimum guaranteed maximum frequency. Actual operational maximum frequency may be greater.
5. 100mV input guarantees full logic at output.


PRODUCT ORDERING CODE

Ordering Code	Package Type	Operating Range	Marking Code
SY100EPT21LZC	Z8-1	Commercial	XEP21L
SY100EPT21LZCTR ⁽¹⁾	Z8-1	Commercial	XEP21L
SY100EPT21LKC	K8-1	Commercial	XP21
SY100EPT21LKCTR ⁽¹⁾	K8-1	Commercial	XP21


Ordering Code	Package Type	Operating Range	Marking Code
SY100EPT21LZI ⁽²⁾	Z8-1	Industrial	XEP21L
SY100EPT21LZITR ^(1,2)	Z8-1	Industrial	XEP21L
SY100EPT21LKI ⁽²⁾	K8-1	Industrial	XP21
SY100EPT21LKITR ^(1,2)	K8-1	Industrial	XP21

Note 1. Tape and Reel.**Note 2.** Recommended for new designs.

8 LEAD PLASTIC SOIC (Z8-1)



Rev. 03

8 LEAD MSOP (K8-1)

Rev. 01

MICREL, INC. 1849 FORTUNE DRIVE SAN JOSE, CA 95131 USATEL + 1 (408) 944-0800 FAX + 1 (408) 944-0970 WEB <http://www.micrel.com>

The information furnished by Micrel in this datasheet is believed to be accurate and reliable. However, no responsibility is assumed by Micrel for its use. Micrel reserves the right to change circuitry and specifications at any time without notification to the customer.

Micrel Products are not designed or authorized for use as components in life support appliances, devices or systems where malfunction of a product can reasonably be expected to result in personal injury. Life support devices or systems are devices or systems that (a) are intended for surgical implant into the body or (b) support or sustain life, and whose failure to perform can be reasonably expected to result in a significant injury to the user. A Purchaser's use or sale of Micrel Products for use in life support appliances, devices or systems is at Purchaser's own risk and Purchaser agrees to fully indemnify Micrel for any damages resulting from such use or sale.

© 2003 Micrel, Incorporated.