

- Programmable LED Driver
- Output Wattage: 60W
- Universal Voltage (120-277VAC)
- CC Programmable 500-2100mA
- Wireless Dimming
- Compact Case and Wire
- Output voltage range of 10-57VDC

### General Specifications

Input Voltage	120-277VAC, 50/60 Hz
Input Current	0.6A Max.
Input Power	72W
NTC Input	Ext. NTC Derating Resistance Range: 1k to 51k Ohm programmable. Default/Recommended Ext. NTC P/N:TSM2A104J4503RZ,SMD0805,Thinking Electronic.
Power Factor	>0.9
THD	<20%
Efficiency	86% Typical
Driver Type	Constant Current & Constant Power
Output Current	500-2100mA Programmable;See Label For Set Current;To Program The Output Current Use R-SET Resistor.(Figure 1) or TPSB-100 (Setting Controller) ;Print & Record New Setting On 1"x0.5" Label.
Output Voltage Range	10-57VDC(500-2100mA)
Output Power	60W Max.
Number of Output Channels	1 Channel
Dimming Controller Type/Dimming Range	Wireless / 100%-1%,0%
RFI/EMI	FCC Part 15B Consumer
Output Type	NON Class 2
Potting Type / Degree of Fill	Potting As Per ASTM D36-86 / Fully Potted
Ambient Operating Temperature Range	-40°C to 60°C (-40°F to 140°F)
Max. Case Temperature	90°C (194°F)
Sound Rating	A
Input Surge Protection	Line-Neutral 4kV, Line & Neutral-Ground 6kV
Protections	Input Current Protection
	Output Short Circuit Protection
	Output Open Circuit Protection
	Output to Ground Short Protection
	Overload Protection
	Over Temperature Protection
FCC	ID: 2AJ9LT1R1UNV210P60C
	This device complies with Part 15 of the FCC Rules.Operation is subject to the following two conditions: 1.This device may not cause harmful interference 2.This device must accept any interference received,including interference that may cause undesired operation.
Runtime Counting of Every 10 Degrees	Yes
Service Life	50,000 hours @Tc 82°C (179.6°F)
Approvals / Class	RoHS,UL LISTED,Class P,Type HL,IP65,FCC,SELV,ENEC,Dry and Damp
Warranty	5 years

Figure 1





Figure 2



Fulham extends a limited warranty to the original purchaser or first user for a period of 5 years @ Tc 80°C from the date of manufacture when properly installed and operated under normal conditions of use. The usage of appropriate series connected Surge Protection Device (SPD) is required in high risk applications.For complete terms and conditions, please refer to the Warranty Center at [www.fulham.com](http://www.fulham.com).Specifications subject to change without notice.

Figure 3




Figure 4




Figure 5




Figure 6




Figure 7





Figure 8



Fulham extends a limited warranty to the original purchaser or first user for a period of 5 years @ Tc 80°C from the date of manufacture when properly installed and operated under normal conditions of use. The usage of appropriate series connected Surge Protection Device (SPD) is required in high risk applications. For complete terms and conditions, please refer to the Warranty Center at [www.fulham.com](http://www.fulham.com). Specifications subject to change without notice.

Figure 9




Figure 10






Figure 11



**MECHANICAL DATA**



**NOTE :**


- 1.This Driver Must Be Installed By A Licensed Electrician
- 2.This Driver Must Be Grounded

Tolerance=±0.02"

**WIRING DIAGRAMS**

FCC ID:2AJ9LT1R1UNV210P60C

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:  
 1.This device may not cause harmful interference, and  
 2.This device must accept any interference received, including interference that may cause undesired operation.  
 Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.



INPUT SIDE	LENGTH
WHITE	13" (330mm)
BLACK	13" (330mm)

Programming SIDE	LENGTH
ORANGE	9.84" (250mm)
YELLOW	9.84" (250mm)

OUTPUT SIDE	LENGTH
RED	13" (330mm)
BLUE	13" (330mm)

**TPSB-100:**

Only for luminaire manufacturer not for end user. For detail information on using TPSB-100 Driver Programming Box, please consult user's manual of TPSB-100.



Fulham extends a limited warranty to the original purchaser or first user for a period of 5 years @ Tc 80°C from the date of manufacture when properly installed and operated under normal conditions of use. The usage of appropriate series connected Surge Protection Device (SPD) is required in high risk applications. For complete terms and conditions, please refer to the Warranty Center at [www.fulham.com](http://www.fulham.com). Specifications subject to change without notice.