



1101 KSS PCB Support




- Material: UL approved Nylon 66, 94V-2
- Color: Natural
- Feature: Easy to install / unload by hand, without tool. Pre-drill the hole on P.C Board and chassis before usage. Double locking design ensure that once support inside the panel cannot be removed accidentally, simply to push - through.



Standard Design



CS-0305, 0406



CS-0305S

Unit: mm						
	Item No.	A	PCB		Chassis	
			hole	thickness	hole	thickness
☐	CS-0305	4.8 (3/16")	4.0	1.8	4.8	2.5
☐	CS-0305S	4.8 (3/16")	3.0	2.0	3.0	2.0
☐	CS-0406	6.4 (1/4")	4.0	1.8	4.8	2.5
☐	CS-0406S	6.4 (1/4")	4.0	2.3	4.8	2.0
☐	CS-0610	9.3 (3/8")	4.0	1.8	4.8	2.5
☐	CS-0813	12.7 (1/2")	4.0	1.8	4.8	2.5
☐	CS-1016	15.9 (5/8")	4.0	1.8	4.8	2.5
☐	CS-1219	19.1 (3/4")	4.0	1.8	4.8	2.5
☐	CS-1422	22.2 (7/8")	4.0	1.8	4.8	2.5
☐	CS-1625	25.4 (1")	4.0	1.8	4.8	2.5
☐	CS-1828	28.5 (1 1/8")	4.0	1.8	4.8	2.5
☐	CS-2236	35.0 (1 3/8")	4.0	1.8	4.8	2.5
☐	CS-2236L	35.0 (1 3/8")	4.8	1.8	4.8	2.5

100 pcs / Bag

[Input Sample Order](#)

[Check Selected](#)

[Return All Selected](#)