


0808 KSS Screw On Wire Connector

- Material: Tough thermoplastic, UL 94V-2 flame-retardant shell.
- Strip wires before application.
- SW71BH, SW72BH rated to 300V max. Others rated to 600V max.
- Temperature: 105°C (221° F)
- Spring design provided more secure connection.



Unit: mm								
	Item No.	B	C	E	Wires Combination		Color	Packing
					sq	AWG		
☐	SW-71BH	6.5	8.6	15.2	Max. 2#1.25 Min. 2#0.5	Max. 2#16 Min. 2#18	Grey	100 pcs / Bag
☐	SW-72BH	7.1	9.9	17.7	Max. 3#1.25 Min. 2#0.5	Max. 3#16 Min. 2#18	Blue	
☐	SW-73BH	9.7	12.7	22.0	Max. 2#2.0 Min. 3#1.25	Max. 2#14 Min. 3#16	Orange	
☐	SW-74BH	11.0	14.0	24.6	Max. 3#3.5 Min. 2#2.0	Max. 3#12 Min. 2#14	Yellow	
☐	SW-76BH	13.1	16.3	26.5	Max. 2#5.5 Min. 2#3.5	Max. 2#10 Min. 2#12	Red	

[Input Sample Order](#)[Check Selected](#)[Return All Selected](#)