

## Zener Voltage Regulators 500 mW SOD-123 Surface Mount


### ● FEATURES

- 1) 500 mW Rating on FR-4 or FR-5 Board
- 2) Package Designed for Optimal Automated Board Assembly
- 3) Small Package Size for High Density Applications
- 4) General Purpose, Medium Current
- 5) ESD Rating of Class 3 (>16 kV) per Human Body Model
- 6) We declare that the material of product compliance with RoHS requirements.
- 7) S- Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable.

**LMSZ5231BT1G**  
**S-LMSZ5231BT1G**



**SOD-123**



### ● MECHANICAL CHARACTERISTICS:

CASE: Void-free, transfer-molded, thermosetting plastic case  
 FINISH: Corrosion resistant finish, easily solderable  
 FLAMMABILITY RATING: UL 94 V-0

### ● DEVICE MARKING AND RESISTOR VALUES

Device	Marking	Shipping
LMSZ5231BT1G	E1	3000/Tape&Reel
LMSZ5231BT3G	E1	10000/Tape&Reel

### ● MAXIMUM RATINGS(Ta = 25 °C)

Parameter	Symbol	Limits	Unit
Total Power Dissipation on FR-5 Board, (Note 1) @ TL = 75°C Derated above 75°C	PD	500 6.7	mW mW/°C
Thermal Resistance, Junction-to-Ambient(Note 2)	R <sub>θJA</sub>	340	°C/W
Thermal Resistance, Junction-to-Lead(Note 2)	R <sub>θJL</sub>	150	°C/W
Junction and Storage Temperature Range	T <sub>J,T<sub>stg</sub></sub>	-55~+150	°C


1. FR-5 = 3.5 X 1.5 inches, using the minimum recommended footprint.

2. Thermal Resistance measurement obtained via infrared Scan Method.

# LMSZ5231BT1G,S-LMSZ5231BT1G

**ELECTRICAL CHARACTERISTICS** ( $T_A = 25^\circ\text{C}$  unless otherwise noted,  $V_F = 0.9 \text{ V Max.} @ I_F = 10 \text{ mA}$ )

Symbol	Parameter
$V_Z$	Reverse Zener Voltage @ $I_{ZT}$
$I_{ZT}$	Reverse Current
$Z_{ZT}$	Maximum Zener Impedance @ $I_{ZT}$
$I_{ZK}$	Reverse Current
$Z_{ZK}$	Maximum Zener Impedance @ $I_{ZK}$
$I_R$	Reverse Leakage Current @ $V_R$
$V_R$	Reverse Voltage
$I_F$	Forward Current
$V_F$	Forward Voltage @ $I_F$



●**ELECTRICAL CHARACTERISTICS** ( $T_A = 25^\circ\text{C}$  unless otherwise noted,  $V_F = 0.9 \text{ V Max.} @ I_F = 10 \text{ mA}$ )

Device	Zener Voltage (Notes 3 and 4)				Zener Impedance (Note 5)			Leakage Current	
	VZ (Volts)			@ $I_{ZT}$	$Z_{ZT}$ @ $I_{ZT}$	$Z_{ZK}$ @ $I_{ZK}$	$I_R$ @ $V_R$		
	Min	Nom	Max	mA	$\Omega$	$\Omega$	mA	$\mu\text{A}$	Volts
LMSZ5231BT1G	4.85	5.1	5.36	20	17	1600	0.25	5	2

3. The type numbers shown have a standard tolerance of  $\pm 5\%$  on the nominal Zener voltage.

4. Nominal Zener voltage is measured with the device junction in thermal equilibrium at  $T_L = 30^\circ\text{C} \pm 1^\circ\text{C}$ .

5.  $Z_{ZT}$  and  $Z_{ZK}$  are measured by dividing the AC voltage drop across the device by the ac current applied.

The specified limits are for  $I_{Z(AC)} = 0.1 I_{Z(dc)}$  with the AC frequency = 1 KHz.


**LMSZ5231BT1G,S-LMSZ5231BT1G****ELECTRICAL CHARACTERISTICS CURVES**

FIG. 1 Zener Voltage vs Zener Current





FIG. 2 Typical Leakage Current

# LMSZ5231BT1G, S-LMSZ5231BT1G

## SOD-123




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

DIM	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.94	1.17	1.35	0.037	0.046	0.053
A1	0.00	0.05	0.10	0.000	0.002	0.004
b	0.51	0.61	0.71	0.020	0.024	0.028
c	---	---	0.15	---	---	0.006
D	1.40	1.60	1.80	0.055	0.063	0.071
E	2.54	2.69	2.84	0.100	0.106	0.112
H <sub>E</sub>	3.56	3.68	3.86	0.140	0.145	0.152
L	0.25	---	---	0.010	---	---

STYLE 1:  
 PIN 1. CATHODE  
 2. ANODE

## SOLDERING FOOTPRINT\*



SCALE 10:1  $(\frac{\text{mm}}{\text{inches}})$