

Bias Resistor Transistor

PNP Silicon Surface Mount Transistor with Monolithic Bias Resistor Network

This new series of digital transistors is designed to replace a single device and its external resistor bias network. The BRT (Bias Resistor Transistor) contains a single transistor with a monolithic bias network consisting of two resistors; a series base resistor and a base-emitter resistor. The BRT eliminates these individual components by integrating them into a single device. The use of a BRT can reduce both system cost and board space. The device is housed in the SC-70/SOT-323 package which is designed for low power surface mount applications.



- Simplifies Circuit Design
- Reduces Board Space
- Reduces Component Count
- The SC-70/SOT-323 package can be soldered using wave or reflow. The modified gull-winged leads absorb thermal stress during soldering eliminating the possibility of damage to the die.
- We declare that the material of product compliance with RoHS requirements.

Ordering Information


Device	Package	Shipping
LMUN51XXT1G	SOT323	3000/Tape&Reel
LMUN51XXT3G	SOT323	10000/Tape&Reel

LMUN5111T1G SERIES

PNP SILICON BIAS RESISTOR TRANSISTORS



MARKING DIAGRAM



6X =Specific Device Code
X =(See Marking Table)
M =Date Code

MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Rating	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	50	Vdc
Collector-Emitter Voltage	V_{CEO}	50	Vdc
Collector Current	I_C	100	mAdc

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation	P_D	202 (Note 1)	mW
$T_A = 25^\circ\text{C}$		310 (Note 2)	
Derate above 25°C		1.6 (Note 1) 2.5 (Note 2)	$^\circ\text{C}/\text{W}$
Thermal Resistance – Junction-to-Ambient	R_{JA}	618 (Note 1) 403 (Note 2)	$^\circ\text{C}/\text{W}$
Thermal Resistance – Junction-to-Lead	R_{JL}	280 (Note 1) 332 (Note 2)	$^\circ\text{C}/\text{W}$
Junction and Storage Temperature Range	T_J, T_{stg}	-55 to +150	$^\circ\text{C}$

1. FR-4 @ Minimum Pad

2. FR-4 @ 1.0 x 1.0 inch Pad

LMUN5111T1G SERIES
DEVICE MARKING AND RESISTOR VALUES

Device	Package	Marking	R1 (K)	R2 (K)	Shipping
LMUN5111T1G	SC-70/SOT-323	6A	10	10	3000/Tape & Reel
LMUN5112T1G	SC-70/SOT-323	6B	22	22	3000/Tape & Reel
LMUN5113T1G	SC-70/SOT-323	6C	47	47	3000/Tape & Reel
LMUN5114T1G	SC-70/SOT-323	6D	10	47	3000/Tape & Reel
LMUN5115T1G (Note 3)	SC-70/SOT-323	6E	10	∞	3000/Tape & Reel
LMUN5116T1G (Note 3)	SC-70/SOT-323	6F	4.7	∞	3000/Tape & Reel
LMUN5130T1G (Note 3)	SC-70/SOT-323	6G	1.0	1.0	3000/Tape & Reel
LMUN5131T1G (Note 3)	SC-70/SOT-323	6H	2.2	2.2	3000/Tape & Reel
LMUN5132T1G (Note 3)	SC-70/SOT-323	6J	4.7	4.7	3000/Tape & Reel
LMUN5133T1G (Note 3)	SC-70/SOT-323	6K	4.7	47	3000/Tape & Reel
LMUN5134T1G (Note 3)	SC-70/SOT-323	6L	22	47	3000/Tape & Reel
LMUN5135T1G (Note 3)	SC-70/SOT-323	6M	2.2	47	3000/Tape & Reel
LMUN5136T1G	SC-70/SOT-323	6N	100	100	3000/Tape & Reel
LMUN5137T1G	SC-70/SOT-323	6P	47	22	3000/Tape & Reel

3. New devices. Updated curves to follow in subsequent data sheets.

LMUN5111T1G SERIES
ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector–Base Cutoff Current ($V_{CB} = 50 \text{ V}$, $I_E = 0$)	I_{CBO}	—	—	100	nAdc
Collector–Emitter Cutoff Current ($V_{CE} = 50 \text{ V}$, $I_B = 0$)	I_{CEO}	—	—	500	nAdc
Emitter–Base Cutoff Current ($V_{EB} = 6.0 \text{ V}$, $I_C = 0$)	I_{EBO}	—	—	0.5	mAdc
LMUN5111T1G		—	—	0.2	
LMUN5112T1G		—	—	0.1	
LMUN5113T1G		—	—	0.2	
LMUN5114T1G		—	—	0.9	
LMUN5115T1G		—	—	1.9	
LMUN5116T1G		—	—	4.3	
LMUN5130T1G		—	—	2.3	
LMUN5131T1G		—	—	1.5	
LMUN5132T1G		—	—	0.18	
LMUN5133T1G		—	—	0.13	
LMUN5134T1G		—	—	0.2	
LMUN5135T1G		—	—	0.05	
LMUN5136T1G		—	—	0.13	
LMUN5137T1G		—	—	—	—
Collector–Base Breakdown Voltage ($I_C = 10 \mu\text{A}$, $I_E = 0$)	$V_{(BR)CBO}$	50	—	—	Vdc
Collector–Emitter Breakdown Voltage (Note 4) ($I_C = 2.0 \text{ mA}$, $I_B = 0$)	$V_{(BR)CEO}$	50	—	—	Vdc


ON CHARACTERISTICS (Note 4)






DC Current Gain ($V_{CE} = 10 \text{ V}$, $I_C = 5.0 \text{ mA}$)	LMUN5111T1G LMUN5112T1G LMUN5113T1G LMUN5114T1G LMUN5115T1G LMUN5116T1G LMUN5130T1G LMUN5131T1G LMUN5132T1G LMUN5133T1G LMUN5134T1G LMUN5135T1G LMUN5136T1G LMUN5137T1G	h_{FE}	35 60 80 80 160 160 3.0 8.0 15 80 80 80 80 80	60 100 140 140 250 250 5.0 15 27 140 130 140 150 140	— — — — — — — — — — — — — —	
Collector–Emitter Saturation Voltage ($I_C = 10 \text{ mA}$, $I_E = 0.3 \text{ mA}$) ($I_C = 10 \text{ mA}$, $I_B = 5 \text{ mA}$) LMUN5130T1G/LMUN5131T1G ($I_C = 10 \text{ mA}$, $I_B = 1 \text{ mA}$) LMUN5115T1G/LMUN5116T1G/ LMUN5132T1G/LMUN5133T1G/LMUN5134T1G		$V_{CE(\text{sat})}$	—	—	0.25	Vdc
Output Voltage (on) ($V_{CC} = 5.0 \text{ V}$, $V_B = 2.5 \text{ V}$, $R_L = 1.0 \text{k}\Omega$)	LMUN5111T1G LMUN5112T1G LMUN5114T1G LMUN5115T1G LMUN5116T1G LMUN5130T1G LMUN5131T1G LMUN5132T1G LMUN5133T1G LMUN5134T1G LMUN5135T1G LMUN5113T1G LMUN5136T1G LMUN5137T1G	V_{OL}	— — — — — — — — — — — — — — —	— — — — — — — — — — — — — — —	0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.2	Vdc






4. Pulse Test: Pulse Width < 300 μs , Duty Cycle < 2.0%

LMUN5111T1G SERIES
ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted) (Continued)

Characteristic	Symbol	Min	Typ	Max	Unit
Output Voltage (off) ($V_{CC} = 5.0 \text{ V}$, $V_B = 0.5 \text{ V}$, $R_L = 1.0 \text{ k}\Omega$) ($V_{CC} = 5.0 \text{ V}$, $V_B = 0.050 \text{ V}$, $R_L = 1.0 \text{ k}\Omega$) ($V_{CC} = 5.0 \text{ V}$, $V_B = 0.25 \text{ V}$, $R_L = 1.0 \text{ k}\Omega$)	V_{OH}	4.9	—	—	Vdc
Input Resistor					
LMUN5111T1G	R1	7.0	10	13	
LMUN5112T1G		15.4	22	28.6	
LMUN5113T1G		32.9	47	61.1	
LMUN5114T1G		7.0	10	13	
LMUN5115T1G		7.0	10	13	
LMUN5116T1G		3.3	4.7	6.1	
LMUN5130T1G		0.7	1.0	1.3	
LMUN5131T1G		1.5	2.2	2.9	
LMUN5132T1G		3.3	4.7	6.1	
LMUN5133T1G		3.3	4.7	6.1	
LMUN5134T1G		15.4	22	28.6	
LMUN5135T1G		1.54	2.2	2.86	
LMUN5136T1G		70	100	130	
LMUN5137T1G		32.9	47	61.1	
Resistor Ratio	R_1/R_2				
LMUN5111T1G/LMUN5112T1G/LMUN5113T1G/ LMUN5136T1G		0.8	1.0	1.2	
LMUN5114T1G		0.17	0.21	0.25	
LMUN5115T1G/LMUN5116T1G		—	—	—	
LMUN5130T1G/LMUN5131T1G/LMUN5132T1G		0.8	1.0	1.2	
LMUN5133T1G		0.055	0.1	0.185	
LMUN5134T1G		0.38	0.47	0.56	
LMUN5135T1G		0.038	0.047	0.056	
LMUN5137T1G		1.7	2.1	2.6	


Figure 1. Derating Curve

LMUN5111T1G SERIES
TYPICAL ELECTRICAL CHARACTERISTICS – LMUN5111T1G

Figure 2. $V_{CE(sat)}$ versus I_C

Figure 3. DC Current Gain

Figure 4. Output Capacitance

Figure 5. Output Current versus Input Voltage

Figure 6. Input Voltage versus Output Current

TYPICAL ELECTRICAL CHARACTERISTICS – LMUN5112T1G

Figure 7. $V_{CE(sat)}$ versus I_C

Figure 8. DC Current Gain

Figure 9. Output Capacitance

Figure 10. Output Current versus Input Voltage

Figure 11. Input Voltage versus Output Current

TYPICAL ELECTRICAL CHARACTERISTICS – LMUN5113T1G




 Figure 12. $V_{CE(sat)}$ versus I_C


Figure 13. DC Current Gain




Figure 14. Output Capacitance




Figure 15. Output Current versus Input Voltage










Figure 16. Input Voltage versus Output Current

TYPICAL ELECTRICAL CHARACTERISTICS – LMUN5114T1G



LMUN5111T1G SERIES
TYPICAL ELECTRICAL CHARACTERISTICS — LMUN5132T1G


Figure 23. Maximum Collector Voltage versus Collector Current




Figure 24. DC Current Gain




Figure 25. Output Capacitance




Figure 26. Output Current versus Input Voltage




Figure 27. Input Voltage versus Output Current


LMUN5111T1G SERIES
TYPICAL ELECTRICAL CHARACTERISTICS — LMUN5136T1G


Figure 28. Maximum Collector Voltage versus Collector Current




Figure 29. DC Current Gain




Figure 30. Output Capacitance




Figure 31. Output Current versus Input Voltage




Figure 32. Input Voltage versus Output Current


TYPICAL ELECTRICAL CHARACTERISTICS — LMUN5137T1G


Figure 33. Maximum Collector Voltage versus Collector Current




Figure 34. DC Current Gain




Figure 35. Output Capacitance




Figure 36. Output Current versus Input Voltage






Figure 37. Input Voltage versus Output Current

LMUN5111T1G SERIES
SC-70 (SOT-323)


NOTES:
 1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 2. CONTROLLING DIMENSION: INCH.

DIM	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.80	0.90	1.00	0.032	0.035	0.040
A1	0.00	0.05	0.10	0.000	0.002	0.004
A2	0.7	REF		0.028	REF	
b	0.30	0.35	0.40	0.012	0.014	0.016
c	0.10	0.18	0.25	0.004	0.007	0.010
D	1.80	2.10	2.20	0.071	0.083	0.087
E	1.15	1.24	1.35	0.045	0.049	0.053
e	1.20	1.30	1.40	0.047	0.051	0.055
e1	0.65	BSC		0.026	BSC	
L	0.425	REF		0.017	REF	
H _E	2.00	2.10	2.40	0.079	0.083	0.095

**GENERIC
MARKING DIAGRAM**


XX = Specific Device Code
 M = Date Code
 ^ = Pb-Free Package

*This information is generic. Please refer to device data sheet for actual part marking.
 Pb-Free indicator, "G" or microdot "^", may or may not be present.

