


Six IGBTMOD™ + Brake NF-Series Module 150 Amperes/600 Volts



Outline Drawing and Circuit Diagram

Dimensions	Inches	Millimeters
A	4.72	120.0
B	2.17	55.0
C	1.39	35.0
D	4.17±0.02	106.0±0.5
E	0.43	11.0
F	0.28	7.0
G	0.54	13.62
H	1.61	40.78
J	0.67	17.0
K	0.47	12.0
L	M5	M5
M	0.27 Dia.	Dia. 5.5

Dimensions	Inches	Millimeters
N	1.23	32.0
P	0.47	11.75
Q	0.53	13.5
R	0.91	23.0
S	0.87	22.0
T	0.76	19.75
U	0.42	10.75
V	0.87+0.04/-0.02	22.0+1.0/-0.5
W	0.91	23.2
X	0.63	16.0
Y	0.12	3.0

Housing Types (J.S.T. Mfg. Co. Ltd.)

AA – B8P-VH-FB-B

AB – B2P-VH-FB-B



Description:

Powerex IGBTMOD™ Modules are designed for use in switching applications. Each module consists of six IGBT Transistors in a three phase bridge configuration and a seventh IGBT with free-wheel diode for dynamic braking. All components and interconnects are isolated from the heat sinking baseplate, offering simplified system assembly and thermal management.

Features:

- ☐ Low Drive Power
- ☐ Low $V_{CE(sat)}$
- ☐ Discrete Super-Fast Recovery Free-Wheel Diode
- ☐ Isolated Baseplate for Easy Heat Sinking

Applications:

- ☐ AC Motor Control
- ☐ Motion/Servo Control
- ☐ Photovoltaic/Fuel Cell

Ordering Information:

Example: Select the complete module number you desire from the table below -i.e. CM150RL-12NF is a 600V (V_{CES}), 150 Ampere Six-IGBTMOD™ + Brake Power Module.

Type	Current Rating Amperes	V_{CES} Volts (x 50)
CM	150	12



Powerex, Inc., 200 E. Hillis Street, Youngwood, Pennsylvania 15697-1800 (724) 925-7272

CM150RL-12NF

Six IGBTMOD™ + Brake NF-Series Module

150 Amperes/600 Volts

Absolute Maximum Ratings, $T_j = 25^\circ\text{C}$ unless otherwise specified

Characteristics	Symbol	CM150RL-12NF	Units
Power Device Junction Temperature	T_j	-40 to 150	$^\circ\text{C}$
Storage Temperature	T_{stg}	-40 to 125	$^\circ\text{C}$
Mounting Torque, M5 Mounting Screws	—	31	in-lb
Mounting Torque, M5 Main Terminal Screws	—	31	in-lb
Module Weight (Typical)	—	350	Grams
Isolation Voltage, AC 1 minute, 60Hz Sinusoidal	V_{ISO}	2500	Volts

Inverter Sector

Collector-Emitter Voltage (G-E Short)	V_{CES}	600	Volts
Gate-Emitter Voltage (C-E Short)	V_{GES}	± 20	Volts
Collector Current ($T_C = 93^\circ\text{C}$)*	I_C	150	Amperes
Peak Collector Current ($T_j \leq 150^\circ\text{C}$)	I_{CM}	300**	Amperes
Emitter Current***	I_E	150	Amperes
Peak Emitter Current***	I_{EM}	300**	Amperes
Maximum Collector Dissipation ($T_C = 25^\circ\text{C}$, $T_j < 150^\circ\text{C}$)	P_C	730	Watts

Brake Sector

Collector-Emitter Voltage (G-E Short)	V_{CES}	600	Volts
Gate-Emitter Voltage (C-E Short)	V_{GES}	± 20	Volts
Collector Current ($T_C = 102^\circ\text{C}$)*	I_C	75	Amperes
Peak Collector Current ($T_j \leq 150^\circ\text{C}$)	I_{CM}	150**	Amperes
Maximum Collector Dissipation ($T_C = 25^\circ\text{C}$, $T_j < 150^\circ\text{C}$)	P_C	430	Watts
Repetitive Peak Reverse Voltage (Clamp Diode Part)	V_{RRM}	600	Volts
Forward Current (Clamp Diode Part)	I_{FM}	75	Amperes

* T_C , T_f measured point is just under the chips.

**Pulse width and repetition rate should be such that device junction temperature (T_j) does not exceed $T_{j(\text{max})}$ rating.

***Represents characteristics of the anti-parallel, emitter-to-collector free-wheel diode (FWDI).

CM150RL-12NF

Six IGBTMOD™ + Brake NF-Series Module

150 Amperes/600 Volts

Electrical and Mechanical Characteristics, $T_j = 25^\circ\text{C}$ unless otherwise specified

Inverter Sector

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Collector Cutoff Current	I_{CES}	$V_{CE} = V_{CES}, V_{GE} = 0V$	—	—	1.0	mA
Gate-Emitter Threshold Voltage	$V_{GE(th)}$	$I_C = 15mA, V_{CE} = 10V$	6	7	8	Volts
Gate Leakage Current	I_{GES}	$V_{GE} = V_{GES}, V_{CE} = 0V$	—	—	0.5	μA
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 150A, V_{GE} = 15V, T_j = 25^\circ\text{C}$	—	1.7	2.2	Volts
		$I_C = 150A, V_{GE} = 15V, T_j = 125^\circ\text{C}$	—	1.7	—	Volts
Input Capacitance	C_{ies}	$V_{CE} = 10V, V_{GE} = 0V$	—	—	23.0	nf
Output Capacitance	C_{oes}		—	—	2.8	nf
Reverse Transfer Capacitance	C_{res}		—	—	0.9	nf
Total Gate Charge	Q_G	$V_{CC} = 300V, I_C = 150A, V_{GE} = 15V$	—	600	—	nC
Inductive	Turn-on Delay Time	$V_{CC} = 300V, I_C = 150A, V_{GE1} = V_{GE2} = 15V, R_G = 4.2\Omega, I_E = 150A,$	—	—	120	ns
Load	Turn-on Rise Time		—	—	100	ns
Switch	Turn-off Delay Time		—	—	300	ns
Time	Turn-off Fall Time		—	—	300	ns
Reverse Recovery Time*	t_{rr}	Inductive Load Switching Operation	—	—	150	ns
Reverse Recovery Charge*	Q_{rr}		—	2.5	—	μC
Emitter-Collector Voltage*	V_{EC}	$I_E = 150A, V_{GE} = 0V$	—	—	2.8	Volts

Thermal and Mechanical Characteristics, $T_j = 25^\circ\text{C}$ unless otherwise specified

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Thermal Resistance, Junction to Case**	$R_{th(j-c)Q}$	Per IGBT 1/6 Module	—	—	0.17	$^\circ\text{C/W}$
Thermal Resistance, Junction to Case**	$R_{th(j-c)D}$	Per FWDi 1/6 Module	—	—	0.31	$^\circ\text{C/W}$
Contact Thermal Resistance	$R_{th(c-f)}$	Per 1/6 Module, Thermal Grease Applied	—	0.085	—	$^\circ\text{C/W}$
External Gate Resistance	R_G		4.2	—	42	Ω

*Represents characteristics of the anti-parallel, emitter-to-collector free-wheel diode (FWDi).

** T_C, T_f measured point is just under the chips.

CM150RL-12NF

Six IGBTMOD™ + Brake NF-Series Module

150 Amperes/600 Volts

Electrical and Mechanical Characteristics, $T_j = 25^\circ\text{C}$ unless otherwise specified

Brake Sector

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Collector Cutoff Current	I_{CES}	$V_{CE} = V_{CES}, V_{GE} = 0V$	—	—	1.0	mA
Gate-Emitter Threshold Voltage	$V_{GE(th)}$	$I_C = 7.5mA$	6	7	8	Volts
Gate Leakage Current	I_{GES}	$V_{GE} = V_{GES}, V_{CE} = 0V$	—	—	0.5	μA
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 75A, V_{GE} = 15V, T_j = 25^\circ\text{C}$	—	1.7	2.2	Volts
		$I_C = 75A, V_{GE} = 15V, T_j = 125^\circ\text{C}$	—	1.7	—	Volts
Input Capacitance	C_{ies}	$V_{CE} = 10V, V_{GE} = 0V$	—	—	11.3	nf
Output Capacitance	C_{oes}		—	—	1.4	nf
Reverse Transfer Capacitance	C_{res}		—	—	0.45	nf
Total Gate Charge	Q_G	$V_{CC} = 300V, I_C = 75A, V_{GE} = 15V$	—	300	—	nC
Forward Voltage Drop	V_{FM}	$I_F = 75A$	—	—	2.6	Volts

Thermal and Mechanical Characteristics, $T_j = 25^\circ\text{C}$ unless otherwise specified


Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Thermal Resistance, Junction to Case*	$R_{th(j-c)Q}$	Per IGBT 1/6 Module	—	—	0.29	$^\circ\text{C/W}$
Thermal Resistance, Junction to Case*	$R_{th(j-c)D}$	Per FWDi 1/6 Module	—	—	0.51	$^\circ\text{C/W}$

* T_C, T_f measured point is just under the chips.

CM150RL-12NF

Six IGBTMOD™ + Brake NF-Series Module

150 Amperes/600 Volts



CM150RL-12NF

Six IGBTMOD™ + Brake NF-Series Module

150 Amperes/600 Volts

