



佛山市国星光电股份有限公司
FOSHAN NATIONSTAR OPTOELECTRONICS CO., LTD

产品规格书 SPECIFICATION

顾客名称 Customer		产品名称 Product	多芯片组合 Combination of multi-chip
顾客部品号 Customer No.		产品型号 Type	MC-P2828NW-50W1501208

顾 客 确 认 APPROVED SIGNATURES			



ISO14001
环境管理体系认证



ISO9001
质量管理体系认证

地址：广东省佛山市禅城区华宝南路 18 号
Add: NO.18 South Huabao Rd, Foshan, Guangdong, China
电话 (Tel): 086-0757-83985604, 83985605, 83985607
传真 (Fax): 086-0757-82100221, 82100223
邮编 (Zip): 528000
<http://www.nationstar.com>

研究开发中心 Research & Development Center		
批 淮 APPROVE	审 核 CHECK	制 定 DRAW
版本号 (Version No.): B1.XMZM01		
文件发放日期 (Release Date): 2014-01-02		

20140102P1919XMZMB1



MC-P2828NW-50W1501208

多芯片组合
Combination of multi-chip

技术数据表 Technical Data Sheet

本产品在小尺寸上集成了高光强、高光效，长寿命等优点，其主要应用为家庭日常照明，建筑照明，泛光照明，路灯以及各类商业和娱乐的装饰照明。

This product combines high luminous, high illuminant efficiency and long working life with small package, it is generally used for common illuminate, architectural lighting, street lighting or commercial and entertainment decorative lighting.

特性:

Features:

- 功率等级: 50W
Power: 50W
- 适合大电流应用电路
Adapt to large current circuit
- 特别适合恶劣的工作环境
Adapt to severe working atmosphere especially
- 热阻 0.6K/W
Thermal Resistance: 0.6K/W
- 高发光效率: 105 lm/W
High Illuminant Efficiency: 105 lm/W
- 符合欧盟公布 RoHS 指令
Complied With RoHS Directive

目录

Catalogue

光电性参数

Optical-Electrical Characteristics.....2

典型特性曲线

Typical Characteristic Curves.....3

可靠性实验

Reliability Test Items And Conditions.....6

外形尺寸

Outline Dimensions7

使用注意事项

Precautions.....8

附录：分档标准

Appendix: Ranking Criteria.....10

* 产品规格如因工艺改进而有所改变，恕不另行通知。

*The Specifications of the product may be modified for improvement without notice.



光电性参数

Optical-Electrical Characteristics

◆ 极限参数 (温度=25°C):

Absolute Maximum Ratings (Temperature=25 °C):

参数名称 Parameter	符号 Symbol	数值 Rating	单位 Unit
正向电流 Forward Current	I _F	2 MAX	A
反向电压 Reverse Voltage	V _R	60 MAX	V
静电敏感 Antistatic Effect	--	1000	V
工作温度 Operating Temperature	T _{OPR}	-30 ~ +100	°C
贮存温度 Storage Temperature	T _{Stg}	-40 ~ +100	°C
功耗 Power	P _D	75	W
焊接温度 Solder Temperature	T _{sld}	手工焊: 350°C < 5 sec.	

* 注: 脉冲宽度≤0.1ms, 占空比≤1/10

* Note: Pulse width≤0.1ms, Duty≤1/10

◆ 光电参数 (温度=25°C):



Electro-Optical Characteristics (Temperature=25 °C):

参数名称 Parameter	符号 Symbol	条件 Condition	最小值 Min.	典型值 Typ.	最大值 Max.	单位 Unit
正向电压 Forward Voltage	V _F	I _F =1.5A	36.0	36.5	37.5	V
反向电流 Reverse Current	I _R	V _R =60V	--	--	40	μA
色温 Color temperature	T _C	I _F =1.5A	--	4000	--	K
显色指数 CRI	R _a	I _F =1.5A	--	80	--	
光通量 Flux	Φ _v	I _F =1.5A	--	5750	--	lm




典型特性曲线

Typical Characteristics Curves




光衰特性曲线：

Optic Attention Characteristics Curves:




I-V 特性曲线：

Forward Voltage vs. Forward Current:



相对发光强度随电流变化曲线
Relative Luminous Intensity VS. Forward Current





可靠性试验

Reliability Test Items And Conditions

实验项目 Test Items	参考标准 Reference	实验条件 Test Conditions	时间 Time	样品数 Quantity	判据 Criterion
冷热冲击 Thermal Shock	MIL-STD-202G	-40°C(30min)→100°C(30min)	循环 100 次 100 cycles	22	0/22
湿热循环 Temperature And Humidity Cyclic	JEITA ED-4701 200 203	-10°C~65°C , 0%~90%RH 24hrs./1cycle	循环 10 次 10 cycles	22	0/22
高温高湿储存 High Temperature High Humidity Storage	JEITA ED-4701 100 103	Ta=60°C, RH=90%	1000h	22	0/22
高温寿命 High Temperature Life Test	JESD22-A108D	Ta=55°C IF =1.5A	1000h	22	0/22
常温寿命试验 Life Test	JESD22-A108D	Ta=25°C IF =1.5A	1000h	22	0/22

* 单个 LED 失效判断标准 Criteria For Judging Damage of One single LED

测试项目 Test Items	符号 Symbol	测试条件 Test Conditions	判定标准 Criteria For Judging Damage
正向电压 Forward Voltage	V_F	$I_F = I_{FT}$	初始值±10% Initial Data±10%
光通量 Luminous Flux	Φ_V	$I_F = I_{FT}$	平均 Φ_V 衰减≤30%, 单个 Φ_V 衰减≤50% Average Φ_V degradation≤30%; Single LED Φ_V degradation≤50%
耐焊接热 Resistance to Soldering Heat			材料无内部裂痕、无材料间爆裂、剥离、无死灯。 Material without internal cracks, no material between stripped, no deaded light.

* 注: Tsol-锡液温度 * Note: Tsol-Temperature of tin liquid.





国星光电
NATIONSTAR

多芯片组合
Combination of multi-chip

外形尺寸

Outline Dimension



单位: mm

All dimensions in mm.



使用注意事项 (1)

Precautions (1)

1. 使用烙铁人手焊接

Hand Soldering

焊接温度请控制在 350~400°C，焊接时间请控制在 3 秒内。

Hand soldering temperature should be 350~400°C, and soldering time should less than 3 seconds.

人手焊接过程中的不慎操作易引起 LED 产品的损坏，应当小心谨慎。

Be careful because the damage of the product is often started at the time of the hand soldering.

在焊接升温过程中，请不要对 LED 施加任何压力。

Stress on the LEDs should be avoided during heating in soldering process.

在焊接完成后，待产品温度下降到室温之后，再进行其他处理。

After soldering, do not deal with the product before its temperature drop down to room temperature.

2. 清洗:

Cleaning

在焊接后推荐使用酒精进行清洗，在温度不高于 30°C 的条件下持续 3 分钟，不高于 50°C 的条件下持续 30 秒。使用其他类似溶剂清洗前，请先确认使用的溶剂不会对 LED 的封装和硅树脂部分造成损伤。

超声波清洗也是有效的方法，一般最大功率不应超过 300W，否则可能对 LED 造成损伤。请根据具体的情况预先测试清洗条件是否会对 LED 造成损伤。

It is recommended that alcohol be used as a solvent for cleaning after soldering. Cleaning is to go under 30°C for 3 minutes or 50°C for 30 seconds. When using other solvents, it should be confirmed beforehand whether the solvents will dissolve the package and the resin or not.

Ultrasonic cleaning is also an effective way for cleaning. But the influence of Ultrasonic cleaning on LED depends on factors such as ultrasonic power. Generally, the ultrasonic power should not be higher than 300W. Before cleaning, a pre-test should be done to confirm whether any damage to LEDs will occur.

* 注意：此一般指导原则并不适用于所有焊接设备的配置。具体工艺受到诸多因素的影响，请根据特定的设计和焊接设备来确定焊接方案。

* Note: This general guideline may not apply to configurations of all soldering equipment. The techniques in practice are influenced by many factors, it should be specialized based on the designs and configurations of the soldering equipment..



使用注意事项（2）

Precautions (2)

3. 静电：

Static Electricity

静电和电涌会导致产品特性发生改变，例如正向电压降低等，如果情况严重甚至会损毁产品。所以在使用时必须采取有效的防静电措施。

所有相关的设备和机器都应该正确接地，同时必须采取其他防止静电和电涌的措施。

使用防静电手环，防静电垫子，防静电工作服、工作鞋、手套，防静电容器，都是有效的防止静电和电涌的措施。

Static electricity or surge voltage damages the LEDs. Damaged LEDs will show some unusual characteristics such as the forward voltage becomes lower, or the LEDs do not light at the low current., even not light.

All devices, equipment and machinery must be properly grounded. At the same time, it is recommended that wrist bands or anti-electrostatic gloves, anti-electrostatic containers be used when dealing with the LEDs.

4. 设计建议：

Design Consideration

设计电路时，通过 LED 的电流不能超过规定的最大值，同时，还需使用保护电阻，否则，微小的电压变化将会引起较大的电流变化，可能导致产品损毁。

In designing a circuit, the current through each LED must not exceed the absolute maximum rating specified for each LED. In the meanwhile, resistors for protection should be applied, otherwise slight voltage shift will cause big current change, burn out may happen.

LED 的特性容易因为自身的发热和环境的温度的改变而发生改变。温度的升高会降低 LED 的发光效率、影响发光颜色等，所以在设计时应充分考虑散热的问题。

Thermal Design is paramount importance because heat generation may result in the Characteristics decline, such as brightness decreased, Color changed and so on. Please consider the heat generation of the LEDs when making the system design.

5. 眼睛保护忠告：

Safety Advice For Human Eyes

点亮 LED 前，请勿直视发光光源，强光可能伤害你的眼睛。


Before you turn on LED, make sure nobody is watching the LED lighting area. High Luminous Flux can make great hazard to human eyes.



附录：分档标准

Appendix: Ranking Criteria

色坐标分档图 Chromaticity Diagram of Ranking



中性白 Natural White (NW)											
Region	x	y	Region	x	y	Region	x	y	Region	x	y
4A	0.353	0.3597	4B	0.3548	0.3736	4C	0.3641	0.3804	4D	0.3615	0.3659
	0.3615	0.3659		0.3641	0.3804		0.3736	0.3874		0.3702	0.3722
	0.359	0.3521		0.3615	0.3659		0.3702	0.3722		0.367	0.3578
	0.3512	0.3465		0.353	0.3597		0.3615	0.3659		0.359	0.3521
	0.3495	0.3339	4AA	0.3571	0.3907	4CC	0.3671	0.397	4DD	0.3567	0.3389
	0.3512	0.3465		0.3671	0.397		0.3771	0.4034		0.359	0.3521
	0.359	0.3521		0.3641	0.3804		0.3736	0.3874		0.367	0.3578
	0.3567	0.3389		0.3548	0.3736		0.3641	0.3804		0.364	0.344
5A	0.367	0.3578	5B	0.3702	0.3722	5C	0.3825	0.3798	5D	0.3783	0.3646
	0.3702	0.3722		0.3736	0.3874		0.3869	0.3958		0.3825	0.3798
	0.3825	0.3798		0.3869	0.3958		0.4006	0.4044		0.395	0.3875
	0.3783	0.3646		0.3825	0.3798		0.395	0.3875		0.3898	0.3716



佛山市国星光电股份有限公司
FOSHAN NATIONSTAR OPTOELECTRONICS CO., LTD

地址: 佛山市禅城区华宝南路 18 号

Add: NO.18 South Huabao Rd, Foshan, Guangdong China

邮编 (Zip): 528000

电话 (Tel): (0757) 83985604, 83985605, 83985607

传真 (Fax): (0757) 82100221, 82100223

<http://www.nationstar.com>