

Specifications

| Product Name: | GU10 Spotlight | | |
|---------------|----------------|--|--|
| Part No.: | NS-GU10-H3 | | |
| Date: | 2012-11-16 | | |
| Version | V1.0 | | |

| Foshan NationStar Optoelectronics Co., Ltd. | | | | | |
|---|-------|---------|--|--|--|
| LED Lighting Branch | | | | | |
| DRAFT | CHECK | CONFIRM | | | |
| | | | | | |



NS-GU10-H3

1. Product Features:

- 1. Environmental friendly, no Pb or Hg
- 2. No stroboflash, no UV and IR
- 3. Light source is high power LED with high luminous efficiency.
- 4. Optimized reflection lens with higher efficiency of the lamps
- 5. High thermal insulation ceramic matericals, safe and reliable.
- 6. Low consumption, energy saver, long lifespan, high stability and reliable
- 7. CCT: 3000K-6500K.
- 8. Standard GU10 socket.
- 9. In accordance with the RoHS.

2. Application

Widely used in exbition hall, jewellery shops, hotel, shopping mall museum specialty store and other lighting area which needs sopt lighting.

3. Parameters

• Electronic parameters:


| Parameter | Value | Unit |
|---------------------|------------------|---------------|
| Input voltage | AC 100-240 | V |
| Rate input | 4.0 | W |
| IFM | DC 300 | mA |
| Power factor | 0.5 | 1 |
| Frequency | 50/60 | Hz |
| Illumiant | 大功率 LED | - |
| Luminous flux | 200 | Lm |
| Color temperature | 3000-6500 | K |
| CRI | 70 | - |
| Light beam | 30 | degreee |
| Lifespan | 30,000 | hrs |
| Working temperature | -20∼ + 40 | ${\mathbb C}$ |
| Storage temperature | -30∼ + 60 | ${\mathbb C}$ |
| Working humidity | 30%~80% | - |
| Storage humidity | 10%~80% | - |
| Weight | 60 | g |
| Inner box size | 55×55×60 | mm |
| Package size | 310×310×410 | mm |




● Typical Electrical-optical Parameter (30°):

| Louminous flux (Im) | Color rendering index (Ra) | AT 1M | AT 2M | AT 3M |
|---------------------|----------------------------|---------|---------|---------|
| 200-250 | 70 | 950 LUX | 250 LUX | 100 LUX |

● Light Distribution Curve (30°):








4. Optional Parameter

Cold White (CW): 6000K-6500K, viewing angel 30° Nertural White (NW): 4000K-4500K, viewing angel 30° Warm White (WW): 3000K-3500K, viewing angel 30°

5. Dimensions and size




6. Product Picture









Color box package with paper tray inside Inner box dimension: 55mm×55mm×60mm

Outer carton dimension: 310mm×310mm×410mm (150 pcs total)

8. Warning and Liability

- The information contained herein is presented only as a guide for the applications of our products.
- No responsibility is assumed by NationStar for any infringements of intellectual property or other infringements of the rights of third parties that may result from its use
- NationStar is committed to a process of continuous improvements of the quality and features of its products and reserves the right to make changes that result in such improvements.
- NationStar products are not intended for use in applications where extraordinarily high reliability is required to prevent the loss of human life or where failure could result in bodily injury.
- NationStar limits the extent of our liability to the failure product and will replace a failed component or refund the purchase price at NationStar option.
- The parameter above are for reference only, detailed figure are subject to the product.
- NationStar keeps the right to modify the content of specification without giving notice to customers. We apologize for any inconvenience caused.