

Аудио/видео шнур FC-A-0003 1.5m (3.5mm)



Description:

- 1.3.5mm stereo male to male
- 2.nickel plated male connector
- 3.PVC molding style
- 4.Conductor: pure Cu
- 5.Shielding: braid
- 6.Length: 300mm, (10cm-500cm can customized)
7. Wire size: 10*10*0.1mm (copper-clad steel)

3.5mm audio cable

- Connectors: Single stereo plug (male) to male
- Fully molding connectors provide excellent strain relief.
- High-quality coaxial wire with copper braid shield reduces unwanted noise and distortion.
- Gold-plated stereo connectors give you solid corrosion-free contact.
- Easy installation and convenient to carry
- Improves digital signal delivery as compared to standard stereo type audio cables.
- True digital signal maintained by high quality materials and connectors.
- 99.9% pure copper non-OFC conductor.
- High-density double shielding for maximum rejection of EMI and RFI.

- *Technology process: cutting, crimping, welding, assembly and testing*
- *Customized specifications and drawings are accepted*
- *Available for ODM/OEM order*

- *Make samples according to your drawings and specifications.*
- *Used in the most of home appliances, computer, PCB, LCD, TV*
- *Inspections: 100% tested before delively*

Electrical

1.100% open & short test;
2.Hi-Pot: DC 300V 10ms;
3.Insulation Resistance: 10M OHM /300V Min;
4.Contact Resistance: 0.01 OHM Max;
5.Shield upon 95% braid;
6.Working Temperature: -25oC ~ +85oC.

Mechanical

Over mold:	PVC 80Pa ,UL94V-0 Black or white;
Pre mold:	PE Low Density;
Contact:	Copper Alloy;
Insertion Force:	35 N Max;
Withdraw Force:	10 N Min.