




180-7010

Plastic Screws







Cat. No.	Dimensions				Pitch mm	Std. Pkg. pcs
	A mm	B mm	C mm	D mm		
	AS - 306A	3	6	2.5	6	0.5
	AS - 308A	3	8	2.5	6	0.5
	AS - 310A	3	10	2.5	6	0.5
	AS - 312A	3	12	2.5	6	0.5
	AS - 408A	4	8	2.8	7.5	0.7
	AS - 410A	4	10	2.8	7.5	0.7
	AS - 412A	4	12	2.8	7.5	0.7
	AS - 414A	4	14	2.8	7.5	0.7
	AS - 420A	4	20	2.8	7.5	0.7
	AS - 520B	5	20	3.5	9	0.8
	AS - 530B	5	30	3.5	9	0.8
	AS - 620B	6	20	4	10	1
	AS - 630B	6	30	4	10	1
	AS - 640B	6	40	4	10	1
	AS - 3M	3	2.4	5.6	6.4	0.5
	AS - 4M	4	3.2	7	8.1	0.7
	AS - 5M	5	4	8	9.2	0.8
	AS - 6M	6	5	10	11.5	1

- Material : Polycarbonate or Polyamide.
- Color : Natural.
- Application : The screws are the light-weight / vibration-proof / insulated fasteners for building, repairing, and maintaining computer systems.

180-8010

Supporting Foot



Cat. No.		Mounting Hole mm	Dimensions			Thickness T mm	Std. Pkg. pcs
			A mm	B mm	H mm		
	SF1406S	3.1	14	14	5.5	0.8 ~ 1.2	100
	SF1810S	7.8	20	18	10	0.8 ~ 1.2	100
	SF1810A	8.1	20	18	10		
	SF1810P	8.1	20	18	10		
	SF1812A	8.1	20	18	12		
	SF1812P	8.1	20	18	12		
	SF1815A	8.1	20	18	15		
	SF1815P	8.1	20	18	15		
	SF1818A	8.1	20	18	18		
	SF1818P	8.1	20	18	18		
	SF2305S	7.8	25	23	5	0.8 ~ 1.2	10
	SF3008G	3.2	30	30	7.9		
	SF4010G	3.2	40	40	9.6		
	SF5014G	4.1	50	50	14		

- Material (The last letter of Cat. No.) :
S : TPE A : TPE + P.P.
P : P.P. G : ABS + HOT GOLDEN FOIL STAMP.
- No residue remains, easy installation and skid resistant.