

TM5



connectwell
THE RIGHT CONNECTION

Tree marker

Flexible marker carrier can be placed on the double level Terminal block, for visibility of markers and easy identification of Terminal Blocks.

| PRODUCT SPECIFICATION | |
|-----------------------|---------|
| Height | 38.1 mm |
| Length | 21 mm |
| Width (Thickness) | 5 mm |

| ORDERING INFORMATION | | |
|----------------------|---|-----------|
| CAT. NO. | DESCRIPTION | STD. PACK |
| TM5 | Flexible Marker Carrier for double level Terminal Block | 50 |

| SUITABLE FOR | |
|-----------------|--|
| CPDL2.5(E)D1 | 2.5 sq.mm Terminal Blocks with diode circuit - D1 configuration |
| CPDL2.5(E)D2 | 2.5 sq.mm Terminal Blocks with diode circuit - D2 configuration |
| CPDL2.5(E)DD5 | 2.5 sq.mm Terminal Blocks in push-in connection with diode circuit - DD5 configuration |
| CPDLG2.5 | 2.5 sq.mm Double Level Earthing Terminal Blocks. |
| CXDL2.5 | 2.5 sq.mm Double Level Spring Clamp Terminal Blocks |
| CXDLG2.5/2B/I.S | pluggable feed through Spring Clamp Ground Terminal Block Internally shorted in Green Yello colour |
| CPDL2.5 | 2.5 sq.mm Double Level Push in Terminal Blocks |
| CPDL2.5(E)D3 | 2.5 sq.mm Terminal Blocks with in Push In Connection with diode circuit - D3 configuration |
| CPDL2.5(E)DD2 | 2.5 sq.mm Terminal Blocks in pushin connection with diode circuit - DD2 configuration |
| CPDL2.5(E)DD3 | 2.5 sq.mm Terminal Blocks in Push in with diode circuit - DD3 configuration |
| CPDL2.5(E)DD6 | 2.5 sq.mm Terminal Blocks in push-in connection with diode circuit - DD6 configuration |
| CXDLG2.5 | 2.5 sq.mm Double Level Earthing Terminal Blocks. |
| CPDL2.5(E)DD1 | 2.5 sq.mm Terminal Blocks in Pushin connection with diode circuit - DD1 configuration |
| CPDLG2.5(I.S) | 2.5 sq.mm Multiple Connection Earthing Terminal Blocks with 4 connection points. |
| CXDL2.5(I.S) | 2.5 sq.mm Multiple Connection Internally shorted Terminal Blocks with 4 connection points. |
| CXDLG2.5/2B | 2.5 sq.mm Double Level Ground/Earth Spring Clamp Terminal Blocks |
| CPDL2.5(E)DD4 | 2.5 sq.mm Terminal Blocks in push-in connection with diode circuit - DD4 configuration |
| CPDL2.5(E)LD1 | 2.5 sq.mm Double Level Terminal Blocks with LED indication for LD1 Configuration |
| CPDL2.5(E)TS1 | 2.5 sq.mm Double Level Terminal Blocks with Temperature Sensor indication - TS1 Configuration |
| CPDL2.5(I.S) | 2.5 sq.mm Multiple Connection Internally Shorted Terminal Blocks with 4 connection points. |
| CXDLG2.5(I.S) | 2.5 sq.mm Multiple Connection Earthing Terminal Blocks with 4 connection points. |