

Description

Indoor drop coaxial cable for digital reception - 75 Ohm

Cable for digital reception (Screening Class A+)

**Data Sheet****DG113**

Ø	1,13	4,80	4,90	5,30	6,60
	(Cu)	(PEG)	(Al/Pet/Al)	(CuSn)	(PVC)

Standards

EN 50117-2-4

Construction data

Inner conductor of plain copper	(Cu)	Ø 1,13 ± 0,02	mm
Dielectric of physical foam polyethylene	(PEG)	Ø 4,80 ± 0,10	mm
Aluminium/Polyester/Aluminium tape longitudinally overlapped	(Al/Pet/Al)		
Water repellent sealing (dielectric)	(Jelly1)		
Braid of tinned copper wires	(CuSn)		
Braid optical coverage (IEC 96-1)		72	%
Diameter under Sheath		5,30	mm
Outer sheath of Polyvinylchloride - white (PVC) - lead-free	(PVC)	Ø 6,60 ± 0,10	mm
Printed each meter by blue ink-jet :			

CAVEL DG 113 MADE IN ITALY 75 Ohm EN50117-2-4 CEI-UNEL 36762 C-4 (U₀ =400V) * LTE PROTECTION *
ss/aa m

(ss=week, aa=year) (m=meter marking)

Physical data

Weight of copper conductors	19,20	kg/km
Total weight of cable	43,38	kg/km
Minimum bending radius (single/repetead bending)	35/70	mm
Maximum cable pulling strength	150	N
Fire Load	597 MJ/km	166 kWh/km

Electrical data

Characteristic impedance	200 MHz	75 ± 3	Ohm
Capacitance (@1kHz)		52 ± 2	pF/m
Velocity Ratio		85 %	
Inner conductor resistance		18	Ohm/km
Outer conductor resistance		13,90	Ohm/km
Loop resistance		31,90	Ohm/km
Sheat Insulation voltage (spark test)		3	kV
Maximum current (I _{eff})		8	A
Structural return loss (SRL)			
5 - 470 MHz	>30 dB		
470 - 1000 MHz	>28 dB		
1000 - 2000 MHz	>26 dB		
2000 - 3000 MHz	>22 dB		

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
 Tel +39-382.815150 Fax +39-0382.814212

Date

27/02/2012

Responsible

PierPaolo Piccinini

Description

Indoor drop coaxial cable for digital reception - 75 Ohm

Cable for digital reception (Screening Class A+)

Coaxial Cables

CAVEL®

since 1968

Data Sheet**DG113****Screening Attenuation (SA)****Class A+**

30 - 1000 MHz	>95 dB
1000 - 2000 MHz	>90 dB
2000 - 3000 MHz	>80 dB


Shield Transfer Impedance (Zt)

5 - 30 MHz

< 2,5 mOhm/m

Attenuation (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	Frequency [MHz]	Attenuation [dB/100m]
5	1,60	862	17,10
10	2,30	1000	18,50
30	3,20	1750	24,90
50	4,10	2150	27,90
200	8,00	2400	29,60
300	9,80	3000	33,40
470	12,40		

Attenuazione di schermatura / Screening Attenuation**Cavo classe A+ / A+ Class Cable****Cavo tipo / Cable type : DG 113****Connectors**

FA703	Serie F Twist-On, F Twist-On, for indoor installation, nitin-plated brass - 21,0 mm x 12,0 mm
F703	Series F Crimp, F Crimp, for indoor installation, nitin-plated brass - 21,0 mm x 12,0 mm
FR703	Series F Crimp, F crimp, "Rapid", for indoor installation
F90	Series F Crimp, F Crimp, for indoor installation
IECF5.1C	Series IEC (no tool), female, no tool, for indoor installation
IECM5.1C	Series IEC (no tool), male, no tool, for indoor installation
IECF90C	Series IEC (no tool), Ø 5,1 90° female, for indoor installation

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
 Tel +39-382.815150 Fax +39-0382.814212

Date**27/02/2012****Responsible****PierPaolo Piccinini**

Description

Indoor drop coaxial cable for digital reception - 75 Ohm

Cable for digital reception (Screening Class A+)



Data Sheet

DG113**↑↑↑ Connectors**

IECM90C	Series IEC (no tool), Ø 5,1 90° male, for indoor installation
FCPO5.1C	Series F Compression, Ø 5,1 Push-On, for outdoor installation, nitin-plated brass
FC7.0QM	Series F Compression, Quick Mount, for outdoor installation
FC703	Series F Compression, F Compression, for outdoor installation, nitin-plated brass - 30,0 mm x 12,0 mm
IECF703	Serie IEC Compression, female, no tool, for outdoor installation
IECMC703	Serie IEC Compression, male, for outdoor installation
BNCC703	Series BNC Compression, BNC Compression, for outdoor installation, nitin-plated brass - 35,0 mm x 14,0 mm

ITALIANA CONDUTTORI s.r.l.Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

27/02/2012

Responsible

PierPaolo Piccinini