

AG Series Dual-channel Arbitrary Waveform Generator



- + Advanced DDS technology, max 60MHz frequency output
- + Up to 250MS/s sample rate, and 1μHz frequency resolution
- + Vertical Resolution : 14 bits, up to 1M arb waveform length
- + Comprehensive waveform output : 5 basic waveforms, and 45 built-in arbitrary waveforms
- + Comprehensive modulation functions : AM, FM, PM, FSK, PWM, Sweep, and Burst
- + High-accuracy frequency counter integrated, supported range 100mHz - 200MHz
- + Supported SCPI
- + 4 inch high resolution (480 × 320 pixels) TFT LCD display

+ Performance Specifications

Model	AG1012	AG1012F	AG1022	AG1022F	AG2052F	AG2062F
Channel	dual					
Frequency Output	10MHz		25MHz		50MHz	60MHz
Sample Rate	125MS/s					
Vertical Resolution	14 bits					

Waveform

Standard Waveform	Sine, Square, Pulse, Ramp, and Noise			
Arbitrary Waveform	Exponential Rise, Exponential Fall, Sin(x)/x, Step Wave, and others, total 45 built-in waveforms, and user-defined arbitrary waveform			

Frequency (resolution 1μHz)

Sine	1μHz - 10MHz	1μHz - 25MHz	1μHz - 50MHz	1μHz - 60MHz
Square		1μHz - 5MHz	1μHz - 25MHz	1μHz - 30MHz
Pulse		1μHz - 5MHz		1μHz - 10MHz
Ramp			1μHz - 1MHz	
Noise			25MHz (-3dB) (typical)	
Arbitrary Waveform			1μHz - 10MHz	

Amplitude

Amplitude	1m Vpp - 10 Vpp (50Ω), 1m Vpp - 20 Vpp (high impedance)			
Resolution	1m Vpp or 14 bits			
DC Offset Range (AD+DC)	±5V (50Ω), ±10V (high impedance)			
DC Offset Range Resolution	1mV			
Load Impedance	50Ω (typical)			

Model	AG1012	AG1022	AG1012F	AG1022F	AG2052F	AG2062F
Arbitrary Waveform						
Wave Length			2 pts to 8K pts		2 pts to 1M pts	
Sample Rate			125MS/s		250MS/s	
Vertical Resolution					14 bits	
Non-volatile Memory					26 waveforms	
Modulation						
Modulation Waveform	/		AM, FM, PM, FSK, Sweep, and Burst	AM, FM, PM, FSK, PWM, Sweep, and Burst		
Modulation Frequency	/			2mHz to 20.00KHz (FSK 1μHz - 100KHz)		
Counter						
Function	/		Frequency Period, +Width, -Width, +Duty, and -Duty			
Frequency Range	/		100mHz - 200MHz			
Frequency Resolution	/			6 digits		
Input / Output						
Display	4 inch (480 × 320 pixels) TFT LCD					
Type	external reference clock input / output		counter external modulation input / output, external trigger input / output, external reference clock input / output			
Communication Interface	USB host, USB device, RS232					
Mechanical						
Dimension (W×H×D)	235 × 110 × 295 (mm)					
Weight (without package)	3.00 kg					

Specifications subject to change without prior notice.

+ Application

design and debug circuit function test education and training

+ Accessories


The accessories subject to final delivery.



Power Cord



CD Rom



User's Manual



USB Cable



Q9