

PHILIPS

Fortimo

LED

Fortimo FastFlex IP



Datasheet

Fortimo FastFlex IP

Fortimo FastFlex IP Standard is an integrated module solution with IP66 protection, excellent optical and heat management that offers high energy efficacy (greater than 150 lumens per watt) and high quality of light. Fortimo FastFlex IP Standard products are designed to enable optimum LED lighting in Outdoor - streets and roads - applications. A range of compatible IP67 Xitanium drivers complement these modules to further differentiate your lighting solution on efficacy, lifetime and robustness under extreme temperature conditions.

Key features and benefits

- IP66 integrated heat sink and optics
- High energy efficacy, greater than 150 lm/W
- 6000 lumen-level modules
- 3 Color temperatures: 3000K, 4000K, 5700K
- Dedicated light distributions for Outdoor (street/road)
- CRI 70
- Enables complete IP66 system with IP driver
- Easy to design-in with practical optical solutions for Street and Road lighting.
- Easy to install and maintain - CSA compliant, modular solution
- 50K hours at B50L70 at Tc 75°C
- 5 years system warranty

May 2018

Ordering data

Commercial product name	12NC	Box quantity
Fortimo FastFlex IP 6KLM 730 II-S	9290 014 27780	12
Fortimo FastFlex IP 6KLM 740 II-S	9290 014 28180	12
Fortimo FastFlex IP 6KLM 757 II-S	9290 014 28580	12
Fortimo FastFlex IP 6KLM 730 II-M	9290 014 27880	12
Fortimo FastFlex IP 6KLM 740 II-M	9290 014 28280	12
Fortimo FastFlex IP 6KLM 757 II-M	9290 014 28680	12
Fortimo FastFlex IP 6KLM 730 III-S	9290 014 27980	12
Fortimo FastFlex IP 6KLM 740 III-S	9290 014 28380	12
Fortimo FastFlex IP 6KLM 757 III-S	9290 014 28780	12
Fortimo FastFlex IP 6KLM 730 III-M	9290 014 28080	12
Fortimo FastFlex IP 6KLM 740 III-M	9290 014 28480	12
Fortimo FastFlex IP 6KLM 757 III-M	9290 014 28880	12

Drive currents

Parameter	Nominal*	Life**	Max***	Unit
Fortimo FastFlex IP	700	700	1296	mA

Module temperatures

Parameter	Nominal*	Life**	Max***	Unit
T _c (case temperature at T _c point)	50	75	90	°C

* Nominal value at which typical performance is specified

** Value at which life time is specified

*** Maximum value for safe operation, do not operate above this value


Optical characteristics - table per color (CCT)

[Fortimo FastFlex IP 6KLM 730 II-S](#)
[Fortimo FastFlex IP 6KLM 730 II-M](#)
[Fortimo FastFlex IP 6KLM 730 III-S](#)
[Fortimo FastFlex IP 6KLM 730 III-M](#)

Parameter	Min	Typ	Max	Unit
Luminous flux	5310	5900	7080	lm
Module efficacy	129	143		lm/W
Correlated color temperature (CCT)		3000		K
Color coordinates (CIEx, CIEy)		(0.437, 0.406)		-
Color consistency			5	SDCM
CRI	70			
Photobiological safety			RG2	
Ethr			502	lux

Measurement precision for flux +/- 5%. Measurement precision for efficacy +/- 6%. Measurement precision for x, y +/- 0.005. Measurement precision for CRI 1.5

Operation point	730	lm	lm/W
80% I-nom 560mA	Tc 25 °C	4977	151
	Tc-nom 50 °C	4821	147
	Tc-max 90 °C	4615	142
I-nom 700mA	Tc 25 °C	6097	144
	Tc-nom 50 °C	5900	140
	Tc-max 90 °C	5641	135
I-life 700mA	Tc 25 °C	6097	144
	Tc-nom 50 °C	5900	140
	Tc-max 90 °C	5641	135




[Fortimo FastFlex IP 6KLM 740 II-S](#)
[Fortimo FastFlex IP 6KLM 740 II-M](#)
[Fortimo FastFlex IP 6KLM 740 III-S](#)
[Fortimo FastFlex IP 6KLM 740 III-M](#)

Parameter	Min	Typ	Max	Unit
Luminous flux	5625	6250	7500	lm
Module efficacy	136	151		lm/W
Correlated color temperature (CCT)		4000		K
Color coordinates (CIEx, CIEy)		(0.385, 0.383)		-
Color consistency			5	SDCM
CRI	70			
Photobiological safety			RG2	
Ethr			502	lux

Measurement precision for flux +/- 5%. Measurement precision for efficacy +/- 6%. Measurement precision for x, y +/- 0.005. Measurement precision for CRI 1.5

Operation point	740	lm	lm/W
80% I-nom 560mA	Tc 25 °C	5272	160
	Tc-nom 50 °C	5106	156
	Tc-max 90 °C	4889	150
I-nom 700mA	Tc 25 °C	6458	153
	Tc-nom 50 °C	6250	149
	Tc-max 90 °C	5976	143
I-life 700mA	Tc 25 °C	6458	153
	Tc-nom 50 °C	6250	149
	Tc-max 90 °C	5976	143




Fortimo FastFlex IP 6KLM 757 II-S
Fortimo FastFlex IP 6KLM 757 II-M
Fortimo FastFlex IP 6KLM 757 III-S
Fortimo FastFlex IP 6KLM 757 III-M

Parameter	Min	Typ	Max	Unit
Luminous flux	5625	6250	7500	lm
Module efficacy	136	151		lm/W
Correlated color temperature (CCT)		5700		K
Color coordinates (CIEx, CIEy)		(0.333, 0.348)		-
Color consistency			5	SDCM
CRI	70			
Photobiological safety			RG2	
Ethr			502	lux


Measurement precision for flux +/- 5%. Measurement precision for efficacy +/- 6%. Measurement precision for x, y +/- 0.005. Measurement precision for CRI 1.5

Operation point	757	lm	lm/W
80% I-nom 560mA	Tc 25 °C	5272	160
	Tc-nom 50 °C	5106	156
	Tc-max 90 °C	4889	150
I-nom 700mA	Tc 25 °C	6458	153
	Tc-nom 50 °C	6250	149
	Tc-max 90 °C	5976	143
I-life 700mA	Tc 25 °C	6458	153
	Tc-nom 50 °C	6250	149
	Tc-max 90 °C	5976	143




Beam shape

Light distributions of Type II S (left) and M (right)



Light distributions of Type III S (left) and M (right)



Electrical characteristics

[Fortimo FastFlex IP 6KLM 730 II-S](#)
[Fortimo FastFlex IP 6KLM 740 II-S](#)
[Fortimo FastFlex IP 6KLM 757 II-S](#)
[Fortimo FastFlex IP 6KLM 730 II-M](#)
[Fortimo FastFlex IP 6KLM 740 II-M](#)
[Fortimo FastFlex IP 6KLM 757 II-M](#)
[Fortimo FastFlex IP 6KLM 730 III-S](#)
[Fortimo FastFlex IP 6KLM 740 III-S](#)
[Fortimo FastFlex IP 6KLM 757 III-S](#)
[Fortimo FastFlex IP 6KLM 730 III-M](#)
[Fortimo FastFlex IP 6KLM 740 III-M](#)
[Fortimo FastFlex IP 6KLM 757 III-M](#)


Parameter	Min	Typ	Max	Unit
Forward voltage	58.0	59.0	62.0	V
Power consumption	40.6	41.3	43.4	W
Thermal power		21.9		W
Number of modules in series per chain			5	
Number of modules in parallel per chain			1	

Measurement precision for Vf +/- 3%. Measurement precision for power +/- 3.3%
 Specifications stated at Tc-nom and I-nom

Tuning information


Flux and efficacy versus current (at T_c nominal)

I [mA]	Flux [%]	Efficacy [%]
700	100	100
700	100	100
700	100	100
560	82	105
350	53	112



Flux and efficacy versus temperature at T_c (at I nominal)

T _{case} [°C]	Flux [%]	Efficacy [%]
75	96	96
50	100	100
25	103	103
0	106	104




Lifetime

Parameter	Value	Unit
C10 at T _c life	50000	hours

L70B50 50000 hours

Lumen maintenance graphs


Lumen maintenance at I-life and Tc-life conditions



Mechanical characteristics

- Fortimo FastFlex IP 6KLM 730 II-S
- Fortimo FastFlex IP 6KLM 740 II-S
- Fortimo FastFlex IP 6KLM 757 II-S
- Fortimo FastFlex IP 6KLM 730 II-M
- Fortimo FastFlex IP 6KLM 740 II-M
- Fortimo FastFlex IP 6KLM 757 II-M
- Fortimo FastFlex IP 6KLM 730 III-S
- Fortimo FastFlex IP 6KLM 740 III-S
- Fortimo FastFlex IP 6KLM 757 III-S
- Fortimo FastFlex IP 6KLM 730 III-M
- Fortimo FastFlex IP 6KLM 740 III-M
- Fortimo FastFlex IP 6KLM 757 III-M

Parameter	Min	Typ	Max	Unit
Length	299.5	300	300	mm
Width	69.5	70	70	mm
Height without cable	46.8	47.3	47.8	mm
Height with cable		66.8		mm



Absolute ratings

Parameter	Min	Typ	Max	Unit
Current through the LED module (I-max)			1296	mA
Case temperature (Tc-max)			90	°C
Power at rated Vf-max and I-max			84	W
Working voltage			500	V _{dc}
Ambient temperature	-30		50	°C
Storage temperature	-40		65	°C

Application information

Certificates and Standards

IEC/EN 62031


IEC TR 62278

IEC 62717

Application

IP rating	IP-rating 66, IK-rating 08
Dimming	Yes

Performance Window





© 2018 Philips Lighting Holding B.V. All rights reserved.

This document contains information relating to the Philips Lighting portfolio, intended for companies who may be interested in developing their product offering. Note that the information provided is subject to change. Philips Lighting does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract.

www.philips.com/technology

05/2018