

PHILIPS

Outdoor SPD

Surge Protector
Class-II



Datasheet

Protect your outdoor luminaires against damaging spikes and transients

Outdoor SPD - Surge Protector Class-II

The unique solution for Outdoor lighting systems offering full protection against high surges in insulation Class II installations.

Benefits

- Maximize the lifetime of outdoor lighting applications
- Lower maintenance costs
- Easy to apply in new or existing installations

Features

- Suitable for insulation Class II luminaires only
- Long lifetime, robust protection against vibration and temperature
- Provides high surge protection of up to 10 kV / 10 kA for all lighting technologies
- Optical failure indicator

Application

- Highways
- Rural roads
- Industrial zones
- Open space parking areas

Insulation Class	Application field				
	TN	TNC	TNS	TNCS	TT
Class II	✓	✓	✓	✓	✓

June 2017

Logistical data

Specification item	Value
Product name	Surge Protector Class-II
European order code	8718696 772829 00
Logistic code 12NC	9290 016 07106
Pieces per box	20

Electrical Specifications

Specifications	Parameter	Value	Unit	Condition
Certifications		CE		
Designation		Type 3		Acc. EN61643-11
Classification		Class III		Acc. IEC61643-11
Protection mode		Diff. mode		
Nominal input voltage	U_n (L-N)	230	VAC	50 ... 60 Hz, max. +10%
Max. continuous operating voltage	U_c (L-N)	255	VAC	50 ... 60 Hz
Power grids		TN, TT		Incl. all TN varieties TN-C, TN-C-S, TN-S
Nominal discharge current	I_n (L-N)	5	kA	8/20 μ s
Max. voltage protection level at I_n	U_p (L-N)	1,5	kV	See separate protection level table for other I_n values
Open-circuit voltage	U_{oc}	10	kV	
Backup fuse		20	A	max., gG fuse
End of life indication		yes		Optical, light ON: SPD is functional. Light OFF: SPD has reached end-of-life
Servicability		n/a		No user servicable parts inside

Other specifications


Specifications	Parameter	Value	Unit	Condition
Surge withstand capability		1	strike	max. at 10 kA
Surge withstand capability		50	strikes	min. at 5 kA
Surge withstand capability		100	strikes	min. at 3 kA
Nominal current		4	A	Rated load current at 50 ... 60 Hz
Power consumption		0.001	W	max. at $U_c = 255$ VAC
Suitable for luminaires		Class II only		Insulation Class acc. IEC60598

Protection levels U_p

Surge Protector Class-II

I_c 8/20 μ s	Differential mode U_2
1 kA	1100 V
3 kA	1250 V

I_c 8/20 μ s	Differential mode U_2
5 kA	1350 V
10 kA	1500 V




Environmental conditions

Specification item	Value	Unit	Condition
Ambient temperature	-40...70	°C	
Tcase-max.	80	°C	Measured at Tc-point
Storage temperature	-40...85	°C	
Relative humidity	5...95	%	Non-condensing
Suitable for outdoor luminaires	Yes		Built-in only

Lifetime

Specification item	Value	Unit	Condition
Lifetime	100,000	hours	Measured @ Tcase-max with min 90% survival

Product dimensions




Specification item	Value	Unit
Mounting length	70	mm
Overall length	90	mm
Case Width	45	mm
Case Height	37.5	mm
Fixing hole diameter	M4	
Fixing screw type	M8	
Max. screw torque	0.8	Nm
Weight	70	gr

Wiring

Specification item	Value	Unit	Condition
Connector type	Push-in		Single wire only
Wire diameter	0.5...2.5	mm ²	Solid and stranded
Wire strip length	10...11	mm	

Wiring diagram Insulation Class II application



Electrical connections

Signal	Description	Color
LINE	Line connection	Black
LINE	Line connection	Black
NEUTRAL	Neutral connection	White
NEUTRAL	Neutral connection	White



© Philips Lighting Holding B.V. 2017. All rights reserved. Philips reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

Date of release: 06/2017

www.philips.com/surgeprotection