


**DOUBLE DIODE-OUTPUT PENTODE
DOUBLE DIODE-PENTHODE DE SORTIE
DOPPELDIODE-ENDPENTHODE**

Heating: indirect by A.C. or D.C.;
series supply


Chauffage: indirect par C.A. ou C.C.; $V_f = 44$ V
alimentation en série $I_f = 0,2$ A

Heizung: indirekt durch Wechsel-
oder Gleichstrom;
Serienpeisung


Dimensions in mm
Dimensions en mm
Abmessungen in mm



P-base



Culot P



P-Fuss

Capacitances
Capacités
Kapazitäten

Pentode section
Partie penthode
Pentodenteil

$$C_{ag1} < 0,5 \text{ pF}$$

Diode section
Partie diode
Diodenteil

$$Cd1k = 3,0 \text{ pF}$$

$$Cd2k = 2,7 \text{ pF}$$

$$Cd1f < 1,0 \text{ pF}$$

$$Cd2f < 0,4 \text{ pF}$$

$$Cd1d2 < 0,4 \text{ pF}$$

Between pentode and diode sections
Entre les parties penthode et diode
Zwischen Penthoden- und Diodenteil

$$Cd1g1 < 0,05 \text{ pF}$$

$$Cd2g1 < 0,05 \text{ pF}$$

$$Cd1a < 0,4 \text{ pF}$$

$$Cd2a < 0,3 \text{ pF}$$

Operating characteristics
Caractéristiques d'utilisation
Betriebsdaten

V _a	=	100	200 V
V _{g2}	=	100	100 V
R _k	=	140	190 Ω
V _{g1}	=	-8	-9,2 V
I _a	=	45	40 mA
I _{g2}	=	12	9 mA
S	=	6,5	6,2 mA/V
R _i	=	20	37 kΩ
R _a	=	2,2	5 kΩ
W _o (d = 10%)	=	1,8	3,8 W
V _i (d = 10%)	=	7,0	7,3 V _{eff}
V _i (W _o = 50 mW)	=	0,6	0,8 V _{eff}

Limiting values of the pentode section
Caractéristiques limites de la partie penthode
Grenzdaten des Penthodenteiles

V _{a0}	=	max.	550 V
V _a	=	max.	250 V
W _a	=	max.	9 W
V _{g20}	=	max.	550 V
V _{g2}	=	max.	125 V
W _{g2} (V _i = 0)	=	max.	1,3 W
W _{g2} (W _o = max.)	=	max.	2,5 W
I _k	=	max.	90 mA
V _{g1} (I _{g1} = +0,3 μA)	=	max.	-1,3 V
R _{g1}	=	max.	1 MΩ
R _{fk}	=	max.	5 kΩ
V _{fk}	=	max.	175 V

Limiting values of the diode section
Caractéristiques limites de la partie diode
Grenzdaten des Diodenteiles

V _{d1} = max. 200 V ¹)	I _{d2}	= max.	0,8 mA
V _{d2} = max. 200 V ¹)	V _{d1} (I _{d1} =+0,3μA)=	max.	-1,3 V
I _{d1} = max. 0,8 mA	V _{d2} (I _{d2} =+0,3μA)=	max.	-1,3 V

¹) Peak value; valeur de crête; Scheitelwert

PHILIPS

Electronic
Tube

HANDBOOK

page	CBL6 sheet	date
1	1	1949.10.10
2	2	1949.10.10
3	FP	1999.07.16