



10-Y

10-Y

POWER AMPLIFIER TRIODE

GENERAL DATA

Electrical:

Filament, Thoriated Tungsten:

Voltage	7.5	ac or dc volts
Current	1.25	amp

Amplification Factor 8

Direct Interelectrode Capacitances (Approx.):

Grid to Plate	7	$\mu\mu f$
Grid to Filament	4	$\mu\mu f$
Plate to Filament	3	$\mu\mu f$

Mechanical:

Mounting Position Vertical, base down

Maximum Overall Length 5-3/8"


Maximum Seated Length 4-3/4"

Maximum Diameter 2-1/16"

Bulb ST-16

Base Medium-Shell Small 4-Pin Micanol, Bayonet
Basing Designation for BOTTOM VIEW 4D

Pin 1 - Filament



Pin 3 - Grid

Pin 2 - Plate

Pin 4 - Filament

PLATE-MODULATED RF POWER AMPLIFIER - Class C Telephony

Carrier conditions per tube for use with a max. modulation factor of 1.0

Maximum Ratings, Absolute Values:

DC PLATE VOLTAGE	350	max.	volts
DC GRID VOLTAGE	-200	max.	volts
DC PLATE CURRENT	60	max.	ma.
DC GRID CURRENT	15	max.	ma.
PLATE INPUT	17.5	max.	watts
PLATE DISSIPATION	10	max.	watts

Typical Operation:

DC Plate Voltage	250	350	. . .	volts
DC Grid Voltage	-95	-135	. . .	volts
Peak RF Grid Voltage	195	235	. . .	volts
DC Plate Current	45	45	. . .	ma.
DC Grid Current (Approx.) [□]	15	15	. . .	ma.
Driving Power (Approx.) [□]	3	3.5	. . .	watts
Power Output (Approx.)	5.5	8	. . .	watts

Subject to wide variations as explained on sheet TUBE RATINGS in General Section.



10-Y

POWER AMPLIFIER TRIODE

RF POWER AMPLIFIER & OSCILLATOR - Class C Telegraphy

Key-down conditions per tube without modulation [□]

Maximum Ratings, Absolute Values:

DC PLATE VOLTAGE	450	max.	volts
DC GRID VOLTAGE.	-200	max.	volts
DC PLATE CURRENT	60	max.	ma.
DC GRID CURRENT.	15	max.	ma.
PLATE INPUT.	27	max.	watts
PLATE DISSIPATION.	15	max.	watts

Typical Operation:

DC Plate Voltage	350	450	. . .	volts
DC Grid Voltage.	-90	-115	. . .	volts
Peak RF Grid Voltage	190	215	. . .	volts
DC Plate Current	55	55	. . .	ma.
DC Grid Current (Approx.) [□]	15	15	. . .	ma.
Driving Power (Approx.) [□]	3	3.3	. . .	watts
Power Output (Approx.)	9	13	. . .	watts

[□] Subject to wide variations as explained on sheet TUBE RATINGS in General Section.

[□] Modulation essentially negative may be used if the positive peak of the audio-frequency envelope does not exceed 115% of the carrier conditions.

Data on operating frequencies for the 10-Y are given on the sheet TRANS. TUBE RATINGS vs FREQUENCY