

14AF7  
TO  
14C5



## 14AF7

### MEDIUM-MU TWIN TRIODE

(continued from preceding page)

Amplification Factor . . . . .	17	16	16	
Plate Resistance . . . . .	6500	8400	7600	ohms
Transconductance . . . . .	2600	1900	2100	μmhos
Plate Current . . . . .	10.8	5	9	ma

## 14B6

### TWIN DIODE—HIGH-MU TRIODE

Heater, for Unipotential Cathode:

Voltage . . . . . 12.6<sup>□</sup> . . . . . ac or dc volts  
 Current . . . . . 0.15<sup>□□</sup> . . . . . amp

*The 14B6 is the same as the 7B6 except for heater rating.*

<sup>□</sup> Nominal voltage = 14.0 volts.

<sup>□□</sup> Nominal current = 0.16 ampere.

## 14B8

### PENTAGRID CONVERTER

Heater, for Unipotential Cathode:

Voltage . . . . . 12.6<sup>□</sup> . . . . . ac or dc volts  
 Current . . . . . 0.15<sup>□□</sup> . . . . . amp

*The 14B8 is the same as the 7B8 except for heater rating.*

<sup>□</sup> Nominal voltage = 14.0 volts.

<sup>□□</sup> Nominal current = 0.16 ampere.

## 14C5

### BEAM POWER AMPLIFIER

Heater, for Unipotential Cathode:

Voltage . . . . . 12.6<sup>□</sup> . . . . . ac or dc volts  
 Current . . . . . 0.225<sup>□□</sup> . . . . . amp

*The 14C5 is the same as the 7C5 except for heater rating.*

<sup>□</sup> Nominal voltage = 14.0 volts.

<sup>□□</sup> Nominal current = 0.240 ampere.