

## BEAM POWER AMPLIFIER

35A5

GENERAL DATA**Electrical:**

Heater, for Unipotential Cathode:

Voltage. . . . . 35.0 . . . . . ac or dc volts  
Current. . . . . 0.15 . . . . . amp**Mechanical:**

Mounting Position. . . . .	. . . . .	Any
Maximum Overall Length	. . . . .	3-5/32"
Maximum Seated Length.	. . . . .	2-5/8"
Maximum Diameter . . . . .	. . . . .	1-3/16"
Bulb . . . . .	. . . . .	T-9
Base . . . . .	. . . . .	Lock-in 8-Pin
Basing Designation for BOTTOM VIEW . . . . .	. . . . .	6AA
Pin 1 - Heater	. . . . .	Pin 6 - Grid No. 1
Pin 2 - Plate	. . . . .	Pin 7 - Cathode, Grid No. 3
Pin 3 - Grid No. 2	. . . . .	Pin 8 - Heater
Pin 4 - No Connection	. . . . .	Plug - Base Shell
Pin 5 - No Connection	. . . . .	


AF POWER AMPLIFIER - Class A1**Maximum Ratings, Design-Center Values:**

PLATE VOLTAGE. . . . .	200	max.	volts
GRID-No. 2 (SCREEN) VOLTAGE . . . . .	125	max.	volts
PLATE DISSIPATION. . . . .	8.5	max.	watts
GRID-No. 2 DISSIPATION. . . . .	1.0	max.	watt
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode.	90	max.	volts
Heater positive with respect to cathode.	90	max.	volts

**Typical Operation and Characteristics:**

Plate Voltage. . . . .	110	200	. .	volts
Grid-No. 2 Voltage . . . . .	110	110	. .	volts
Grid-No. 1 (Control-Grid) Voltage . . . . .	-7.5	-8	. .	volts
Zero-Signal Plate Current. . . . .	40	41	. .	ma.
Max.-Signal Plate Current. . . . .	41	44	. .	ma.
Zero-Signal Grid-No. 2 Current. . . . .	3.0	2.0	. .	ma.
Max.-Signal Grid-No. 2 Current. . . . .	7.0	7.0	. .	ma.
Plate Resistance (Approx.) . . . . .	16000	40000	. .	ohms
Transconductance . . . . .	5800	5900	. .	$\mu$ hos
Load Resistance. . . . .	2500	4500	. .	ohms
Total Harmonic Distortion. . . . .	10	10	. .	%
Max.-Sig. Power Output . . . . .	1.5	3.3	. .	watts

**Maximum Circuit Values (for maximum rated conditions):**

Grid-No. 1-Circuit Resistance:

For fixed bias . . . . . 0.1 . . megohm  
For cathode bias . . . . . 0.5 . . megohm