

Medium-Mu Triode-

Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

Electrical:

Heater Characteristics and Ratings:

Voltage (AC or DC)	6.3 ^a	6.3 ± 0.6	volts
Current	0.450 + 0.030	0.450 ^b	amp
Warm-up time (Average)	11	-	sec

Peak heater-cathode voltage (Each unit):

Heater negative with respect to cathode . .	200 max.	volts
Heater positive with respect to cathode . .	200 ^c max.	volts

Direct Interelectrode Capacitances:

	Without External Shield	With External Shield ^d	
<i>Triode Unit:</i>			
Grid to plate	1.8	1.8	pf
Grid to cathode, pentode cathode & pentode No. 3 & internal shield, and heater	2.8	2.8	pf
Plate to cathode, pentode cathode & pentode grid No. 3 & internal shield, and heater	1.5	2	pf
<i>Pentode Unit:</i>			
Grid No. 1 to plate	0.02 max.	0.01 max.	pf
Grid No. 1 to cathode & grid No. 3 & internal shield, grid No. 2, and heater	5	5	pf
Plate to cathode & grid No. 3 & internal shield, grid No. 2, and heater	2	3	pf
Pentode plate to triode plate	0.15 max.	0.03 max.	pf

Characteristics, Class A₁ Amplifier:

	Triode Unit	Pentode Unit	
Plate Voltage	125	125	volts
Grid-No. 2 Voltage	-	125	volts
Grid-No. 1 Voltage	-1	-1	volt
Amplification Factor	45	-	
Plate Resistance (Approx.)	5600	200000	ohms
Transconductance	8000	6500	μmhos
Plate Current	12	12	ma
Grid-No. 2 Current	-	4	ma
Grid-No. 1 Voltage (Approx.) for plate μa = 20	-7.5	-9	volts

Mechanical:


Operating Position	Any
Maximum Overall Length	2-3/16"
Maximum Seated Length	1-15/16"
Length, Base Seat to Bulb Top (Excluding tip)	1-9/16" ± 3/32"
Diameter	0.750" to 0.875"



6FV8A

Dimensional Outline See General Section
Bulb. T6-1/2
Base. Small-Button Naval 9-Pin (JEDEC No. E9-1)
Basing Designation for BOTTOM VIEW. 9FA

Pin 1 - Triode Grid
Pin 2 - Triode Plate
Pin 3 - Triode Cathode
Pin 4 - Heater
Pin 5 - Heater
Pin 6 - Pentode Plate
Pin 7 - Pentode Grid No. 2
Pin 8 - Pentode Cathode, Grid No. 3,
 Internal Shield
Pin 9 - Pentode Grid No. 1



AMPLIFIER — Class A₁ (Pentode Unit)

Maximum Ratings, Design-Maximum Values:

Plate Voltage 330 max. volts
Grid-No. 2 (Screen-Grid) Supply Voltage. . . 330 max. volts
Grid-No. 2 Voltage See Grid-No. 2 Input Rating Chart at front of Receiving Tube Section

Grid-No. 1 (Control-Grid) Voltage:

Positive-bias value 0 max. volts

Grid-No. 2 Input:

For grid-No. 2 voltages up to 165 volts. . 0.55 max. watt

For grid-No. 2 voltages between 165 and 330 volts See Grid-No. 2 Input Rating Chart at front of Receiving Tube Section

Plate Dissipation 2.3 max. watts

Maximum Circuit Values:

Grid-No. 1-Circuit Resistance:

For fixed-bias operation. 0.25 max. megohm

For cathode-bias operation. 1 max. megohm

VERTICAL-DEFLECTION OSCILLATOR (Triode Unit)

Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system^e
DC Plate Voltage. 330 max. volts
Peak Negative-Pulse Grid Voltage. 250 max. volts

Cathode Current:

Peak. 70 max. ma

Average 20 max. ma

Plate Dissipation 2 max. watts

Maximum Circuit Values:

Grid-Circuit Resistance:

For cathode-bias operation. 3 max. megohms

a At heater amperes = 0.450.

b At heater volts = 6.3.

c The dc component must not exceed 100 volts.

d With external shield JEDEC No. 315 connected to pin 4.

e As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations," Federal Communications Commission.

