



7AH7

7AH7

REMOTE-CUTOFF PENTODE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage	6.3 [□]	ac or dc volts
Current	0.15 ^{□□}	amp

Direct Interelectrode Capacitances:⁰


Grid No.1 to Plate	0.005 max.	μf
Input	7	μf
Output	6.5	μf

⁰ with external shield connected to cathode.

Mechanical:

Mounting Position	Any
Maximum Overall Length	2-25/32"
Maximum Seated Length	2-1/4"
Maximum Diameter	1-3/16"
Bulb	T-9
Base	Lock-in 8-Pin
Basing Designation for BOTTOM VIEW	8V

Pin 1-Heater
 Pin 2-Plate
 Pin 3-Grid No.2
 Pin 4-Grid No.3
 Pin 5-Internal
 Shield



Pin 6-Grid No.1
 Pin 7-Cathode
 Pin 8-Heater

Plug - Base
Shell

AMPLIFIER - Class A₁

Maximum Ratings, Design-Center Values:

PLATE VOLTAGE	300 max.	volts
GRID-No.2 (SCREEN) VOLTAGE	300 max.	volts
PLATE DISSIPATION	2 max.	watts
GRID-No.2 DISSIPATION	0.7 max.	watt
GRID-No.1 (CONTROL-GRID) VOLTAGE:		
Negative bias value	-1 min.	volt
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode	90 max.	volts
Heater positive with respect to cathode	90 max.	volts

Typical Operation and Characteristics:

Plate Voltage	250	volts
Grid No.3 (Suppressor)	Connected to cathode at socket	
Internal Shield	Connected to cathode at socket	
Grid-No.2 Voltage	250	volts
Cathode-Bias Resistor*	250	ohms
Plate Resistance (Approx.)	1	megohm
Transconductance	3300	μhos
Grid-No.1 Bias (Approx.) for transconductance of 35 μhos	-20	volts

* Fixed bias not recommended.

□ Nominal voltage = 7.0 volts.

□□ Nominal current = 0.16 ampere.

7AH7



7AH7

REMOTE-CUTOFF PENTODE

Plate Current.	6.8	ma
Grid-No.2 Current.	1.9	ma