

-PRODUCT INFORMATION-

Compactron Triode-Pentode

16LU8-A

Page 1

10-68

FOR TV VERTICAL-DEFLECTION OSCILLATOR AND AMPLIFIER APPLICATIONS

The 16LU8-A is a compactron containing a medium-mu triode and a beam pentode. The triode is designed for service as a vertical-deflection oscillator and the pentode as a vertical-deflection amplifier in television receivers. Except for heater characteristics and shorter bulb length, the 16LU8-A is identical to the 6LU8.

GENERAL

ELECTRICAL

Cathode - Coated Unipotential

Heater Characteristics and Ratings Heater Voltage, AC or DC* Heater Current●	04 Amperes
MECHANICAL Outline Drawing - EIA 12-56	
Maximum Diameter	62 Inches
Minimum Diameter	38 Inches
Maximum Over-all Length	
Maximum Seated Height	
Minimum Seated Height 2.2	50 Inches

NOTES

- ★ Heater voltage for a bogey tube at If = 0.6 amperes.
- The equipment designer should design the equipment so that heater current is centered at the specified bogey value, with heater supply variations restricted to maintain heater current within the specified tolerance.
- ♦ The time required for the voltage across the heater to reach 80 percent of the bogey value after applying 4 times the bogey heater voltage to a circuit consisting of the tube heater in series with a resistance equal to 3 times the bogey heater voltage divided by the bogey heater current.

The tubes and arrangements disclosed herein may be covered by patents of General Electric Company or others. Neither the disclosure of any information herein nor the sale of tubes by General Electric Company conveys any license under patent claims covering combinations of tubes with other devices or elements. In the absence of an

express written agreement to the contrary, General Electric Company assumes no liability for patent infringement arising out of any use of the tubes with other devices or elements by any purchaser of tubes or others.



TUBE DEPARTMENT



Owensboro, Kentucky 42301