
TUNG-SOL -

DOUBLE TRIODE

MINIATURE TYPE



COATED UNIPOTENTIAL CATHODE

HEATER

SERIES 12.6 VOLTS 225 MA. PARALLEL 6.3 VOLTS 450 MA.

AC OR DC

FOR 12.6 VOLT OPERATION APPLY HEATER VOLTAGE BETWEEN PINS *4 AND *5. FOR 6.3 VOLT OPERATION APPLY HEATER VOLTAGE BETWEEN PIN *9 AND PINS *4 AND *5 CONNECTED TOGETHER.

BOTTOM VIEW
MINIATURE BUTTON
9 PIN BASE

9.6

ANY MOUNTING POSITION

THE 12AZ7 COMBINES TWO INDEPENDENT MEDIUM-MU TRIODES IN THE 9 PIN MINIATURE CONSTRUCTION: IT IS ADAPTABLE TO APPLICATION EITHER AS AN AF AMPLIFIER OR AS COMBINED OSCILLATOR AND MIXER.

DIRECT INTERELECTRODE CAPACITANCES -

	WITHOUT SHIELD	WITH SHIELD #315 A	
GRID TO PLATE: (G TO P) EACH SECTION	2.0	1.9	μμf
INPUT: G TO (H+K) EACH SECTION	2.6 -	2.8 -	μμ f
OUTPUT: P TO (H+K) SECTION #1	0.44 -	1.4 -	μμf
SECTION #2	0.36	1.6	μμf

Awith internal shield #315 connected to cathode of section under test.

RATINGS

INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM

EACH TRIODE UNIT

			VOLTS-
HEATER VOLTAGE	12.6	6.3	VOLTS
MAXIMUM PLATE VOLTAGE	300		VOLTS
MAXIMUM NEGATIVE DC GRID VOLTAGE	-50		VOLTS
MAXIMUM PLATE DISSIPATION	2.5		WATTS

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

RATINGS -CONT'D. INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM

EACH TRIODE UNIT

MAXIMUM HEATER—CATHODE VOLTAGE: HEATER NEGATIVE WITH RESPECT TO CATHODE		
TOTAL DC AND PEAK	200	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE		
DC	100	VOLTS
TOTAL DC AND PEAK	200	VOLTS
MAXIMUM GRID-CIRCUIT RESISTANCE:*		
FOR CATHODE-BIAS OPERATION	1.0	ME GOHMS
FOR FIXED BIAS OPERATION	0.25	MEGOHMS

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

CLASS A1 AMPLIFIER - EACH TRIODE UNIT

HEATER VOLTAGE HEATER CURRENT	6.3 450	12.6 225	6.3 450	12.6 225	VOLTS MA.
PLATE VOLTAGE	490	100	250		VOLTS
CATHODE BIAS RESISTOR		270	200		OHMS
PLATE CURRENT		3.7	10		MA.
PLATE RESISTANCE		000		900	OHMS
TRANSCONDUCTANCE	4	000	5	500	µмноs
AMPLIFICATION FACTOR		60		60	
GRID VOLTAGE (APPROX.) FOR I _b = 10 μΑ.		- 5		-12	VOLTS

^{*} INDICATES ÀN ADDITION.

⁻⁻⁻⁻ INDICATES A CHANGE.