



## SARGENT HIGH SPEED "Enclosed Head" MICRO AND SEMI MICRO CENTRIFUGES

There are no externally moving parts and therefore no possibility for injury from accidental contact with an exposed, revolving head. The head is completely enclosed in a lightweight cast metal housing having walls  $\frac{1}{4}$ " thick.

Centrifuges of this design are available in models taking shields to accommodate glassware ranging from 0.5 ml to 5 ml centrifuge tubes or 4 x  $\frac{1}{2}$  inch test tubes. Speeds range from 3300 to 4400 r.p.m. depending on current and tube and shield combinations.

These centrifuges are stable and free of vibration. They are equipped with "on" and "off" switch, cover and three rubber feet to prevent creeping. All models operate from 115 volt A.C. or D.C. circuits.

**S-46800 Micro Centrifuge**—Angle Head, Four Place, Sargent. With angle head, 4 shields with rubber cushions to take 0.5, 1 and 2 ml standard centrifuge tubes and cover but without glassware.....**\$28.50**

**S-46801 Semi-Micro Centrifuge**—Takes standard 3 ml centrifuge tubes or 10x75 mm test tubes. Without glassware.....**\$28.70**

**S-46797 Semi-Micro Centrifuge**—Takes 4 x  $\frac{1}{2}$  inch test tubes or 5 ml conical centrifuge tubes. Without glassware.....**\$34.00**

**S-46808 Adapter**—Used with No. 46797 semi-micro centrifuge to take No. 46802 shield which accommodates 0.5, 1, and 2 ml centrifuge tubes and No. 46803 shield for 3 ml centrifuge tubes and 10 x 75 mm test tubes. Each .....**\$0.25**

**S-46802 Micro Shield**—For 0.5, 1 and 2 ml centrifuge tubes .....**\$0.55**

**S-46803 Shield**—For 3 ml centrifuge tubes and 10 x 75 mm test tubes. Each.....**\$0.60**

E. H. SARGENT & CO., 155-165 E. Superior St., Chicago, Ill.

**S A R G E N T**  
SCIENTIFIC LABORATORY SUPPLIES